



Description: UNITRONIC ROBUST C (TP) 4 x 2 x 0,5_

Lapp code: Lapp 1032121

The **Test voltage** of the cable Lapp 1032121 is At 0.14 mm²: 1200 V ? 0.25 mm²: 1500 V.

Application range

- Machine tool building, medical technology, laundries, car washing equipment, chemical industry, composting plants, sewage works
- Food and beverage industry, especially for production and processing equipment of milk and meat products
- For data processing, measurement and control engineering, safety related systems and as electronics cable
- For indoor and outdoor use

Product Make-up

- Fine-wire/multi-wire (0.34 mm²) strand made of bare copper wires
- Core insulation made of special halogen-free compound
- TP structure
- Tinned-copper braiding
- Outer sheath made of special TPE
Outer sheath colour: black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 1032121 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|---------------------------------------|--------------|---|---------------------|----------------------|----------------|
| UNITRONIC® ROBUST C (TP) | | | | | |
| UNITRONIC ROBUST C (TP) 2 x 2 x 0,14 | Lapp 1032100 | 2 x 2 x 0,14 | 5.3 | 16.1 | 31 |
| UNITRONIC ROBUST C (TP) 3 x 2 x 0,14 | Lapp 1032101 | 3 x 2 x 0,14 | 5.8 | 19.0 | 38 |
| UNITRONIC ROBUST C (TP) 4 x 2 x 0,14 | Lapp 1032102 | 4 x 2 x 0,14 | 6.2 | 23.1 | 46 |
| UNITRONIC ROBUST C (TP) 5 x 2 x 0,14 | Lapp 1032103 | 5 x 2 x 0,14 | 6.4 | 27.2 | 54 |
| UNITRONIC ROBUST C (TP) 6 x 2 x 0,14 | Lapp 1032104 | 6 x 2 x 0,14 | 7.1 | 31.3 | 63 |
| UNITRONIC ROBUST C (TP) 8 x 2 x 0,14 | Lapp 1032105 | 8 x 2 x 0,14 | 8.2 | 43.4 | 90 |
| UNITRONIC ROBUST C (TP) 10 x 2 x 0,14 | Lapp 1032106 | 10 x 2 x 0,14 | 8.7 | 50.9 | 93 |
| UNITRONIC ROBUST C (TP) 12 x 2 x 0,14 | Lapp 1032107 | 12 x 2 x 0,14 | 8.9 | 56.6 | 102 |
| UNITRONIC ROBUST C (TP) 2 x 2 x 0,25 | Lapp 1032108 | 2 x 2 x 0,25 | 6.3 | 22.7 | 43 |
| UNITRONIC ROBUST C (TP) 3 x 2 x 0,25 | Lapp 1032109 | 3 x 2 x 0,25 | 7.1 | 28.9 | 56 |
| UNITRONIC ROBUST C (TP) 4 x 2 x 0,25 | Lapp 1032110 | 4 x 2 x 0,25 | 7.6 | 38.3 | 72 |
| UNITRONIC ROBUST C (TP) 5 x 2 x 0,25 | Lapp 1032111 | 5 x 2 x 0,25 | 7.9 | 45.1 | 85 |
| UNITRONIC ROBUST C (TP) 6 x 2 x 0,25 | Lapp 1032112 | 6 x 2 x 0,25 | 8.5 | 48.7 | 96 |
| UNITRONIC ROBUST C (TP) 8 x 2 x 0,25 | Lapp 1032113 | 8 x 2 x 0,25 | 10.3 | 64.3 | 135 |
| UNITRONIC ROBUST C (TP) 2 x 2 x 0,34 | Lapp 1032114 | 2 x 2 x 0,34 | 7.1 | 27.6 | 56 |
| UNITRONIC ROBUST C (TP) 3 x 2 x 0,34 | Lapp 1032115 | 3 x 2 x 0,34 | 7.8 | 38.8 | 74 |
| UNITRONIC ROBUST C (TP) 4 x 2 x 0,34 | Lapp 1032116 | 4 x 2 x 0,34 | 8.4 | 47.5 | 90 |
| UNITRONIC ROBUST C (TP) 5 x 2 x 0,34 | Lapp 1032117 | 5 x 2 x 0,34 | 8.8 | 58.2 | 110 |
| UNITRONIC ROBUST C (TP) 1 x 2 x 0,5 | Lapp 1032118 | 1 x 2 x 0,5 | 4.9 | 20.1 | 37 |
| UNITRONIC ROBUST C (TP) 2 x 2 x 0,5 | Lapp 1032119 | 2 x 2 x 0,5 | 7.9 | 40.3 | 72 |
| UNITRONIC ROBUST C (TP) 3 x 2 x 0,5 | Lapp 1032120 | 3 x 2 x 0,5 | 8.7 | 51.7 | 91 |
| UNITRONIC ROBUST C (TP) 4 x 2 x 0,5 | Lapp 1032121 | 4 x 2 x 0,5 | 9.4 | 64.1 | 112 |
| UNITRONIC ROBUST C (TP) 5 x 2 x 0,5 | Lapp 1032122 | 5 x 2 x 0,5 | 10.3 | 76.6 | 141 |
| UNITRONIC ROBUST C (TP) 6 x 2 x 0,5 | Lapp 1032123 | 6 x 2 x 0,5 | 11.1 | 91.7 | 170 |

UNITRONIC ROBUST C (TP) 4 x 2 x 0,5_

Lapp 1032121



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--------------------------------------|--------------|---|---------------------|----------------------|----------------|
| UNITRONIC ROBUST C (TP) 8 x 2 x 0,5 | Lapp 1032124 | 8 x 2 x 0,5 | 13.1 | 123.2 | 238 |
| UNITRONIC ROBUST C (TP) 10 x 2 x 0,5 | Lapp 1032125 | 10 x 2 x 0,5 | 14.5 | 146.4 | 247 |
| UNITRONIC ROBUST C (TP) 2 x 2 x 0,75 | Lapp 1032126 | 2 x 2 x 0,75 | 8.5 | 48.4 | 84 |
| UNITRONIC ROBUST C (TP) 3 x 2 x 0,75 | Lapp 1032127 | 3 x 2 x 0,75 | 9.4 | 68.9 | 114 |
| UNITRONIC ROBUST C (TP) 4 x 2 x 0,75 | Lapp 1032128 | 4 x 2 x 0,75 | 10.7 | 86.2 | 149 |
| UNITRONIC ROBUST C (TP) 6 x 2 x 0,75 | Lapp 1032129 | 6 x 2 x 0,75 | 12.1 | 131.9 | 225 |
| UNITRONIC ROBUST C (TP) 8 x 2 x 0,75 | Lapp 1032130 | 8 x 2 x 0,75 | 14.7 | 168.2 | 315 |
| UNITRONIC ROBUST C (TP) 2 x 2 x 1 | Lapp 1032131 | 2 x 2 x 1 | 9.0 | 64.1 | 98 |
| UNITRONIC ROBUST C (TP) 3 x 2 x 1 | Lapp 1032132 | 3 x 2 x 1 | 10.4 | 83.5 | 135 |
| UNITRONIC ROBUST C (TP) 4 x 2 x 1 | Lapp 1032133 | 4 x 2 x 1 | 11.3 | 105.7 | 168 |