



Description: UNITRONIC ST 2 x AWG 20-7_

Lapp code: Lapp 0033000

The **Test voltage** of the cable Lapp 0033000 is 1500 V.

Application range

- Especially designed for the transmission of the smallest measurement and control signals at minimal space requirements
- Internal wiring of electronic equipment
- For fixed and limited flexible installation
- For use in dry, damp and wet rooms

Product Make-up

- 7-wire tinned stranded copper conductor
- Core insulation made of polyethylene (PE)
- Plastic-laminated aluminium foil with tinned copper drain wire
- Outer sheath made of PVC, Colour of the outer sheath: Similar to Silver-grey/ RAL 7001

In our Cable list on next page you can find all interesting information acc. article Lapp 0033000 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of conductors and AWG size | Conductor cross-section (mm ²) | Core insulation material | Outer sheath material | Outer diameter (mm) | Copper index (kg/km) |
|---------------------------|--------------|-----------------------------------|--|--------------------------|-----------------------|---------------------|----------------------|
| UNITRONIC® ST | | | | | | | |
| UNITRONIC ST 2 x AWG 20/7 | Lapp 0033000 | 2 x AWG 20/7 | 0,52 | PE | PVC | 5.2 | 17.2 |
| UNITRONIC ST 3 x AWG 20/7 | Lapp 0033001 | 3 x AWG 20/7 | 0,52 | PE | PVC | 5.3 | 23.0 |