



Description: UNITRONIC ST 3 x AWG 20-7_

Lapp code: Lapp 0033001

The **Test voltage** of the cable Lapp 0033001 is 1500 V.

Application range

- Especially designed for the transmission of the smallest measurement and control signals at minimal space requirements
- Internal wiring of electronic equipment
- For fixed and limited flexible installation
- For use in dry, damp and wet rooms

Product Make-up

- 7-wire tinned stranded copper conductor
- Core insulation made of polyethylene (PE)
- Plastic-laminated aluminium foil with tinned copper drain wire
- Outer sheath made of PVC, Colour of the outer sheath: Similar to Silver-grey/ RAL 7001

In our Cable list on next page you can find all interesting information acc. article Lapp 0033001 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of conductors and AWG size	Conductor cross-section (mm ²)	Core insulation material	Outer sheath material	Outer diameter (mm)	Copper index (kg/km)
UNITRONIC® ST							
UNITRONIC ST 2 x AWG 20/7	Lapp 0033000	2 x AWG 20/7	0,52	PE	PVC	5.2	17.2
UNITRONIC ST 3 x AWG 20/7	Lapp 0033001	3 x AWG 20/7	0,52	PE	PVC	5.3	23.0