



Description: X00V3-D Copper Earthing Cable 95_

Lapp code: Lapp 4571115

The **Test voltage** of the cable Lapp 4571115 is 1000 V.

Application range

- Provides protection during repairs
- For earthing in high-voltage power installations of power companies and railway systems
- For earthing devices and potential equalisation on machine parts and EDP systems
- For applications in cold environments

Product Make-up

- Strands of bare copper wires
- PVC-based outer sheath, transparent

In our Cable list on next page you can find all interesting information acc. article Lapp 4571115 and much more.

X00V3-D Copper Earthing Cable 95_

Lapp 4571115



CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Conductor cross-section (mm ²) | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|----------------------------------|--------------|--|---------------------|----------------------|----------------|
| X00V3-D Copper Earthing Cable 16 | Lapp 4571110 | 16 | 8,1 | 153.6 | 223 |
| X00V3-D Copper Earthing Cable 25 | Lapp 4571111 | 25 | 9,5 | 240.0 | 330 |
| X00V3-D Copper Earthing Cable 35 | Lapp 4571112 | 35 | 11.0 | 336.0 | 455 |
| X00V3-D Copper Earthing Cable 50 | Lapp 4571113 | 50 | 13,2 | 480.0 | 648 |
| X00V3-D Copper Earthing Cable 70 | Lapp 4571114 | 70 | 15,8 | 672.0 | 913 |
| X00V3-D Copper Earthing Cable 95 | Lapp 4571115 | 95 | 18,3 | 912.0 | 1234 |