



Description: ÖLFLEX 120 H 5 G 1,5_

Lapp code: Lapp 1021305

The **Test voltage** of the cable Lapp 1021305 is 4000 V.

Application range

- Public buildings
- Airport, railway station
- Plant engineering
Industrial machinery
Heating and air-conditioning systems
- Particularly where human and animal life as well as valuable property are exposed to high risk of fire hazards

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: Halogen-free
- Outer sheath made of special halogen-free compound, grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 1021305 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® 120 H U ₀ /U: 300/500 V					
ÖLFLEX 120 H 2 X 1,5	Lapp 1021902	2 X 1,5	6,3	29.0	63
ÖLFLEX 120 H 3 G 1,5	Lapp 1021303	3 G 1,5	6,7	43.0	79
ÖLFLEX 120 H 4 G 1,5	Lapp 1021304	4 G 1,5	7,2	58.0	98
ÖLFLEX 120 H 5 G 1,5	Lapp 1021305	5 G 1,5	8,1	72.0	120
ÖLFLEX 120 H 7 G 1,5	Lapp 1021307	7 G 1,5	8,9	101.0	158
ÖLFLEX 120 H 12 G 1,5	Lapp 1021312	12 G 1,5	12.0	173.0	265
ÖLFLEX 120 H 18 G 1,5	Lapp 1021318	18 G 1,5	14,4	259.0	388
ÖLFLEX 120 H 25 G 1,5	Lapp 1021325	25 G 1,5	16,9	360.0	535
ÖLFLEX 120 H 3 G 2,5	Lapp 1021403	3 G 2,5	8,1	72.0	124
ÖLFLEX 120 H 4 G 2,5	Lapp 1021404	4 G 2,5	8,9	96.0	154
ÖLFLEX 120 H 5 G 2,5	Lapp 1021405	5 G 2,5	10.0	120.0	189
ÖLFLEX 120 H 7 G 2,5	Lapp 1021407	7 G 2,5	11,1	168.0	254
ÖLFLEX 120 H 12 G 2,5	Lapp 1021412	12 G 2,5	14,8	288.0	425
ÖLFLEX 120 H 4 G 4	Lapp 1021504	4 G 4	10,8	154.0	236
ÖLFLEX 120 H 4 G 6	Lapp 1021604	4 G 6	13.0	230.0	350