



Description: ÖLFLEX 450 P 4 G 1,5_

Lapp code: Lapp 00122033

The **Test voltage** of the cable Lapp 00122033 is 3000 V.

Application range

- Portable handheld electrical devices such as drills, sanders, jig saws or grinders
- Power or extension cord
- Portable devices for the home and garden
- Outdoor use is possible within the indicated operating temperature range

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: Based on PVC
- Cores twisted together
- Inner sheath: PVC - colour red
- Outer sheath: PUR – colour yellow

In our Cable list on next page you can find all interesting information acc. article Lapp 00122033 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® 450 P					
ÖLFLEX 450 P 2 X 1,0	Lapp 0012101	2 X 1,0	8,0	19,2	82
ÖLFLEX 450 P 3 G 1,0	Lapp 0012102	3 G 1,0	8,4	29,0	89
ÖLFLEX 450 P 3 G 1,5	Lapp 0012202	3 G 1,5	9,3	43,0	120
ÖLFLEX 450 P 4 G 1,5	Lapp 00122033	4 G 1,5	10,1	58,0	160
ÖLFLEX 450 P 5 G 1,5	Lapp 00122043	5 G 1,5	10,9	72,0	179
ÖLFLEX 450 P 3 G 2,5	Lapp 0012302	3 G 2,5	10,8	72,0	186
ÖLFLEX 450 P 5 G 2,5	Lapp 00123043	5 G 2,5	13,6	120,0	283