



Description: ÖLFLEX 500 P 4 G 1,0_

Lapp code: Lapp 00123473

The **Test voltage** of the cable Lapp 00123473 is 3000 V.

Application range

- Portable handheld electrical devices such as drills, sanders, jig saws or grinders
- Portable devices for the home and garden
- Connection and extension cables

Product Make-up

- Extra-fine wire strand made of bare copper
- Core insulation: see data sheet
- Cores twisted together
- PUR outer sheath
- Sheath colour: orange

In our Cable list on next page you can find all interesting information acc. article Lapp 00123473 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|----------------------|---------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® 500 P | | | | | |
| ÖLFLEX 500 P 2 X 1,0 | Lapp 0012345 | 2 X 1,0 | 7,2 | 19.5 | 64 |
| ÖLFLEX 500 P 3 G 1,0 | Lapp 0012346 | 3 G 1,0 | 7,6 | 29.0 | 77 |
| ÖLFLEX 500 P 4 G 1,0 | Lapp 00123473 | 4 G 1,0 | 8,5 | 38.4 | 96 |
| ÖLFLEX 500 P 5 G 1,0 | Lapp 00123483 | 5 G 1,0 | 9,2 | 48.0 | 120 |
| ÖLFLEX 500 P 2 X 1,5 | Lapp 0012351 | 2 X 1,5 | 8.0 | 29.0 | 81 |
| ÖLFLEX 500 P 3 G 1,5 | Lapp 0012352 | 3 G 1,5 | 8,7 | 43.0 | 105.3 |
| ÖLFLEX 500 P 4 G 1,5 | Lapp 00123543 | 4 G 1,5 | 9,6 | 58.0 | 135 |
| ÖLFLEX 500 P 5 G 1,5 | Lapp 00123533 | 5 G 1,5 | 10,8 | 72.0 | 158.9 |
| ÖLFLEX 500 P 3 G 2,5 | Lapp 0012365 | 3 G 2,5 | 10,9 | 72.0 | 173.2 |
| ÖLFLEX 500 P 4 G 2,5 | Lapp 00123553 | 4 G 2,5 | 11,9 | 96.0 | 204 |
| ÖLFLEX 500 P 5 G 2,5 | Lapp 00123663 | 5 G 2,5 | 13,2 | 120.0 | 254 |