



Description: ÖLFLEX 500 P 5 G 1,5_

Lapp code: Lapp 00123533

The **Test voltage** of the cable Lapp 00123533 is 3000 V.

Application range

- Portable handheld electrical devices such as drills, sanders, jig saws or grinders
- Portable devices for the home and garden
- Connection and extension cables

Product Make-up

- Extra-fine wire strand made of bare copper
- Core insulation: see data sheet
- Cores twisted together
- PUR outer sheath
- Sheath colour: orange

In our Cable list on next page you can find all interesting information acc. article Lapp 00123533 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® 500 P					
ÖLFLEX 500 P 2 X 1,0	Lapp 0012345	2 X 1,0	7,2	19.5	64
ÖLFLEX 500 P 3 G 1,0	Lapp 0012346	3 G 1,0	7,6	29.0	77
ÖLFLEX 500 P 4 G 1,0	Lapp 00123473	4 G 1,0	8,5	38.4	96
ÖLFLEX 500 P 5 G 1,0	Lapp 00123483	5 G 1,0	9,2	48.0	120
ÖLFLEX 500 P 2 X 1,5	Lapp 0012351	2 X 1,5	8.0	29.0	81
ÖLFLEX 500 P 3 G 1,5	Lapp 0012352	3 G 1,5	8,7	43.0	105.3
ÖLFLEX 500 P 4 G 1,5	Lapp 00123543	4 G 1,5	9,6	58.0	135
ÖLFLEX 500 P 5 G 1,5	Lapp 00123533	5 G 1,5	10,8	72.0	158.9
ÖLFLEX 500 P 3 G 2,5	Lapp 0012365	3 G 2,5	10,9	72.0	173.2
ÖLFLEX 500 P 4 G 2,5	Lapp 00123553	4 G 2,5	11,9	96.0	204
ÖLFLEX 500 P 5 G 2,5	Lapp 00123663	5 G 2,5	13,2	120.0	254