



Description: ÖLFLEX 540 CP 2 X 1,0_

Lapp code: Lapp 0012757

The **Test voltage** of the cable Lapp 0012757 is 3000 V.

Application range

- Connection and extension cables
- Construction machinery
- Building sites, camp sites, stage applications
- Agricultural equipment
- For indoor and outdoor use

Product Make-up

- Fine-wire, tinned-copper conductor
- Core insulation: TPE
- Cores twisted together
- Inner sheath made of TPE
- Tinned copper screen braiding
- Outer sheath: PUR – colour yellow

In our Cable list on next page you can find all interesting information acc. article Lapp 0012757 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|---|---------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® 540 CP U ₀ /U: 300/500 V | | | | | |
| ÖLFLEX 540 CP 2 X 0,75 | Lapp 0012752 | 2 X 0,75 | 8,2 | 43.9 | 103 |
| ÖLFLEX 540 CP 3 G 0,75 | Lapp 0012753 | 3 G 0,75 | 8,5 | 67.6 | 140 |
| ÖLFLEX 540 CP 5 G 0,75 | Lapp 00127553 | 5 G 0,75 | 10,2 | 75.0 | 164 |
| ÖLFLEX 540 CP 2 X 1,0 | Lapp 0012757 | 2 X 1,0 | 8,5 | 65.2 | 138 |
| ÖLFLEX 540 CP 3 G 1,0 | Lapp 0012758 | 3 G 1,0 | 9,3 | 74.9 | 153 |
| ÖLFLEX 540 CP 5 G 1,0 | Lapp 00127603 | 5 G 1,0 | 10,8 | 87.2 | 184 |
| ÖLFLEX 540 CP 7 G 1,0 | Lapp 0012761 | 7 G 1,0 | 12,6 | 138.5 | 281 |
| ÖLFLEX® 540 CP U ₀ /U: 450/750 V | | | | | |
| ÖLFLEX 540 CP 2 X 1,5 | Lapp 0012762 | 2 X 1,5 | 10,5 | 67.7 | 159 |
| ÖLFLEX 540 CP 3 G 1,5 | Lapp 0012763 | 3 G 1,5 | 11.0 | 82.3 | 181 |
| ÖLFLEX 540 CP 4 G 1,5 | Lapp 00127643 | 4 G 1,5 | 12.0 | 101.8 | 218 |
| ÖLFLEX 540 CP 5 G 1,5 | Lapp 00127653 | 5 G 1,5 | 13,7 | 143.3 | 287 |
| ÖLFLEX 540 CP 7 G 1,5 | Lapp 0012766 | 7 G 1,5 | 16,6 | 195.7 | 394 |
| ÖLFLEX 540 CP 2 X 2,5 | Lapp 0012767 | 2 X 2,5 | 11,9 | 92.4 | 213 |
| ÖLFLEX 540 CP 3 G 2,5 | Lapp 0012768 | 3 G 2,5 | 12,5 | 119.0 | 263 |
| ÖLFLEX 540 CP 4 G 2,5 | Lapp 00127693 | 4 G 2,5 | 14,2 | 168.2 | 334 |
| ÖLFLEX 540 CP 5 G 2,5 | Lapp 00127703 | 5 G 2,5 | 15,7 | 204.7 | 416 |
| ÖLFLEX 540 CP 4 G 4 | Lapp 00127753 | 4 G 4 | 17.0 | 240.1 | 476 |
| ÖLFLEX 540 CP 4 G 6 | Lapp 00127783 | 4 G 6 | 18,4 | 355.5 | 634 |
| ÖLFLEX 540 CP 5 G 6 | Lapp 00127793 | 5 G 6 | 20,5 | 452.9 | 770 |
| ÖLFLEX 540 CP 4 G 10 | Lapp 00127813 | 4 G 10 | 22,3 | 577.8 | 993 |
| ÖLFLEX 540 CP 5 G 10 | Lapp 00127823 | 5 G 10 | 25,3 | 681.2 | 1151 |