



**Description:** ÖLFLEX 540 P 4 G 4\_  
**Lapp code:** Lapp 00124753

The **Test voltage** of the cable Lapp 00124753 is 3000 V.

## Application range

- Connection and extension cables
- Construction machinery
- Building sites, camp sites, stage applications
- Agricultural equipment
- For indoor and outdoor use

## Product Make-up

- Fine-wire, tinned-copper conductor
- Core insulation: TPE
- Cores twisted together
- Outer sheath: PUR – colour yellow
- Other sheath colours are available upon request

In our Cable list on next page you can find all interesting information acc. article Lapp 00124753 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® 540 P U <sub>0</sub> /U: 300/500 V					
ÖLFLEX 540 P 2 X 0,75	Lapp 0012452	2 X 0,75	6,2	14.4	52
ÖLFLEX 540 P 3 G 0,75	Lapp 0012453	3 G 0,75	6,7	21.6	63
ÖLFLEX 540 P 4 G 0,75	Lapp 00124543	4 G 0,75	7,3	28.8	80
ÖLFLEX 540 P 5 G 0,75	Lapp 00124553	5 G 0,75	8,2	36.0	98
ÖLFLEX 540 P 7 G 0,75	Lapp 0012456	7 G 0,75	9,9	51.0	126
ÖLFLEX 540 P 2 X 1,0	Lapp 0012457	2 X 1,0	6,7	19.2	53
ÖLFLEX 540 P 3 G 1,0	Lapp 0012458	3 G 1,0	7,1	29.0	72
ÖLFLEX 540 P 4 G 1,0	Lapp 00124593	4 G 1,0	7,7	38.4	96
ÖLFLEX 540 P 5 G 1,0	Lapp 00124603	5 G 1,0	8,6	48.0	117
ÖLFLEX 540 P 7 G 1,0	Lapp 0012461	7 G 1,0	10,4	68.0	147
ÖLFLEX® 540 P U <sub>0</sub> /U: 450/750 V					
ÖLFLEX 540 P 2 X 1,5	Lapp 0012462	2 X 1,5	8,3	29.0	82
ÖLFLEX 540 P 3 G 1,5	Lapp 0012463	3 G 1,5	8,8	43.0	108
ÖLFLEX 540 P 4 G 1,5	Lapp 00124643	4 G 1,5	9,8	58.0	147
ÖLFLEX 540 P 5 G 1,5	Lapp 00124653	5 G 1,5	10,7	72.0	164
ÖLFLEX 540 P 7 G 1,5	Lapp 0012466	7 G 1,5	13,4	101.0	267
ÖLFLEX 540 P 2 X 2,5	Lapp 0012467	2 X 2,5	9,7	48.0	142
ÖLFLEX 540 P 3 G 2,5	Lapp 0012468	3 G 2,5	10,3	72.0	161
ÖLFLEX 540 P 4 G 2,5	Lapp 00124693	4 G 2,5	11,4	96.0	220
ÖLFLEX 540 P 5 G 2,5	Lapp 00124703	5 G 2,5	12,7	120.0	245
ÖLFLEX 540 P 7 G 2,5	Lapp 0012471	7 G 2,5	15,8	168.0	321
ÖLFLEX 540 P 3 G 4	Lapp 0012474	3 G 4	12,3	115.2	262
ÖLFLEX 540 P 4 G 4	Lapp 00124753	4 G 4	13,6	154.0	284
ÖLFLEX 540 P 5 G 4	Lapp 00124763	5 G 4	15,2	192.0	355
ÖLFLEX 540 P 4 G 6	Lapp 00124783	4 G 6	15,4	230.0	440
ÖLFLEX 540 P 5 G 6	Lapp 00124793	5 G 6	17,1	288.0	530
ÖLFLEX 540 P 4 G 10	Lapp 00124813	4 G 10	20,1	384.0	615
ÖLFLEX 540 P 5 G 10	Lapp 00124823	5 G 10	22,3	480.0	735