



**Description:** ÖLFLEX 540 P 7 G 0,75\_

**Lapp code:** Lapp 0012456

The **Test voltage** of the cable Lapp 0012456 is 3000 V.

## Application range

- Connection and extension cables
- Construction machinery
- Building sites, camp sites, stage applications
- Agricultural equipment
- For indoor and outdoor use

## Product Make-up

- Fine-wire, tinned-copper conductor
- Core insulation: TPE
- Cores twisted together
- Outer sheath: PUR – colour yellow
- Other sheath colours are available upon request

In our Cable list on next page you can find all interesting information acc. article Lapp 0012456 and much more.

CABLE LIST - all informations you need you can find here

| Product Name                               | Lapp Nr.      | Number of cores and mm <sup>2</sup> per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--|---------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® 540 P U <sub>0</sub> /U: 300/500 V |               |   |                     |                      |                |
| ÖLFLEX 540 P 2 X 0,75                      | Lapp 0012452  | 2 X 0,75  | 6,2                 | 14.4                 | 52             |
| ÖLFLEX 540 P 3 G 0,75                      | Lapp 0012453  | 3 G 0,75  | 6,7                 | 21.6                 | 63             |
| ÖLFLEX 540 P 4 G 0,75                      | Lapp 00124543 | 4 G 0,75  | 7,3                 | 28.8                 | 80             |
| ÖLFLEX 540 P 5 G 0,75                      | Lapp 00124553 | 5 G 0,75  | 8,2                 | 36.0                 | 98             |
| ÖLFLEX 540 P 7 G 0,75                      | Lapp 0012456  | 7 G 0,75  | 9,9                 | 51.0                 | 126            |
| ÖLFLEX 540 P 2 X 1,0                       | Lapp 0012457  | 2 X 1,0   | 6,7                 | 19.2                 | 53             |
| ÖLFLEX 540 P 3 G 1,0                       | Lapp 0012458  | 3 G 1,0   | 7,1                 | 29.0                 | 72             |
| ÖLFLEX 540 P 4 G 1,0                       | Lapp 00124593 | 4 G 1,0   | 7,7                 | 38.4                 | 96             |
| ÖLFLEX 540 P 5 G 1,0                       | Lapp 00124603 | 5 G 1,0   | 8,6                 | 48.0                 | 117            |
| ÖLFLEX 540 P 7 G 1,0                       | Lapp 0012461  | 7 G 1,0   | 10,4                | 68.0                 | 147            |
| ÖLFLEX® 540 P U <sub>0</sub> /U: 450/750 V |               |   |                     |                      |                |
| ÖLFLEX 540 P 2 X 1,5                       | Lapp 0012462  | 2 X 1,5   | 8,3                 | 29.0                 | 82             |
| ÖLFLEX 540 P 3 G 1,5                       | Lapp 0012463  | 3 G 1,5   | 8,8                 | 43.0                 | 108            |
| ÖLFLEX 540 P 4 G 1,5                       | Lapp 00124643 | 4 G 1,5   | 9,8                 | 58.0                 | 147            |
| ÖLFLEX 540 P 5 G 1,5                       | Lapp 00124653 | 5 G 1,5   | 10,7                | 72.0                 | 164            |
| ÖLFLEX 540 P 7 G 1,5                       | Lapp 0012466  | 7 G 1,5   | 13,4                | 101.0                | 267            |
| ÖLFLEX 540 P 2 X 2,5                       | Lapp 0012467  | 2 X 2,5   | 9,7                 | 48.0                 | 142            |
| ÖLFLEX 540 P 3 G 2,5                       | Lapp 0012468  | 3 G 2,5   | 10,3                | 72.0                 | 161            |
| ÖLFLEX 540 P 4 G 2,5                       | Lapp 00124693 | 4 G 2,5   | 11,4                | 96.0                 | 220            |
| ÖLFLEX 540 P 5 G 2,5                       | Lapp 00124703 | 5 G 2,5   | 12,7                | 120.0                | 245            |
| ÖLFLEX 540 P 7 G 2,5                       | Lapp 0012471  | 7 G 2,5   | 15,8                | 168.0                | 321            |
| ÖLFLEX 540 P 3 G 4                         | Lapp 0012474  | 3 G 4   | 12,3                | 115.2                | 262            |
| ÖLFLEX 540 P 4 G 4                         | Lapp 00124753 | 4 G 4   | 13,6                | 154.0                | 284            |
| ÖLFLEX 540 P 5 G 4                         | Lapp 00124763 | 5 G 4   | 15,2                | 192.0                | 355            |
| ÖLFLEX 540 P 4 G 6                         | Lapp 00124783 | 4 G 6   | 15,4                | 230.0                | 440            |
| ÖLFLEX 540 P 5 G 6                         | Lapp 00124793 | 5 G 6   | 17,1                | 288.0                | 530            |
| ÖLFLEX 540 P 4 G 10                        | Lapp 00124813 | 4 G 10  | 20,1                | 384.0                | 615            |
| ÖLFLEX 540 P 5 G 10                        | Lapp 00124823 | 5 G 10  | 22,3                | 480.0                | 735            |