



**Description:** ÖLFLEX 550 P\* 5 G 2,5\_

**Lapp code:** Lapp 00136333

The **Test voltage** of the cable Lapp 00136333 is 3000 V.

## Application range

- Portable handheld electrical devices such as drills, sanders, jig saws or grinders
- Building sites, camp sites, stage applications
- Construction machinery
- Agricultural equipment
- For indoor and outdoor use

## Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: rubber compound
- Cores twisted together
- PUR outer sheath
- Sheath colour: orange

In our Cable list on next page you can find all interesting information acc. article Lapp 00136333 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® 550 P U <sub>0</sub> /U: 300/500 V					
ÖLFLEX 550 P* 2 X 0,75	Lapp 0013600	2 X 0,75	5,7 - 7,4	14.4	50
ÖLFLEX 550 P* 3 G 0,75	Lapp 0013601	3 G 0,75	6,2 - 8,1	21.6	64
ÖLFLEX 550 P* 4 G 0,75	Lapp 00136023	4 G 0,75	6,8 - 8,8	28.8	78
ÖLFLEX 550 P* 5 G 0,75	Lapp 00136033	5 G 0,75	7,6 - 9,9	36.0	98
ÖLFLEX 550 P* 2 X 1,0	Lapp 0013610	2 X 1,0	6,1 - 8	19.2	60
ÖLFLEX 550 P* 3 G 1,0	Lapp 0013611	3 G 1,0	6,5 - 8,5	29.0	74
ÖLFLEX 550 P* 4 G 1,0	Lapp 00136123	4 G 1,0	7,1 - 9,3	38.4	92
ÖLFLEX 550 P* 5 G 1,0	Lapp 00136133	5 G 1,0	8 - 10,3	48.0	114
ÖLFLEX® 550 P U <sub>0</sub> /U: 450/750 V					
ÖLFLEX 550 P* 2 X 1,5	Lapp 0013620	2 X 1,5	7,6 - 9,8	29.0	87
ÖLFLEX 550 P* 3 G 1,5	Lapp 0013621	3 G 1,5	8 - 10,4	43.0	108
ÖLFLEX 550 P* 4 G 1,5	Lapp 00136223	4 G 1,5	9 - 11,6	58.0	137
ÖLFLEX 550 P* 5 G 1,5	Lapp 00136233	5 G 1,5	9,8 - 12,7	72.0	165
ÖLFLEX 550 P* 2 X 2,5	Lapp 0013630	2 X 2,5	9 - 11,6	48.0	90
ÖLFLEX 550 P* 3 G 2,5	Lapp 0013631	3 G 2,5	9,6 - 12,4	72.0	161
ÖLFLEX 550 P* 4 G 2,5	Lapp 00136323	4 G 2,5	10,7 - 13,8	96.0	206
ÖLFLEX 550 P* 5 G 2,5	Lapp 00136333	5 G 2,5	11,9 - 16,3	120.0	254