



Description: ÖLFLEX CHAIN 808 CP 3 G 0,5_

Lapp code: Lapp 1027752

The **Test voltage** of the cable Lapp 1027752 is Core/core: 4000 V Core/screen: 2000 V.

Application range

- In power chains or moving machine parts
- In EMC-sensitive environments
- Particularly in wet areas of machine tools and transfer lines
- Suitable for use in measuring, control and regulating circuits
- In dry, damp or wet interiors

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: PVC
- Cores twisted in layers
- Non-woven wrapping
- Tinned-copper braiding
- PUR outer sheath, grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 1027752 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CHAIN 808 CP					
ÖLFLEX CHAIN 808 CP 2 X 0,5	Lapp 1027751	2 X 0,5	5.8	36.0	45
ÖLFLEX CHAIN 808 CP 3 G 0,5	Lapp 1027752	3 G 0,5	6.1	43.0	59
ÖLFLEX CHAIN 808 CP 4 G 0,5	Lapp 1027753	4 G 0,5	6.6	49.0	83
ÖLFLEX CHAIN 808 CP 5 G 0,5	Lapp 1027754	5 G 0,5	7.1	57.0	96
ÖLFLEX CHAIN 808 CP 7 G 0,5	Lapp 1027755	7 G 0,5	8.5	69.0	136
ÖLFLEX CHAIN 808 CP 12 G 0,5	Lapp 1027756	12 G 0,5	10.0	104.0	200
ÖLFLEX CHAIN 808 CP 18 G 0,5	Lapp 1027757	18 G 0,5	11.8	141.0	275
ÖLFLEX CHAIN 808 CP 25 G 0,5	Lapp 1027758	25 G 0,5	14.1	211.0	350
ÖLFLEX CHAIN 808 CP 2 X 0,75	Lapp 1027759	2 X 0,75	6.2	43.0	56
ÖLFLEX CHAIN 808 CP 3 G 0,75	Lapp 1027760	3 G 0,75	6.6	52.0	70
ÖLFLEX CHAIN 808 CP 4 G 0,75	Lapp 1027761	4 G 0,75	7.1	61.0	95
ÖLFLEX CHAIN 808 CP 5 G 0,75	Lapp 1027762	5 G 0,75	7.7	72.0	130
ÖLFLEX CHAIN 808 CP 7 G 0,75	Lapp 1027763	7 G 0,75	9.1	89.0	168
ÖLFLEX CHAIN 808 CP 12 G 0,75	Lapp 1027764	12 G 0,75	10.9	138.0	232
ÖLFLEX CHAIN 808 CP 18 G 0,75	Lapp 1027765	18 G 0,75	13.0	211.0	315
ÖLFLEX CHAIN 808 CP 25 G 0,75	Lapp 1027766	25 G 0,75	15.6	280.0	435
ÖLFLEX CHAIN 808 CP 2 X 1,0	Lapp 1027767	2 X 1,0	6.5	51.0	84
ÖLFLEX CHAIN 808 CP 3 G 1,0	Lapp 1027768	3 G 1,0	6.9	62.0	110
ÖLFLEX CHAIN 808 CP 4 G 1,0	Lapp 1027769	4 G 1,0	7.5	74.0	130
ÖLFLEX CHAIN 808 CP 5 G 1,0	Lapp 1027770	5 G 1,0	8.3	88.0	156
ÖLFLEX CHAIN 808 CP 7 G 1,0	Lapp 1027771	7 G 1,0	9.8	112.0	192
ÖLFLEX CHAIN 808 CP 12 G 1,0	Lapp 1027772	12 G 1,0	11.7	185.0	285
ÖLFLEX CHAIN 808 CP 18 G 1,0	Lapp 1027773	18 G 1,0	14.0	268.0	395
ÖLFLEX CHAIN 808 CP 25 G 1,0	Lapp 1027774	25 G 1,0	16.7	354.0	656

ÖLFLEX CHAIN 808 CP 3 G 0,5_

Lapp 1027752



Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX CHAIN 808 CP 2 X 1,5	Lapp 1027775	2 X 1,5	7.1	65.0	97
ÖLFLEX CHAIN 808 CP 3 G 1,5	Lapp 1027776	3 G 1,5	7.5	82.0	125
ÖLFLEX CHAIN 808 CP 4 G 1,5	Lapp 1027777	4 G 1,5	8.4	100.0	165
ÖLFLEX CHAIN 808 CP 5 G 1,5	Lapp 1027778	5 G 1,5	9.1	119.0	193
ÖLFLEX CHAIN 808 CP 7 G 1,5	Lapp 1027779	7 G 1,5	10.9	154.0	245
ÖLFLEX CHAIN 808 CP 12 G 1,5	Lapp 1027780	12 G 1,5	13.3	268.0	365
ÖLFLEX CHAIN 808 CP 18 G 1,5	Lapp 1027781	18 G 1,5	15.7	373.0	553
ÖLFLEX CHAIN 808 CP 25 G 1,5	Lapp 1027782	25 G 1,5	18.7	530.0	734
ÖLFLEX CHAIN 808 CP 3 G 2,5	Lapp 1027783	3 G 2,5	9.0	118.0	188
ÖLFLEX CHAIN 808 CP 4 G 2,5	Lapp 1027784	4 G 2,5	10.1	147.0	236
ÖLFLEX CHAIN 808 CP 7 G 2,5	Lapp 1027785	7 G 2,5	13.5	253.0	340
ÖLFLEX CHAIN 808 CP 4 G 4	Lapp 1027788	4 G 4	11.9	248.0	305