



**Description:** ÖLFLEX CHAIN 808 P 7 G 2,5\_

**Lapp code:** Lapp 1027734

The **Test voltage** of the cable Lapp 1027734 is Core/core: 4000 V.

## Application range

- Assembly lines, production lines, in all kinds of machines
- In dry, damp or wet interiors
- In power chains or moving machine parts
- Particularly in wet areas of machine tools and transfer lines
- Suitable for use in measuring, control and regulating circuits

## Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: PVC
- Cores twisted in layers
- Non-woven wrapping
- PUR outer sheath, grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 1027734 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CHAIN 808 P					
ÖLFLEX CHAIN 808 P 2 X 0,5	Lapp 1027700	2 X 0,5	5.2	10.0	40
ÖLFLEX CHAIN 808 P 3 G 0,5	Lapp 1027701	3 G 0,5	5.5	15.0	48
ÖLFLEX CHAIN 808 P 4 G 0,5	Lapp 1027702	4 G 0,5	6.0	20.0	58
ÖLFLEX CHAIN 808 P 5 G 0,5	Lapp 1027703	5 G 0,5	6.5	24.0	67
ÖLFLEX CHAIN 808 P 7 G 0,5	Lapp 1027704	7 G 0,5	7.7	34.0	88
ÖLFLEX CHAIN 808 P 12 G 0,5	Lapp 1027705	12 G 0,5	9.2	58.0	136
ÖLFLEX CHAIN 808 P 18 G 0,5	Lapp 1027706	18 G 0,5	11.0	87.0	195
ÖLFLEX CHAIN 808 P 25 G 0,5	Lapp 1027707	25 G 0,5	13.3	120.0	274
ÖLFLEX CHAIN 808 P 2 X 0,75	Lapp 1027708	2 X 0,75	5.6	15.0	49
ÖLFLEX CHAIN 808 P 3 G 0,75	Lapp 1027709	3 G 0,75	6.0	22.0	60
ÖLFLEX CHAIN 808 P 4 G 0,75	Lapp 1027710	4 G 0,75	6.5	29.0	73
ÖLFLEX CHAIN 808 P 5 G 0,75	Lapp 1027711	5 G 0,75	7.1	37.0	86
ÖLFLEX CHAIN 808 P 7 G 0,75	Lapp 1027712	7 G 0,75	8.5	51.0	117
ÖLFLEX CHAIN 808 P 12 G 0,75	Lapp 1027713	12 G 0,75	10.3	87.0	181
ÖLFLEX CHAIN 808 P 18 G 0,75	Lapp 1027714	18 G 0,75	12.2	130.0	259
ÖLFLEX CHAIN 808 P 25 G 0,75	Lapp 1027715	25 G 0,75	14.8	181.0	363
ÖLFLEX CHAIN 808 P 2 X 1,0	Lapp 1027716	2 X 1,0	5.9	19.0	58
ÖLFLEX CHAIN 808 P 3 G 1,0	Lapp 1027717	3 G 1,0	6.3	29.0	72
ÖLFLEX CHAIN 808 P 4 G 1,0	Lapp 1027718	4 G 1,0	6.9	39.0	88
ÖLFLEX CHAIN 808 P 5 G 1,0	Lapp 1027719	5 G 1,0	7.5	48.0	104
ÖLFLEX CHAIN 808 P 7 G 1,0	Lapp 1027720	7 G 1,0	9.0	67.0	142
ÖLFLEX CHAIN 808 P 12 G 1,0	Lapp 1027721	12 G 1,0	10.9	115.0	221
ÖLFLEX CHAIN 808 P 18 G 1,0	Lapp 1027722	18 G 1,0	13.2	173.0	324
ÖLFLEX CHAIN 808 P 25 G 1,0	Lapp 1027723	25 G 1,0	15.7	240.0	445

**ÖLFLEX CHAIN 808 P 7 G 2,5\_**

Lapp 1027734



Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX CHAIN 808 P 2 X 1,5	Lapp 1027724	2 X 1,5	6.5	29.0	74
ÖLFLEX CHAIN 808 P 3 G 1,5	Lapp 1027725	3 G 1,5	6.9	43.2	93
ÖLFLEX CHAIN 808 P 4 G 1,5	Lapp 1027726	4 G 1,5	7.6	58.0	114
ÖLFLEX CHAIN 808 P 5 G 1,5	Lapp 1027727	5 G 1,5	8.5	72.0	139
ÖLFLEX CHAIN 808 P 7 G 1,5	Lapp 1027728	7 G 1,5	10.3	101.0	189
ÖLFLEX CHAIN 808 P 12 G 1,5	Lapp 1027729	12 G 1,5	12.3	173.0	295
ÖLFLEX CHAIN 808 P 18 G 1,5	Lapp 1027730	18 G 1,5	14.9	259.0	429
ÖLFLEX CHAIN 808 P 25 G 1,5	Lapp 1027731	25 G 1,5	17.9	360.0	597
ÖLFLEX CHAIN 808 P 3 G 2,5	Lapp 1027732	3 G 2,5	8.4	72.0	145
ÖLFLEX CHAIN 808 P 4 G 2,5	Lapp 1027733	4 G 2,5	9.3	96.0	179
ÖLFLEX CHAIN 808 P 7 G 2,5	Lapp 1027734	7 G 2,5	12.7	168.0	218
ÖLFLEX CHAIN 808 P 4 G 4	Lapp 1027737	4 G 4	11.1	160.0	266