



Description: ÖLFLEX CHAIN 809 7 G 1,5_

Lapp code: Lapp 1026728

The **Test voltage** of the cable Lapp 1026728 is 4000 V.

Application range

- In power chains or moving machine parts
- In dry, damp or wet interiors
- Suitable for use in measuring, control and regulating circuits
- Wiring of machines, tools, devices, appliances and control cabinets
- Only for outdoor use within the indicated operating temperature range, with UV-protection

Product Make-up

- Fine-wire, bare copper strand
- Core insulation: PVC
- Cores twisted in layers
- Non-woven wrapping
- PVC outer sheath, grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 1026728 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|----------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® CHAIN 809 | | | | | |
| ÖLFLEX CHAIN 809 2 X 0,5 | Lapp 1026700 | 2 X 0,5 | 5.2 | 10.0 | 40 |
| ÖLFLEX CHAIN 809 3 G 0,5 | Lapp 1026701 | 3 G 0,5 | 5.5 | 15.0 | 48 |
| ÖLFLEX CHAIN 809 4 G 0,5 | Lapp 1026702 | 4 G 0,5 | 6.0 | 20.0 | 58 |
| ÖLFLEX CHAIN 809 5 G 0,5 | Lapp 1026703 | 5 G 0,5 | 6.5 | 24.0 | 67 |
| ÖLFLEX CHAIN 809 7 G 0,5 | Lapp 1026704 | 7 G 0,5 | 7.7 | 34.0 | 88 |
| ÖLFLEX CHAIN 809 12 G 0,5 | Lapp 1026705 | 12 G 0,5 | 9.2 | 58.0 | 136 |
| ÖLFLEX CHAIN 809 18 G 0,5 | Lapp 1026706 | 18 G 0,5 | 11.0 | 87.0 | 195 |
| ÖLFLEX CHAIN 809 25 G 0,5 | Lapp 1026707 | 25 G 0,5 | 13.3 | 120.0 | 274 |
| ÖLFLEX CHAIN 809 2 X 0,75 | Lapp 1026708 | 2 X 0,75 | 5.6 | 15.0 | 49 |
| ÖLFLEX CHAIN 809 3 G 0,75 | Lapp 1026709 | 3 G 0,75 | 6.0 | 22.0 | 60 |
| ÖLFLEX CHAIN 809 4 G 0,75 | Lapp 1026710 | 4 G 0,75 | 6.5 | 29.0 | 73 |
| ÖLFLEX CHAIN 809 5 G 0,75 | Lapp 1026711 | 5 G 0,75 | 7.1 | 37.0 | 86 |
| ÖLFLEX CHAIN 809 7 G 0,75 | Lapp 1026712 | 7 G 0,75 | 8.5 | 51.0 | 117 |
| ÖLFLEX CHAIN 809 12 G 0,75 | Lapp 1026713 | 12 G 0,75 | 10.3 | 87.0 | 181 |
| ÖLFLEX CHAIN 809 18 G 0,75 | Lapp 1026714 | 18 G 0,75 | 12.2 | 130.0 | 259 |
| ÖLFLEX CHAIN 809 25 G 0,75 | Lapp 1026715 | 25 G 0,75 | 14.8 | 181.0 | 363 |
| ÖLFLEX CHAIN 809 2 X 1,0 | Lapp 1026716 | 2 X 1,0 | 5.9 | 19.0 | 58 |
| ÖLFLEX CHAIN 809 3 G 1,0 | Lapp 1026717 | 3 G 1,0 | 6.3 | 29.0 | 72 |
| ÖLFLEX CHAIN 809 4 G 1,0 | Lapp 1026718 | 4 G 1,0 | 6.9 | 39.0 | 88 |
| ÖLFLEX CHAIN 809 5 G 1,0 | Lapp 1026719 | 5 G 1,0 | 7.5 | 48.0 | 104 |
| ÖLFLEX CHAIN 809 7 G 1,0 | Lapp 1026720 | 7 G 1,0 | 9.0 | 67.0 | 142 |
| ÖLFLEX CHAIN 809 12 G 1,0 | Lapp 1026721 | 12 G 1,0 | 10.9 | 115.0 | 221 |
| ÖLFLEX CHAIN 809 18 G 1,0 | Lapp 1026722 | 18 G 1,0 | 13.2 | 173.0 | 324 |
| ÖLFLEX CHAIN 809 25 G 1,0 | Lapp 1026723 | 25 G 1,0 | 15.7 | 240.0 | 445 |

ÖLFLEX CHAIN 809 7 G 1,5_

Lapp 1026728



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|---------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX CHAIN 809 2 X 1,5 | Lapp 1026724 | 2 X 1,5 | 6.5 | 29.0 | 74 |
| ÖLFLEX CHAIN 809 3 G 1,5 | Lapp 1026725 | 3 G 1,5 | 6.9 | 43.2 | 93 |
| ÖLFLEX CHAIN 809 4 G 1,5 | Lapp 1026726 | 4 G 1,5 | 7.6 | 58.0 | 114 |
| ÖLFLEX CHAIN 809 5 G 1,5 | Lapp 1026727 | 5 G 1,5 | 8.5 | 72.0 | 139 |
| ÖLFLEX CHAIN 809 7 G 1,5 | Lapp 1026728 | 7 G 1,5 | 10.3 | 101.0 | 189 |
| ÖLFLEX CHAIN 809 12 G 1,5 | Lapp 1026729 | 12 G 1,5 | 12.3 | 173.0 | 295 |
| ÖLFLEX CHAIN 809 18 G 1,5 | Lapp 1026730 | 18 G 1,5 | 14.9 | 259.0 | 429 |
| ÖLFLEX CHAIN 809 25 G 1,5 | Lapp 1026731 | 25 G 1,5 | 17.9 | 360.0 | 597 |
| ÖLFLEX CHAIN 809 3 G 2,5 | Lapp 1026732 | 3 G 2,5 | 8.4 | 72.0 | 145 |
| ÖLFLEX CHAIN 809 4 G 2,5 | Lapp 1026733 | 4 G 2,5 | 9.3 | 96.0 | 179 |
| ÖLFLEX CHAIN 809 7 G 2,5 | Lapp 1026734 | 7 G 2,5 | 12.7 | 168.0 | 218 |
| ÖLFLEX CHAIN 809 4 G 4 | Lapp 1026737 | 4 G 4 | 11.1 | 160.0 | 266 |