



Description: ÖLFLEX CHAIN 809 CY 4 G 1,0_

Lapp code: Lapp 1026769

The **Test voltage** of the cable Lapp 1026769 is Core/core: 4000 V Core/screen: 2000 V.

Application range

- In power chains or moving machine parts
- In EMC-sensitive environments
- Suitable for use in measuring, control and regulating circuits
- Wiring of machines, tools, devices, appliances and control cabinets
- Only for outdoor use within the indicated operating temperature range, with UV-protection

Product Make-up

- Fine copper wire strands
- Core insulation: PVC
- Cores twisted in layers
- Non-woven wrapping
- Tinned-copper braiding
- PVC outer sheath, grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 1026769 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® CHAIN 809 CY | | | | | |
| ÖLFLEX CHAIN 809 CY 2 X 0,5 | Lapp 1026751 | 2 X 0,5 | 5.8 | 36.0 | 45 |
| ÖLFLEX CHAIN 809 CY 3 G 0,5 | Lapp 1026752 | 3 G 0,5 | 6.1 | 43.0 | 59 |
| ÖLFLEX CHAIN 809 CY 4 G 0,5 | Lapp 1026753 | 4 G 0,5 | 6.6 | 49.0 | 83 |
| ÖLFLEX CHAIN 809 CY 5 G 0,5 | Lapp 1026754 | 5 G 0,5 | 7.1 | 57.0 | 96 |
| ÖLFLEX CHAIN 809 CY 7 G 0,5 | Lapp 1026755 | 7 G 0,5 | 8.5 | 69.0 | 136 |
| ÖLFLEX CHAIN 809 CY 12 G 0,5 | Lapp 1026756 | 12 G 0,5 | 10.0 | 104.0 | 200 |
| ÖLFLEX CHAIN 809 CY 18 G 0,5 | Lapp 1026757 | 18 G 0,5 | 11.8 | 141.0 | 275 |
| ÖLFLEX CHAIN 809 CY 25 G 0,5 | Lapp 1026758 | 25 G 0,5 | 14.1 | 211.0 | 350 |
| ÖLFLEX CHAIN 809 CY 2 X 0,75 | Lapp 1026759 | 2 X 0,75 | 6.2 | 43.0 | 56 |
| ÖLFLEX CHAIN 809 CY 3 G 0,75 | Lapp 1026760 | 3 G 0,75 | 6.6 | 52.0 | 70 |
| ÖLFLEX CHAIN 809 CY 4 G 0,75 | Lapp 1026761 | 4 G 0,75 | 7.1 | 61.0 | 95 |
| ÖLFLEX CHAIN 809 CY 5 G 0,75 | Lapp 1026762 | 5 G 0,75 | 7.7 | 72.0 | 130 |
| ÖLFLEX CHAIN 809 CY 7 G 0,75 | Lapp 1026763 | 7 G 0,75 | 9.1 | 89.0 | 168 |
| ÖLFLEX CHAIN 809 CY 12 G 0,75 | Lapp 1026764 | 12 G 0,75 | 10.9 | 138.0 | 232 |
| ÖLFLEX CHAIN 809 CY 18 G 0,75 | Lapp 1026765 | 18 G 0,75 | 13.0 | 211.0 | 315 |
| ÖLFLEX CHAIN 809 CY 25 G 0,75 | Lapp 1026766 | 25 G 0,75 | 15.6 | 280.0 | 435 |
| ÖLFLEX CHAIN 809 CY 2 X 1,0 | Lapp 1026767 | 2 X 1,0 | 6.5 | 51.0 | 84 |
| ÖLFLEX CHAIN 809 CY 3 G 1,0 | Lapp 1026768 | 3 G 1,0 | 6.9 | 62.0 | 110 |
| ÖLFLEX CHAIN 809 CY 4 G 1,0 | Lapp 1026769 | 4 G 1,0 | 7.5 | 74.0 | 130 |
| ÖLFLEX CHAIN 809 CY 5 G 1,0 | Lapp 1026770 | 5 G 1,0 | 8.3 | 88.0 | 156 |
| ÖLFLEX CHAIN 809 CY 7 G 1,0 | Lapp 1026771 | 7 G 1,0 | 9.8 | 112.0 | 192 |
| ÖLFLEX CHAIN 809 CY 12 G 1,0 | Lapp 1026772 | 12 G 1,0 | 11.7 | 185.0 | 285 |
| ÖLFLEX CHAIN 809 CY 18 G 1,0 | Lapp 1026773 | 18 G 1,0 | 14.0 | 268.0 | 395 |
| ÖLFLEX CHAIN 809 CY 25 G 1,0 | Lapp 1026774 | 25 G 1,0 | 16.7 | 354.0 | 486 |

ÖLFLEX CHAIN 809 CY 4 G 1,0_

Lapp 1026769



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX CHAIN 809 CY 2 X 1,5 | Lapp 1026775 | 2 X 1,5 | 7.1 | 65.0 | 97 |
| ÖLFLEX CHAIN 809 CY 3 G 1,5 | Lapp 1026776 | 3 G 1,5 | 7.5 | 82.0 | 125 |
| ÖLFLEX CHAIN 809 CY 4 G 1,5 | Lapp 1026777 | 4 G 1,5 | 8.4 | 76.6 | 165 |
| ÖLFLEX CHAIN 809 CY 5 G 1,5 | Lapp 1026778 | 5 G 1,5 | 9.1 | 119.0 | 193 |
| ÖLFLEX CHAIN 809 CY 7 G 1,5 | Lapp 1026779 | 7 G 1,5 | 10.9 | 154.0 | 245 |
| ÖLFLEX CHAIN 809 CY 12 G 1,5 | Lapp 1026780 | 12 G 1,5 | 13.3 | 268.0 | 365 |
| ÖLFLEX CHAIN 809 CY 18 G 1,5 | Lapp 1026781 | 18 G 1,5 | 15.7 | 373.0 | 553 |
| ÖLFLEX CHAIN 809 CY 25 G 1,5 | Lapp 1026782 | 25 G 1,5 | 18.7 | 530.0 | 734 |
| ÖLFLEX CHAIN 809 CY 3 G 2,5 | Lapp 1026783 | 3 G 2,5 | 9.0 | 118.0 | 188 |
| ÖLFLEX CHAIN 809 CY 4 G 2,5 | Lapp 1026784 | 4 G 2,5 | 10.1 | 147.0 | 236 |
| ÖLFLEX CHAIN 809 CY 7 G 2,5 | Lapp 1026785 | 7 G 2,5 | 13.5 | 253.0 | 340 |
| ÖLFLEX CHAIN 809 CY 4 G 4 | Lapp 1026788 | 4 G 4 | 11.9 | 248.0 | 305 |