



Description: ÖLFLEX CHAIN 896 P 4 G 16_

Lapp code: Lapp 1023252

The **Test voltage** of the cable Lapp 1023252 is 4000 V.

Application range

- Applications in automation engineering
- Power circuits in industrial machines
- In power chains or moving machine parts
- For use in assembling & pick-and-place machinery
- Particularly in wet areas of machine tools and transfer lines

Product Make-up

- Extra-fine wire strand made of bare copper wires (class 6)
- Core insulation: polypropylene (PP)
- Non-woven wrapping
- PUR outer sheath, black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 1023252 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CHAIN 896 P					
ÖLFLEX CHAIN 896 P 4 G 1,5	Lapp 1023229	4 G 1,5	9.6	58.0	120
ÖLFLEX CHAIN 896 P 5 G 1,5	Lapp 1023230	5 G 1,5	10.0	72.0	143
ÖLFLEX CHAIN 896 P 4 G 2,5	Lapp 1023238	4 G 2,5	11.0	96.0	174
ÖLFLEX CHAIN 896 P 5 G 2,5	Lapp 1023239	5 G 2,5	12.0	120.0	210
ÖLFLEX CHAIN 896 P 4 G 4	Lapp 1023245	4 G 4	12.5	154.0	242
ÖLFLEX CHAIN 896 P 5 G 4	Lapp 1023246	5 G 4	13.7	192.0	316
ÖLFLEX CHAIN 896 P 4 G 6	Lapp 1023248	4 G 6	14.3	231.0	335
ÖLFLEX CHAIN 896 P 5 G 6	Lapp 1023249	5 G 6	15.7	288.0	439
ÖLFLEX CHAIN 896 P 4 G 10	Lapp 1023250	4 G 10	17.0	384.0	503
ÖLFLEX CHAIN 896 P 5 G 10	Lapp 1023251	5 G 10	18.9	480.0	663
ÖLFLEX CHAIN 896 P 4 G 16	Lapp 1023252	4 G 16	21.2	615.0	810
ÖLFLEX CHAIN 896 P 5 G 16	Lapp 1023253	5 G 16	23.8	768.0	1065
ÖLFLEX CHAIN 896 P 4 G 25	Lapp 1023254	4 G 25	25.9	960.0	1254
ÖLFLEX CHAIN 896 P 5 G 25	Lapp 1023255	5 G 25	29.0	1200.0	1582