

LAPP KABEL STUFGART ÖLFLEX® CHARGE 5VC 306+3.8 500/750 VAC VDE-Reg. 0787 Norm 11

Description: ÖLFLEX CHARGE 5G6+1X0,5_

Lapp code: Lapp 74880582

The **Test voltage** of the cable Lapp 74880582 is At the core: 2.5 kV AC At the finished cable: 3 kV AC.

/

Product Make-up

- Finely stranded, bare copper conductors of IEC conductor class 5 acc. IEC 60228
- Core insulations of power cores made of special, halogen-free, cross-linked elastomer EVI-2 acc. VDE-AR-E 2283-5
- Core insulation control/ pilot core(s): Halogen-free, thermoplastic, special compound EVI-1 acc. VDE-AR-E 2283-5
- Halogen-free, outer sheath made of PUR in compliance with the normative compound EVM-1 acc. VDE-AR-E 2283-5
- Colour of the outer sheath: Orange similar to RAL 2003, further sheath colours on request

In our Cable list on next page you can find all interesting information acc. article Lapp 74880582 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX CHARGE 3G2,5+1X0,5	Lapp 74880550	3G2,5+1X0,5	10.1	76.8	155
ÖLFLEX CHARGE 3G6+1X0,5	Lapp 74880558	3G6+1X0,5	13.2	178.0	330
ÖLFLEX CHARGE 5G2,5+1X0,5	Lapp 74880574	5G2,5+1X0,5	12.8	125.0	260
ÖLFLEX CHARGE 5G6+1X0,5	Lapp 74880582	5G6+1X0,5	16.0	293.0	460