



**Description:** ÖLFLEX CLASSIC 100 YELLOW 5 G 2,5\_

**Lapp code:** Lapp 00104053

The **Test voltage** of the cable Lapp 00104053 is 4000 V.

## Application range

- For electrical circuits that remain 'live' after the main switch has been disconnected
- Service sockets and illumination circuits in electrical switchboards and cabinets
- Suitable for torsional applications which are typical for the loop in wind turbine generators (WTG)

## Product Make-up

- Fine-wire strand made of bare copper wires
- PVC insulation LAPP P8/1
- PVC outer sheath, yellow (RAL 1016)

In our Cable list on next page you can find all interesting information acc. article Lapp 00104053 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 100 YELLOW; U <sub>0</sub> /U: 450/750 V					
ÖLFLEX CLASSIC 100 YELLOW 3 G 1,5	Lapp 0010400	3 G 1,5	8,1	43.0	95
ÖLFLEX CLASSIC 100 YELLOW 4 G 1,5	Lapp 00104023	4 G 1,5	8,9	58.0	117
ÖLFLEX CLASSIC 100 YELLOW 5 G 1,5	Lapp 00104033	5 G 1,5	10.0	72.0	144
ÖLFLEX CLASSIC 100 YELLOW 3 G 2,5	Lapp 0010401	3 G 2,5	9,6	72.0	152
ÖLFLEX CLASSIC 100 YELLOW 4 G 2,5	Lapp 00104043	4 G 2,5	10,7	96.0	205
ÖLFLEX CLASSIC 100 YELLOW 5 G 2,5	Lapp 00104053	5 G 2,5	11,8	120.0	225