



Description: ÖLFLEX CLASSIC 110 CY 41 G0,75_

Lapp code: Lapp 1135141

The **Test voltage** of the cable Lapp 1135141 is 4000 V.

Application range

- Plant engineering
Industrial machinery
Heating and air-conditioning systems
- Conveyor and transport systems
- In EMC-sensitive environments
(electromagnetic compatibility)

Product Make-up

- Fine-wire strand made of bare copper wires
- PVC insulation LAPP P8/1
- PVC inner sheath, grey
- Tinned-copper braiding
- PVC outer sheath, transparent

In our Cable list on next page you can find all interesting information acc. article Lapp 1135141 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® CLASSIC 110 CY | | | | | |
| ÖLFLEX CLASSIC 110 CY 2 X0,5 | Lapp 1135752 | 2 X0,5 | 7,0 | 41,0 | 75 |
| ÖLFLEX CLASSIC 110 CY 3 G0,5 | Lapp 1135003 | 3 G0,5 | 7,3 | 45,5 | 83 |
| ÖLFLEX CLASSIC 110 CY 3 X0,5 | Lapp 1135753 | 3 X0,5 | 7,3 | 45,5 | 83 |
| ÖLFLEX CLASSIC 110 CY 4 G0,5 | Lapp 1135004 | 4 G0,5 | 7,9 | 55,0 | 99 |
| ÖLFLEX CLASSIC 110 CY 4 X0,5 | Lapp 1135754 | 4 X0,5 | 7,9 | 55,0 | 99 |
| ÖLFLEX CLASSIC 110 CY 5 G0,5 | Lapp 1135005 | 5 G0,5 | 8,4 | 66,0 | 112 |
| ÖLFLEX CLASSIC 110 CY 5 X0,5 | Lapp 1135755 | 5 X0,5 | 8,4 | 66,0 | 112 |
| ÖLFLEX CLASSIC 110 CY 7 G0,5 | Lapp 1135007 | 7 G0,5 | 8,9 | 80,5 | 132 |
| ÖLFLEX CLASSIC 110 CY 7 X0,5 | Lapp 1135757 | 7 X0,5 | 8,9 | 80,5 | 132 |
| ÖLFLEX CLASSIC 110 CY 12 G0,5 | Lapp 1135012 | 12 G0,5 | 11,3 | 138,5 | 202 |
| ÖLFLEX CLASSIC 110 CY 12 X0,5 | Lapp 1135762 | 12 X0,5 | 11,3 | 138,5 | 202 |
| ÖLFLEX CLASSIC 110 CY 18 G0,5 | Lapp 1135018 | 18 G0,5 | 13,3 | 156,4 | 289 |
| ÖLFLEX CLASSIC 110 CY 25 G0,5 | Lapp 1135025 | 25 G0,5 | 15,2 | 250,0 | 378 |
| ÖLFLEX CLASSIC 110 CY 30 G0,5 | Lapp 1135030 | 30 G0,5 | 16,1 | 297,0 | 429 |
| ÖLFLEX CLASSIC 110 CY 40 G0,5 | Lapp 1135040 | 40 G0,5 | 18,2 | 343,0 | 542 |
| ÖLFLEX CLASSIC 110 CY 2 X0,75 | Lapp 1135802 | 2 X0,75 | 7,4 | 46,0 | 86 |
| ÖLFLEX CLASSIC 110 CY 3 G0,75 | Lapp 1135103 | 3 G0,75 | 7,9 | 57,9 | 100 |
| ÖLFLEX CLASSIC 110 CY 3 X0,75 | Lapp 1135803 | 3 X0,75 | 7,9 | 57,9 | 100 |
| ÖLFLEX CLASSIC 110 CY 4 G0,75 | Lapp 1135104 | 4 G0,75 | 8,4 | 64,0 | 115 |
| ÖLFLEX CLASSIC 110 CY 4 X0,75 | Lapp 1135804 | 4 X0,75 | 8,4 | 64,0 | 115 |
| ÖLFLEX CLASSIC 110 CY 5 G0,75 | Lapp 1135105 | 5 G0,75 | 8,9 | 77,4 | 130 |
| ÖLFLEX CLASSIC 110 CY 5 X0,75 | Lapp 1135805 | 5 X0,75 | 8,9 | 77,4 | 130 |
| ÖLFLEX CLASSIC 110 CY 7 G0,75 | Lapp 1135107 | 7 G0,75 | 9,7 | 102,0 | 161 |
| ÖLFLEX CLASSIC 110 CY 7 X0,75 | Lapp 1135807 | 7 X0,75 | 9,7 | 102,0 | 161 |

ÖLFLEX CLASSIC 110 CY 41 G0,75_

Lapp 1135141



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX CLASSIC 110 CY 12 G0,75 | Lapp 1135112 | 12 G0,75 | 12,3 | 177.0 | 247 |
| ÖLFLEX CLASSIC 110 CY 12 X0,75 | Lapp 1135812 | 12 X0,75 | 12,3 | 177.0 | 247 |
| ÖLFLEX CLASSIC 110 CY 18 G0,75 | Lapp 1135118 | 18 G0,75 | 14,5 | 243.0 | 356 |
| ÖLFLEX CLASSIC 110 CY 18 X0,75 | Lapp 1135818 | 18 X0,75 | 14,5 | 243.0 | 356 |
| ÖLFLEX CLASSIC 110 CY 25 G0,75 | Lapp 1135125 | 25 G0,75 | 16,6 | 307.3 | 465 |
| ÖLFLEX CLASSIC 110 CY 34 G0,75 | Lapp 1135134 | 34 G0,75 | 18,9 | 323.2 | 601 |
| ÖLFLEX CLASSIC 110 CY 40 X0,75 | Lapp 1135840 | 40 X0,75 | 20,5 | 369.4 | 734 |
| ÖLFLEX CLASSIC 110 CY 41 G0,75 | Lapp 1135141 | 41 G0,75 | 20,6 | 488.0 | 728 |
| ÖLFLEX CLASSIC 110 CY 2 X1,0 | Lapp 1135852 | 2 X1,0 | 7,9 | 56.0 | 98 |
| ÖLFLEX CLASSIC 110 CY 3 G1,0 | Lapp 1135203 | 3 G1,0 | 8,2 | 65.3 | 111 |
| ÖLFLEX CLASSIC 110 CY 3 X1,0 | Lapp 1135853 | 3 X1,0 | 8,2 | 65.3 | 111 |
| ÖLFLEX CLASSIC 110 CY 4 G1,0 | Lapp 1135204 | 4 G1,0 | 8,7 | 78.1 | 130 |
| ÖLFLEX CLASSIC 110 CY 4 X1,0 | Lapp 1135854 | 4 X1,0 | 8,7 | 78.1 | 130 |
| ÖLFLEX CLASSIC 110 CY 5 G1,0 | Lapp 1135205 | 5 G1,0 | 9,5 | 89.4 | 153 |
| ÖLFLEX CLASSIC 110 CY 7 G1,0 | Lapp 1135207 | 7 G1,0 | 10,2 | 113.3 | 185 |
| ÖLFLEX CLASSIC 110 CY 12 G1,0 | Lapp 1135212 | 12 G1,0 | 13,3 | 188.1 | 307 |
| ÖLFLEX CLASSIC 110 CY 16 G1,0 | Lapp 1135216 | 16 G1,0 | 14,6 | 216.0 | 390 |
| ÖLFLEX CLASSIC 110 CY 18 G1,0 | Lapp 1135218 | 18 G1,0 | 15,5 | 286.0 | 418 |
| ÖLFLEX CLASSIC 110 CY 25 G1,0 | Lapp 1135225 | 25 G1,0 | 17,5 | 388.5 | 544 |
| ÖLFLEX CLASSIC 110 CY 34 G1,0 | Lapp 1135234 | 34 G1,0 | 20,3 | 505.0 | 738 |
| ÖLFLEX CLASSIC 110 CY 41 G1,0 | Lapp 1135241 | 41 G1,0 | 22,0 | 578.0 | 864 |
| ÖLFLEX CLASSIC 110 CY 50 G1,0 | Lapp 1135250 | 50 G1,0 | 23,8 | 688.0 | 1011 |
| ÖLFLEX CLASSIC 110 CY 2 X1,5 | Lapp 1135902 | 2 X1,5 | 8,5 | 65.0 | 117 |
| ÖLFLEX CLASSIC 110 CY 3 G1,5 | Lapp 1135303 | 3 G1,5 | 8,9 | 83.0 | 136 |
| ÖLFLEX CLASSIC 110 CY 3 X1,5 | Lapp 1135903 | 3 X1,5 | 8,9 | 83.0 | 136 |
| ÖLFLEX CLASSIC 110 CY 4 G1,5 | Lapp 1135304 | 4 G1,5 | 9,6 | 100.0 | 163 |

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX CLASSIC 110 CY 4 X1,5 | Lapp 1135904 | 4 X1,5 | 9,6 | 100.0 | 163 |
| ÖLFLEX CLASSIC 110 CY 5 G1,5 | Lapp 1135305 | 5 G1,5 | 10,3 | 125.0 | 188 |
| ÖLFLEX CLASSIC 110 CY 5 X1,5 | Lapp 1135905 | 5 X1,5 | 10,3 | 125.0 | 188 |
| ÖLFLEX CLASSIC 110 CY 7 G1,5 | Lapp 1135307 | 7 G1,5 | 11,3 | 149.0 | 237 |
| ÖLFLEX CLASSIC 110 CY 7 X1,5 | Lapp 1135907 | 7 X1,5 | 11,3 | 149.0 | 237 |
| ÖLFLEX CLASSIC 110 CY 12 G1,5 | Lapp 1135312 | 12 G1,5 | 14,8 | 280.0 | 393 |
| ÖLFLEX CLASSIC 110 CY 18 G1,5 | Lapp 1135318 | 18 G1,5 | 17,2 | 389.0 | 538 |
| ÖLFLEX CLASSIC 110 CY 25 G1,5 | Lapp 1135325 | 25 G1,5 | 20,1 | 535.0 | 745 |
| ÖLFLEX CLASSIC 110 CY 34 G1,5 | Lapp 1135334 | 34 G1,5 | 22,8 | 702.0 | 964 |
| ÖLFLEX CLASSIC 110 CY 41 G1,5 | Lapp 1135341 | 41 G1,5 | 24,7 | 844.6 | 1123 |
| ÖLFLEX CLASSIC 110 CY 50 G1,5 | Lapp 1135350 | 50 G1,5 | 27,1 | 1006.0 | 1372 |
| ÖLFLEX CLASSIC 110 CY 2 X2,5 | Lapp 1135402 | 2 X2,5 | 9,9 | 112.0 | 165 |
| ÖLFLEX CLASSIC 110 CY 3 G2,5 | Lapp 1135403 | 3 G2,5 | 10,3 | 146.0 | 192 |
| ÖLFLEX CLASSIC 110 CY 4 G2,5 | Lapp 1135404 | 4 G2,5 | 11,3 | 167.0 | 233 |
| ÖLFLEX CLASSIC 110 CY 5 G2,5 | Lapp 1135405 | 5 G2,5 | 12,6 | 200.0 | 283 |
| ÖLFLEX CLASSIC 110 CY 7 G2,5 | Lapp 1135407 | 7 G2,5 | 13,9 | 288.0 | 371 |
| ÖLFLEX CLASSIC 110 CY 12 G2,5 | Lapp 1135412 | 12 G2,5 | 17,6 | 477.3 | 585 |
| ÖLFLEX CLASSIC 110 CY 2 X4 | Lapp 1135502 | 2 X4 | 11,4 | 120.0 | 247 |
| ÖLFLEX CLASSIC 110 CY 4 G4 | Lapp 1135504 | 4 G4 | 13,4 | 237.0 | 347 |
| ÖLFLEX CLASSIC 110 CY 5 G4 | Lapp 1135505 | 5 G4 | 14,7 | 280.0 | 413 |
| ÖLFLEX CLASSIC 110 CY 2 X6 | Lapp 1135602 | 2 X6 | 13,6 | 180.0 | 353 |
| ÖLFLEX CLASSIC 110 CY 4 G6 | Lapp 1135604 | 4 G6 | 15,8 | 318.0 | 485 |
| ÖLFLEX CLASSIC 110 CY 5 G6 | Lapp 1135605 | 5 G6 | 17,3 | 441.0 | 702 |
| ÖLFLEX CLASSIC 110 CY 7 G6 | Lapp 1135607 | 7 G6 | 18,8 | 530.0 | 950 |
| ÖLFLEX CLASSIC 110 CY 2 X10 | Lapp 1135702 | 2 X10 | 16,4 | 256.0 | 492 |
| ÖLFLEX CLASSIC 110 CY 3 G10 | Lapp 1135615 | 3 G10 | 17,4 | 362.4 | 507 |

ÖLFLEX CLASSIC 110 CY 41 G0,75_

Lapp 1135141



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-----------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX CLASSIC 110 CY 4 G10 | Lapp 1135614 | 4 G10 | 19,0 | 558,0 | 735 |
| ÖLFLEX CLASSIC 110 CY 5 G10 | Lapp 1135616 | 5 G10 | 21,3 | 595,0 | 847 |
| ÖLFLEX CLASSIC 110 CY 7 G10 | Lapp 1135617 | 7 G10 | 23,2 | 796,0 | 1039 |
| ÖLFLEX CLASSIC 110 CY 2 X16 | Lapp 1135622 | 2 X16 | 18,6 | 390,0 | 698 |
| ÖLFLEX CLASSIC 110 CY 4 G16 | Lapp 1135624 | 4 G16 | 22,2 | 804,0 | 1395 |
| ÖLFLEX CLASSIC 110 CY 5 G16 | Lapp 1135623 | 5 G16 | 24,4 | 935,0 | 1440 |
| ÖLFLEX CLASSIC 110 CY 4 G25 | Lapp 1135626 | 4 G25 | 26,9 | 1161,0 | 1730 |
| ÖLFLEX CLASSIC 110 CY 5 G25 | Lapp 1135627 | 5 G25 | 30,0 | 1400,0 | 2090 |
| ÖLFLEX CLASSIC 110 CY 4 G35 | Lapp 1135625 | 4 G35 | 30,2 | 1543,0 | 2210 |
| ÖLFLEX CLASSIC 110 CY 5 G35 | Lapp 1135628 | 5 G35 | 33,2 | 1901,0 | 2710 |