



Description: ÖLFLEX CLASSIC 110 LT 3 G1,0_

Lapp code: Lapp 1120742

The **Test voltage** of the cable Lapp 1120742 is 4000 V.

Application range

- Plant engineering
Industrial machinery
Heating and air-conditioning systems
- Freezing plants, cold storage
- Suitable for outdoor applications
- Suitable for torsional applications which are typical for the loop in wind turbine generators (WTG)

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: PVC, cold-resistant
- Outer sheath: PVC, cold-resistant, black

In our Cable list on next page you can find all interesting information acc. article Lapp 1120742 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX CLASSIC 110 LT 2 X0,75	Lapp 1120730	2 X0,75	5,4	14.4	45
ÖLFLEX CLASSIC 110 LT 3 X0,75	Lapp 1120731	3 X0,75	5,7	21.6	55
ÖLFLEX CLASSIC 110 LT 3 G0,75	Lapp 1120732	3 G0,75	5,7	21.6	55
ÖLFLEX CLASSIC 110 LT 4 X0,75	Lapp 1120733	4 X0,75	6,2	28.8	66
ÖLFLEX CLASSIC 110 LT 4 G0,75	Lapp 1120734	4 G0,75	6,2	28.8	66
ÖLFLEX CLASSIC 110 LT 5 G0,75	Lapp 1120735	5 G0,75	6,7	36.0	79
ÖLFLEX CLASSIC 110 LT 7 G0,75	Lapp 1120736	7 G0,75	7,3	50.4	101
ÖLFLEX CLASSIC 110 LT 12 G0,75	Lapp 1120737	12 G0,75	9,9	86.4	171
ÖLFLEX CLASSIC 110 LT 18 G0,75	Lapp 1120738	18 G0,75	11,7	130.0	244
ÖLFLEX CLASSIC 110 LT 25 G0,75	Lapp 1120739	25 G0,75	13,8	180.0	337
ÖLFLEX CLASSIC 110 LT 2 X1,0	Lapp 1120740	2 X1,0	5,7	19.2	53
ÖLFLEX CLASSIC 110 LT 3 X1,0	Lapp 1120741	3 X1,0	6,0	28.8	65
ÖLFLEX CLASSIC 110 LT 3 G1,0	Lapp 1120742	3 G1,0	6,0	28.8	65
ÖLFLEX CLASSIC 110 LT 4 X1,0	Lapp 1120743	4 X1,0	6,5	38.4	79
ÖLFLEX CLASSIC 110 LT 4 G1,0	Lapp 1120744	4 G1,0	6,5	38.4	79
ÖLFLEX CLASSIC 110 LT 5 G1,0	Lapp 1120745	5 G1,0	7,1	48.0	94
ÖLFLEX CLASSIC 110 LT 7 G1,0	Lapp 1120746	7 G1,0	8,0	67.2	126
ÖLFLEX CLASSIC 110 LT 12 G1,0	Lapp 1120747	12 G1,0	10,5	115.0	205
ÖLFLEX CLASSIC 110 LT 18 G1,0	Lapp 1120748	18 G1,0	12,7	173.0	300
ÖLFLEX CLASSIC 110 LT 25 G1,0	Lapp 1120749	25 G1,0	14,7	240.0	408
ÖLFLEX CLASSIC 110 LT 2 X1,5	Lapp 1120750	2 X1,5	6,3	29.0	68
ÖLFLEX CLASSIC 110 LT 3 X1,5	Lapp 1120751	3 X1,5	6,7	43.0	84
ÖLFLEX CLASSIC 110 LT 3 G1,5	Lapp 1120752	3 G1,5	6,7	43.0	84
ÖLFLEX CLASSIC 110 LT 4 X1,5	Lapp 1120753	4 X1,5	7,2	58.0	104
ÖLFLEX CLASSIC 110 LT 4 G1,5	Lapp 1120754	4 G1,5	7,2	58.0	104

ÖLFLEX CLASSIC 110 LT 3 G1,0_

Lapp 1120742



Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX CLASSIC 110 LT 5 X1,5	Lapp 1120755	5 X1,5	8,1	72.0	128
ÖLFLEX CLASSIC 110 LT 5 G1,5	Lapp 1120756	5 G1,5	8,1	72.0	128
ÖLFLEX CLASSIC 110 LT 7 X1,5	Lapp 1120757	7 X1,5	8,9	101.0	166
ÖLFLEX CLASSIC 110 LT 7 G1,5	Lapp 1120758	7 G1,5	8,9	101.0	166
ÖLFLEX CLASSIC 110 LT 12 G1,5	Lapp 1120759	12 G1,5	12.0	173.0	279
ÖLFLEX CLASSIC 110 LT 18 G1,5	Lapp 1120760	18 G1,5	14,4	259.0	407
ÖLFLEX CLASSIC 110 LT 25 G1,5	Lapp 1120761	25 G1,5	16,9	360.0	560
ÖLFLEX CLASSIC 110 LT 2 X2,5	Lapp 1120762	2 X2,5	7,5	48.0	101
ÖLFLEX CLASSIC 110 LT 3 G2,5	Lapp 1120763	3 G2,5	8,1	72.0	132
ÖLFLEX CLASSIC 110 LT 4 G2,5	Lapp 1120764	4 G2,5	8,9	96.0	163
ÖLFLEX CLASSIC 110 LT 5 G2,5	Lapp 1120765	5 G2,5	10.0	120.0	200
ÖLFLEX CLASSIC 110 LT 7 G2,5	Lapp 1120766	7 G2,5	11,1	168.0	267
ÖLFLEX CLASSIC 110 LT 12 G2,5	Lapp 1120767	12 G2,5	14,8	288.0	445
ÖLFLEX CLASSIC 110 LT 18 G2,5	Lapp 1120768	18 G2,5	17,8	432.0	648
ÖLFLEX CLASSIC 110 LT 25 G2,5	Lapp 1120769	25 G2,5	20,8	600.0	890
ÖLFLEX CLASSIC 110 LT 4 G4	Lapp 1120770	4 G4	10,8	154.0	249
ÖLFLEX CLASSIC 110 LT 5 G4	Lapp 1120771	5 G4	12,1	192.0	305
ÖLFLEX CLASSIC 110 LT 4 G6	Lapp 1120772	4 G6	13.0	230.0	365
ÖLFLEX CLASSIC 110 LT 5 G6	Lapp 1120773	5 G6	14,5	288.0	447