



Description: ÖLFLEX CLASSIC 110 ORANGE 3 G1,5_

Lapp code: Lapp 0019711

The **Test voltage** of the cable Lapp 0019711 is 4000 V.

Application range

- According to EN 60204-1 (VDE 0113-1), conductors of control circuits that are supplied by an external power source and/or remain live when the main switch is deactivated must be orange
- Electrical lighting and socket circuits for maintenance or repair purposes
- Undervoltage protection circuits
- Interlocking control circuits
- Suitable for torsional applications which are typical for the loop in wind turbine generators (WTG)

Product Make-up

- Fine-wire strand made of bare copper wires
- PVC insulation LAPP P8/1
- Orange cores with black numbers
- PVC outer sheath, orange (RAL 2003)

In our Cable list on next page you can find all interesting information acc. article Lapp 0019711 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 110 ORANGE					
ÖLFLEX CLASSIC 110 ORANGE 2 X1,0	Lapp 0019700	2 X1,0	5,7	19.2	53
ÖLFLEX CLASSIC 110 ORANGE 3 G1,0	Lapp 0019701	3 G1,0	6.0	28.8	65
ÖLFLEX CLASSIC 110 ORANGE 3 X1,0	Lapp 0019702	3 X1,0	6.0	28.8	65
ÖLFLEX CLASSIC 110 ORANGE 4 G1,0	Lapp 0019706	4 G1,0	6,5	38.4	80
ÖLFLEX CLASSIC 110 ORANGE 4 X1,0	Lapp 0019708	4 X1,0	6,5	38.4	80
ÖLFLEX CLASSIC 110 ORANGE 5 G1,0	Lapp 0019709	5 G1,0	7,1	50.0	95
ÖLFLEX CLASSIC 110 ORANGE 2 X1,5	Lapp 0019710	2 X1,5	6,3	29.0	68
ÖLFLEX CLASSIC 110 ORANGE 3 G1,5	Lapp 0019711	3 G1,5	6,7	43.0	85
ÖLFLEX CLASSIC 110 ORANGE 4 G1,5	Lapp 0019718	4 G1,5	7,2	58.0	105
ÖLFLEX CLASSIC 110 ORANGE 5 G1,5	Lapp 0019720	5 G1,5	8,1	72.0	128