



Description: ÖLFLEX CLASSIC 110 ORANGE 4 G1,5_

Lapp code: Lapp 0019718

The **Test voltage** of the cable Lapp 0019718 is 4000 V.

Application range

- According to EN 60204-1 (VDE 0113-1), conductors of control circuits that are supplied by an external power source and/or remain live when the main switch is deactivated must be orange
- Electrical lighting and socket circuits for maintenance or repair purposes
- Undervoltage protection circuits
- Interlocking control circuits
- Suitable for torsional applications which are typical for the loop in wind turbine generators (WTG)

Product Make-up

- Fine-wire strand made of bare copper wires
- PVC insulation LAPP P8/1
- Orange cores with black numbers
- PVC outer sheath, orange (RAL 2003)

In our Cable list on next page you can find all interesting information acc. article Lapp 0019718 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|----------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® CLASSIC 110 ORANGE | | | | | |
| ÖLFLEX CLASSIC 110 ORANGE 2 X1,0 | Lapp 0019700 | 2 X1,0 | 5,7 | 19.2 | 53 |
| ÖLFLEX CLASSIC 110 ORANGE 3 G1,0 | Lapp 0019701 | 3 G1,0 | 6.0 | 28.8 | 65 |
| ÖLFLEX CLASSIC 110 ORANGE 3 X1,0 | Lapp 0019702 | 3 X1,0 | 6.0 | 28.8 | 65 |
| ÖLFLEX CLASSIC 110 ORANGE 4 G1,0 | Lapp 0019706 | 4 G1,0 | 6,5 | 38.4 | 80 |
| ÖLFLEX CLASSIC 110 ORANGE 4 X1,0 | Lapp 0019708 | 4 X1,0 | 6,5 | 38.4 | 80 |
| ÖLFLEX CLASSIC 110 ORANGE 5 G1,0 | Lapp 0019709 | 5 G1,0 | 7,1 | 50.0 | 95 |
| ÖLFLEX CLASSIC 110 ORANGE 2 X1,5 | Lapp 0019710 | 2 X1,5 | 6,3 | 29.0 | 68 |
| ÖLFLEX CLASSIC 110 ORANGE 3 G1,5 | Lapp 0019711 | 3 G1,5 | 6,7 | 43.0 | 85 |
| ÖLFLEX CLASSIC 110 ORANGE 4 G1,5 | Lapp 0019718 | 4 G1,5 | 7,2 | 58.0 | 105 |
| ÖLFLEX CLASSIC 110 ORANGE 5 G1,5 | Lapp 0019720 | 5 G1,5 | 8,1 | 72.0 | 128 |