



Description: ÖLFLEX CLASSIC 115 CY 7 G2,5_

Lapp code: Lapp 1136407

The **Test voltage** of the cable Lapp 1136407 is Core/core: 4000 V Core/screen: 2000 V.

Application range

- Measurement and control technology
- Office machines and systems for data processing

Product Make-up

- Fine-wire strand made of bare copper wires
- PVC insulation LAPP P8/1
- Plastic foil wrapping
- Tinned-copper braiding
- PVC outer sheath, grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 1136407 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® CLASSIC 115 CY | | | | | |
| ÖLFLEX CLASSIC 115 CY 2 X0,5 | Lapp 1136752 | 2 X0,5 | 5,8 | 36.0 | 45 |
| ÖLFLEX CLASSIC 115 CY 3 G0,5 | Lapp 1136003 | 3 G0,5 | 6,1 | 43.0 | 59 |
| ÖLFLEX CLASSIC 115 CY 3 X0,5 | Lapp 1136753 | 3 X0,5 | 6,1 | 43.0 | 59 |
| ÖLFLEX CLASSIC 115 CY 4 G0,5 | Lapp 1136004 | 4 G0,5 | 6,5 | 49.0 | 71 |
| ÖLFLEX CLASSIC 115 CY 4 X0,5 | Lapp 1136754 | 4 X0,5 | 6,5 | 49.0 | 71 |
| ÖLFLEX CLASSIC 115 CY 5 G0,5 | Lapp 1136005 | 5 G0,5 | 7.0 | 57.0 | 86 |
| ÖLFLEX CLASSIC 115 CY 5 X0,5 | Lapp 1136755 | 5 X0,5 | 7.0 | 57.0 | 86 |
| ÖLFLEX CLASSIC 115 CY 7 G0,5 | Lapp 1136007 | 7 G0,5 | 7,5 | 69.0 | 105 |
| ÖLFLEX CLASSIC 115 CY 7 X0,5 | Lapp 1136757 | 7 X0,5 | 7,5 | 69.0 | 105 |
| ÖLFLEX CLASSIC 115 CY 12 G0,5 | Lapp 1136012 | 12 G0,5 | 9,9 | 104.0 | 200 |
| ÖLFLEX CLASSIC 115 CY 12 X0,5 | Lapp 1136762 | 12 X0,5 | 9,9 | 104.0 | 200 |
| ÖLFLEX CLASSIC 115 CY 18 G0,5 | Lapp 1136018 | 18 G0,5 | 11,5 | 141.0 | 275 |
| ÖLFLEX CLASSIC 115 CY 18 X0,5 | Lapp 1136768 | 18 X0,5 | 11,5 | 141.0 | 275 |
| ÖLFLEX CLASSIC 115 CY 25 G0,5 | Lapp 1136025 | 25 G0,5 | 13,4 | 211.0 | 350 |
| ÖLFLEX CLASSIC 115 CY 25 X0,5 | Lapp 1136775 | 25 X0,5 | 13,4 | 211.0 | 350 |
| ÖLFLEX CLASSIC 115 CY 2 X0,75 | Lapp 1136802 | 2 X0,75 | 6,2 | 43.0 | 56 |
| ÖLFLEX CLASSIC 115 CY 3 G0,75 | Lapp 1136103 | 3 G0,75 | 6,5 | 52.0 | 70 |
| ÖLFLEX CLASSIC 115 CY 3 X0,75 | Lapp 1136803 | 3 X0,75 | 6,5 | 52.0 | 70 |
| ÖLFLEX CLASSIC 115 CY 4 G0,75 | Lapp 1136104 | 4 G0,75 | 7.0 | 61.0 | 95 |
| ÖLFLEX CLASSIC 115 CY 4 X0,75 | Lapp 1136804 | 4 X0,75 | 7.0 | 61.0 | 95 |
| ÖLFLEX CLASSIC 115 CY 5 G0,75 | Lapp 1136105 | 5 G0,75 | 7,7 | 72.0 | 108 |
| ÖLFLEX CLASSIC 115 CY 5 X0,75 | Lapp 1136805 | 5 X0,75 | 7,7 | 72.0 | 108 |
| ÖLFLEX CLASSIC 115 CY 7 G0,75 | Lapp 1136107 | 7 G0,75 | 8,3 | 89.0 | 127 |
| ÖLFLEX CLASSIC 115 CY 7 X0,75 | Lapp 1136807 | 7 X0,75 | 8,3 | 89.0 | 127 |

ÖLFLEX CLASSIC 115 CY 7 G2,5_

Lapp 1136407



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX CLASSIC 115 CY 12 G0,75 | Lapp 1136112 | 12 G0,75 | 10,9 | 138.0 | 232 |
| ÖLFLEX CLASSIC 115 CY 18 G0,75 | Lapp 1136118 | 18 G0,75 | 12,7 | 211.0 | 315 |
| ÖLFLEX CLASSIC 115 CY 25 G0,75 | Lapp 1136125 | 25 G0,75 | 14,8 | 280.0 | 435 |
| ÖLFLEX CLASSIC 115 CY 25 X0,75 | Lapp 1136825 | 25 X0,75 | 14,8 | 280.0 | 435 |
| ÖLFLEX CLASSIC 115 CY 2 X1,0 | Lapp 1136852 | 2 X1,0 | 6,5 | 51.0 | 71 |
| ÖLFLEX CLASSIC 115 CY 3 G1,0 | Lapp 1136203 | 3 G1,0 | 6,8 | 62.0 | 86 |
| ÖLFLEX CLASSIC 115 CY 3 X1,0 | Lapp 1136853 | 3 X1,0 | 6,8 | 62.0 | 86 |
| ÖLFLEX CLASSIC 115 CY 4 G1,0 | Lapp 1136204 | 4 G1,0 | 7,3 | 74.0 | 98 |
| ÖLFLEX CLASSIC 115 CY 4 X1,0 | Lapp 1136854 | 4 X1,0 | 7,3 | 74.0 | 98 |
| ÖLFLEX CLASSIC 115 CY 5 G1,0 | Lapp 1136205 | 5 G1,0 | 8,1 | 88.0 | 121 |
| ÖLFLEX CLASSIC 115 CY 5 X1,0 | Lapp 1136855 | 5 X1,0 | 8,1 | 88.0 | 121 |
| ÖLFLEX CLASSIC 115 CY 7 G1,0 | Lapp 1136207 | 7 G1,0 | 8,8 | 112.0 | 147 |
| ÖLFLEX CLASSIC 115 CY 7 X1,0 | Lapp 1136857 | 7 X1,0 | 8,8 | 112.0 | 147 |
| ÖLFLEX CLASSIC 115 CY 12 G1,0 | Lapp 1136212 | 12 G1,0 | 11,5 | 185.0 | 285 |
| ÖLFLEX CLASSIC 115 CY 18 G1,0 | Lapp 1136218 | 18 G1,0 | 13,9 | 268.0 | 395 |
| ÖLFLEX CLASSIC 115 CY 25 G1,0 | Lapp 1136225 | 25 G1,0 | 15,9 | 354.0 | 486 |
| ÖLFLEX CLASSIC 115 CY 2 X1,5 | Lapp 1136902 | 2 X1,5 | 7,1 | 65.0 | 86 |
| ÖLFLEX CLASSIC 115 CY 3 G1,5 | Lapp 1136303 | 3 G1,5 | 7,5 | 82.0 | 112 |
| ÖLFLEX CLASSIC 115 CY 3 X1,5 | Lapp 1136903 | 3 X1,5 | 7,5 | 82.0 | 112 |
| ÖLFLEX CLASSIC 115 CY 4 G1,5 | Lapp 1136304 | 4 G1,5 | 8,2 | 100.0 | 135 |
| ÖLFLEX CLASSIC 115 CY 4 X1,5 | Lapp 1136904 | 4 X1,5 | 8,2 | 100.0 | 135 |
| ÖLFLEX CLASSIC 115 CY 5 G1,5 | Lapp 1136305 | 5 G1,5 | 8,9 | 119.0 | 148 |
| ÖLFLEX CLASSIC 115 CY 5 X1,5 | Lapp 1136905 | 5 X1,5 | 8,9 | 119.0 | 148 |
| ÖLFLEX CLASSIC 115 CY 7 G1,5 | Lapp 1136307 | 7 G1,5 | 9,9 | 154.0 | 192 |
| ÖLFLEX CLASSIC 115 CY 7 X1,5 | Lapp 1136907 | 7 X1,5 | 9,9 | 154.0 | 192 |
| ÖLFLEX CLASSIC 115 CY 12 G1,5 | Lapp 1136312 | 12 G1,5 | 13.0 | 268.0 | 365 |

ÖLFLEX CLASSIC 115 CY 7 G2,5_

Lapp 1136407



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX CLASSIC 115 CY 18 G1,5 | Lapp 1136318 | 18 G1,5 | 15,6 | 373.0 | 520 |
| ÖLFLEX CLASSIC 115 CY 25 G1,5 | Lapp 1136325 | 25 G1,5 | 17,9 | 530.0 | 734 |
| ÖLFLEX CLASSIC 115 CY 34 G1,5 | Lapp 1136334 | 34 G1,5 | 20,8 | 683.0 | 944 |
| ÖLFLEX CLASSIC 115 CY 3 G2,5 | Lapp 1136403 | 3 G2,5 | 8,9 | 118.0 | 151 |
| ÖLFLEX CLASSIC 115 CY 4 G2,5 | Lapp 1136404 | 4 G2,5 | 9,9 | 147.0 | 188 |
| ÖLFLEX CLASSIC 115 CY 5 G2,5 | Lapp 1136405 | 5 G2,5 | 11.0 | 176.0 | 270 |
| ÖLFLEX CLASSIC 115 CY 7 G2,5 | Lapp 1136407 | 7 G2,5 | 11,9 | 253.0 | 340 |
| ÖLFLEX CLASSIC 115 CY 12 G2,5 | Lapp 1136412 | 12 G2,5 | 16.0 | 355.0 | 540 |
| ÖLFLEX CLASSIC 115 CY 18 G2,5 | Lapp 1136418 | 18 G2,5 | 19.0 | 569.0 | 782 |
| ÖLFLEX CLASSIC 115 CY 25 G2,5 | Lapp 1136425 | 25 G2,5 | 22,2 | 827.0 | 1358 |
| ÖLFLEX CLASSIC 115 CY 4 G4 | Lapp 1136504 | 4 G4 | 11,6 | 248.0 | 305 |
| ÖLFLEX CLASSIC 115 CY 7 G4 | Lapp 1136507 | 7 G4 | 14,4 | 355.0 | 500 |
| ÖLFLEX CLASSIC 115 CY 4 G6 | Lapp 1136604 | 4 G6 | 14,2 | 343.0 | 440 |
| ÖLFLEX CLASSIC 115 CY 7 G6 | Lapp 1136607 | 7 G6 | 17.0 | 505.0 | 672 |
| ÖLFLEX CLASSIC 115 CY 4 G10 | Lapp 1136614 | 4 G10 | 17,2 | 535.0 | 680 |
| ÖLFLEX CLASSIC 115 CY 5 G10 | Lapp 1136615 | 5 G10 | 19,5 | 592.0 | 824 |
| ÖLFLEX CLASSIC 115 CY 4 G16 | Lapp 1136624 | 4 G16 | 20,2 | 800.0 | 1050 |
| ÖLFLEX CLASSIC 115 CY 5 G16 | Lapp 1136625 | 5 G16 | 22,6 | 895.0 | 1285 |
| ÖLFLEX CLASSIC 115 CY 4 G25 | Lapp 1136634 | 4 G25 | 25,1 | 1075.0 | 1413 |
| ÖLFLEX CLASSIC 115 CY 5 G25 | Lapp 1136635 | 5 G25 | 28.0 | 1400.0 | 1976 |
| ÖLFLEX CLASSIC 115 CY 4 G35 | Lapp 1136638 | 4 G35 | 28.0 | 1576.0 | 2070 |