



**Description:** ÖLFLEX CLASSIC 115 CY 7 X1,0\_

**Lapp code:** Lapp 1136857

The **Test voltage** of the cable Lapp 1136857 is Core/core: 4000 V Core/screen: 2000 V.

## Application range

- Measurement and control technology
- Office machines and systems for data processing

## Product Make-up

- Fine-wire strand made of bare copper wires
- PVC insulation LAPP P8/1
- Plastic foil wrapping
- Tinned-copper braiding
- PVC outer sheath, grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 1136857 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 115 CY					
ÖLFLEX CLASSIC 115 CY 2 X0,5	Lapp 1136752	2 X0,5	5,8	36.0	45
ÖLFLEX CLASSIC 115 CY 3 G0,5	Lapp 1136003	3 G0,5	6,1	43.0	59
ÖLFLEX CLASSIC 115 CY 3 X0,5	Lapp 1136753	3 X0,5	6,1	43.0	59
ÖLFLEX CLASSIC 115 CY 4 G0,5	Lapp 1136004	4 G0,5	6,5	49.0	71
ÖLFLEX CLASSIC 115 CY 4 X0,5	Lapp 1136754	4 X0,5	6,5	49.0	71
ÖLFLEX CLASSIC 115 CY 5 G0,5	Lapp 1136005	5 G0,5	7.0	57.0	86
ÖLFLEX CLASSIC 115 CY 5 X0,5	Lapp 1136755	5 X0,5	7.0	57.0	86
ÖLFLEX CLASSIC 115 CY 7 G0,5	Lapp 1136007	7 G0,5	7,5	69.0	105
ÖLFLEX CLASSIC 115 CY 7 X0,5	Lapp 1136757	7 X0,5	7,5	69.0	105
ÖLFLEX CLASSIC 115 CY 12 G0,5	Lapp 1136012	12 G0,5	9,9	104.0	200
ÖLFLEX CLASSIC 115 CY 12 X0,5	Lapp 1136762	12 X0,5	9,9	104.0	200
ÖLFLEX CLASSIC 115 CY 18 G0,5	Lapp 1136018	18 G0,5	11,5	141.0	275
ÖLFLEX CLASSIC 115 CY 18 X0,5	Lapp 1136768	18 X0,5	11,5	141.0	275
ÖLFLEX CLASSIC 115 CY 25 G0,5	Lapp 1136025	25 G0,5	13,4	211.0	350
ÖLFLEX CLASSIC 115 CY 25 X0,5	Lapp 1136775	25 X0,5	13,4	211.0	350
ÖLFLEX CLASSIC 115 CY 2 X0,75	Lapp 1136802	2 X0,75	6,2	43.0	56
ÖLFLEX CLASSIC 115 CY 3 G0,75	Lapp 1136103	3 G0,75	6,5	52.0	70
ÖLFLEX CLASSIC 115 CY 3 X0,75	Lapp 1136803	3 X0,75	6,5	52.0	70
ÖLFLEX CLASSIC 115 CY 4 G0,75	Lapp 1136104	4 G0,75	7.0	61.0	95
ÖLFLEX CLASSIC 115 CY 4 X0,75	Lapp 1136804	4 X0,75	7.0	61.0	95
ÖLFLEX CLASSIC 115 CY 5 G0,75	Lapp 1136105	5 G0,75	7,7	72.0	108
ÖLFLEX CLASSIC 115 CY 5 X0,75	Lapp 1136805	5 X0,75	7,7	72.0	108
ÖLFLEX CLASSIC 115 CY 7 G0,75	Lapp 1136107	7 G0,75	8,3	89.0	127
ÖLFLEX CLASSIC 115 CY 7 X0,75	Lapp 1136807	7 X0,75	8,3	89.0	127

# ÖLFLEX CLASSIC 115 CY 7 X1,0\_

## Lapp 1136857



Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX CLASSIC 115 CY 12 G0,75	Lapp 1136112	12 G0,75	10,9	138.0	232
ÖLFLEX CLASSIC 115 CY 18 G0,75	Lapp 1136118	18 G0,75	12,7	211.0	315
ÖLFLEX CLASSIC 115 CY 25 G0,75	Lapp 1136125	25 G0,75	14,8	280.0	435
ÖLFLEX CLASSIC 115 CY 25 X0,75	Lapp 1136825	25 X0,75	14,8	280.0	435
ÖLFLEX CLASSIC 115 CY 2 X1,0	Lapp 1136852	2 X1,0	6,5	51.0	71
ÖLFLEX CLASSIC 115 CY 3 G1,0	Lapp 1136203	3 G1,0	6,8	62.0	86
ÖLFLEX CLASSIC 115 CY 3 X1,0	Lapp 1136853	3 X1,0	6,8	62.0	86
ÖLFLEX CLASSIC 115 CY 4 G1,0	Lapp 1136204	4 G1,0	7,3	74.0	98
ÖLFLEX CLASSIC 115 CY 4 X1,0	Lapp 1136854	4 X1,0	7,3	74.0	98
ÖLFLEX CLASSIC 115 CY 5 G1,0	Lapp 1136205	5 G1,0	8,1	88.0	121
ÖLFLEX CLASSIC 115 CY 5 X1,0	Lapp 1136855	5 X1,0	8,1	88.0	121
ÖLFLEX CLASSIC 115 CY 7 G1,0	Lapp 1136207	7 G1,0	8,8	112.0	147
ÖLFLEX CLASSIC 115 CY 7 X1,0	Lapp 1136857	7 X1,0	8,8	112.0	147
ÖLFLEX CLASSIC 115 CY 12 G1,0	Lapp 1136212	12 G1,0	11,5	185.0	285
ÖLFLEX CLASSIC 115 CY 18 G1,0	Lapp 1136218	18 G1,0	13,9	268.0	395
ÖLFLEX CLASSIC 115 CY 25 G1,0	Lapp 1136225	25 G1,0	15,9	354.0	486
ÖLFLEX CLASSIC 115 CY 2 X1,5	Lapp 1136902	2 X1,5	7,1	65.0	86
ÖLFLEX CLASSIC 115 CY 3 G1,5	Lapp 1136303	3 G1,5	7,5	82.0	112
ÖLFLEX CLASSIC 115 CY 3 X1,5	Lapp 1136903	3 X1,5	7,5	82.0	112
ÖLFLEX CLASSIC 115 CY 4 G1,5	Lapp 1136304	4 G1,5	8,2	100.0	135
ÖLFLEX CLASSIC 115 CY 4 X1,5	Lapp 1136904	4 X1,5	8,2	100.0	135
ÖLFLEX CLASSIC 115 CY 5 G1,5	Lapp 1136305	5 G1,5	8,9	119.0	148
ÖLFLEX CLASSIC 115 CY 5 X1,5	Lapp 1136905	5 X1,5	8,9	119.0	148
ÖLFLEX CLASSIC 115 CY 7 G1,5	Lapp 1136307	7 G1,5	9,9	154.0	192
ÖLFLEX CLASSIC 115 CY 7 X1,5	Lapp 1136907	7 X1,5	9,9	154.0	192
ÖLFLEX CLASSIC 115 CY 12 G1,5	Lapp 1136312	12 G1,5	13.0	268.0	365

# ÖLFLEX CLASSIC 115 CY 7 X1,0\_

Lapp 1136857



Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX CLASSIC 115 CY 18 G1,5	Lapp 1136318	18 G1,5	15,6	373.0	520
ÖLFLEX CLASSIC 115 CY 25 G1,5	Lapp 1136325	25 G1,5	17,9	530.0	734
ÖLFLEX CLASSIC 115 CY 34 G1,5	Lapp 1136334	34 G1,5	20,8	683.0	944
ÖLFLEX CLASSIC 115 CY 3 G2,5	Lapp 1136403	3 G2,5	8,9	118.0	151
ÖLFLEX CLASSIC 115 CY 4 G2,5	Lapp 1136404	4 G2,5	9,9	147.0	188
ÖLFLEX CLASSIC 115 CY 5 G2,5	Lapp 1136405	5 G2,5	11.0	176.0	270
ÖLFLEX CLASSIC 115 CY 7 G2,5	Lapp 1136407	7 G2,5	11,9	253.0	340
ÖLFLEX CLASSIC 115 CY 12 G2,5	Lapp 1136412	12 G2,5	16.0	355.0	540
ÖLFLEX CLASSIC 115 CY 18 G2,5	Lapp 1136418	18 G2,5	19.0	569.0	782
ÖLFLEX CLASSIC 115 CY 25 G2,5	Lapp 1136425	25 G2,5	22,2	827.0	1358
ÖLFLEX CLASSIC 115 CY 4 G4	Lapp 1136504	4 G4	11,6	248.0	305
ÖLFLEX CLASSIC 115 CY 7 G4	Lapp 1136507	7 G4	14,4	355.0	500
ÖLFLEX CLASSIC 115 CY 4 G6	Lapp 1136604	4 G6	14,2	343.0	440
ÖLFLEX CLASSIC 115 CY 7 G6	Lapp 1136607	7 G6	17.0	505.0	672
ÖLFLEX CLASSIC 115 CY 4 G10	Lapp 1136614	4 G10	17,2	535.0	680
ÖLFLEX CLASSIC 115 CY 5 G10	Lapp 1136615	5 G10	19,5	592.0	824
ÖLFLEX CLASSIC 115 CY 4 G16	Lapp 1136624	4 G16	20,2	800.0	1050
ÖLFLEX CLASSIC 115 CY 5 G16	Lapp 1136625	5 G16	22,6	895.0	1285
ÖLFLEX CLASSIC 115 CY 4 G25	Lapp 1136634	4 G25	25,1	1075.0	1413
ÖLFLEX CLASSIC 115 CY 5 G25	Lapp 1136635	5 G25	28.0	1400.0	1976
ÖLFLEX CLASSIC 115 CY 4 G35	Lapp 1136638	4 G35	28.0	1576.0	2070