



Description: ÖLFLEX CLASSIC 130 H BK 0,6-1 kV 5 G 6_

Lapp code: Lapp 1123439

The **Test voltage** of the cable Lapp 1123439 is 4000 V.

Application range

- Public buildings
- Plant engineering
Industrial machinery
Heating and air-conditioning systems
- Particularly where human and animal life as well as valuable property are exposed to high risk of fire hazards
- For outdoor applications
- Note: for the use of AWM (Appliance Wiring Material) cables in industrial machinery (USA) according to NFPA 79 Ed. 2012: please see the catalogue appendix table T29

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: Halogen-free
- Outer sheath made of special halogen-free compound, black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 1123439 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|---|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® CLASSIC 130 H 0.6/1 kV - coloured cores | | | | | |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 2 X 1,0 | Lapp 1123410 | 2 X 1,0 | 8,6 | 19.2 | 107 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 3 G 1,0 | Lapp 1123411 | 3 G 1,0 | 9.0 | 28.8 | 123 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 4 G 1,0 | Lapp 1123412 | 4 G 1,0 | 9,6 | 38.4 | 144 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 5 G 1,0 | Lapp 1123413 | 5 G 1,0 | 10,4 | 48.0 | 167 |
| ÖLFLEX® CLASSIC 130 H 0.6/1 kV - numbered cores | | | | | |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 7 G 1,0 | Lapp 1123414 | 7 G 1,0 | 11,1 | 67.2 | 206 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 12 G 1,0 | Lapp 1123415 | 12 G 1,0 | 14.0 | 115.2 | 314 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 18 G 1,0 | Lapp 1123416 | 18 G 1,0 | 16,1 | 172.8 | 428 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 25 G 1,0 | Lapp 1123417 | 25 G 1,0 | 18,6 | 240.0 | 569 |
| ÖLFLEX® CLASSIC 130 H 0.6/1 kV - coloured cores | | | | | |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 2 X 1,5 | Lapp 1123418 | 2 X 1,5 | 9,6 | 28.8 | 137 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 3 G 1,5 | Lapp 1123419 | 3 G 1,5 | 10,1 | 43.2 | 161 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 4 G 1,5 | Lapp 1123420 | 4 G 1,5 | 10,8 | 57.6 | 190 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 5 G 1,5 | Lapp 1123421 | 5 G 1,5 | 11,7 | 72.0 | 221 |
| ÖLFLEX® CLASSIC 130 H 0.6/1 kV - numbered cores | | | | | |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 7 G 1,5 | Lapp 1123422 | 7 G 1,5 | 12,6 | 100.8 | 276 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 12 G 1,5 | Lapp 1123423 | 12 G 1,5 | 16,1 | 172.8 | 427 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 18 G 1,5 | Lapp 1123424 | 18 G 1,5 | 18,8 | 259.2 | 596 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 25 G 1,5 | Lapp 1123425 | 25 G 1,5 | 21,7 | 360.0 | 799 |
| ÖLFLEX® CLASSIC 130 H 0.6/1 kV - coloured cores | | | | | |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 2 X 2,5 | Lapp 1123426 | 2 X 2,5 | 10,8 | 48.0 | 184 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 3 G 2,5 | Lapp 1123427 | 3 G 2,5 | 11,3 | 72.0 | 219 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 4 G 2,5 | Lapp 1123428 | 4 G 2,5 | 12,2 | 96.0 | 262 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 5 G 2,5 | Lapp 1123429 | 5 G 2,5 | 13,3 | 120.0 | 307 |
| ÖLFLEX® CLASSIC 130 H 0.6/1 kV - numbered cores | | | | | |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 7 G 2,5 | Lapp 1123430 | 7 G 2,5 | 14,4 | 168.0 | 390 |

ÖLFLEX CLASSIC 130 H BK 0,6-1 kV 5 G 6_

Lapp 1123439



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|---|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 12 G 2,5 | Lapp 1123431 | 12 G 2,5 | 18,7 | 288.0 | 624 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 18 G 2,5 | Lapp 1123432 | 18 G 2,5 | 22.0 | 432.0 | 879 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 25 G 2,5 | Lapp 1123433 | 25 G 2,5 | 25,8 | 600.0 | 1212 |
| ÖLFLEX® CLASSIC 130 H 0.6/1 kV - coloured cores | | | | | |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 3 G 4 | Lapp 1123434 | 3 G 4 | 12,6 | 115.2 | 290 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 4 G 4 | Lapp 1123435 | 4 G 4 | 13,7 | 153.6 | 351 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 5 G 4 | Lapp 1123436 | 5 G 4 | 14,9 | 192.0 | 416 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 3 G 6 | Lapp 1123437 | 3 G 6 | 13,9 | 172.8 | 377 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 4 G 6 | Lapp 1123438 | 4 G 6 | 15,1 | 230.4 | 463 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 5 G 6 | Lapp 1123439 | 5 G 6 | 16,8 | 288.0 | 559 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 4 G 10 | Lapp 1123440 | 4 G 10 | 18,7 | 384.0 | 757 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 5 G 10 | Lapp 1123441 | 5 G 10 | 20,7 | 480.0 | 915 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 4 G 16 | Lapp 1123442 | 4 G 16 | 21,3 | 614.4 | 1070 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 5 G 16 | Lapp 1123443 | 5 G 16 | 23,6 | 768.0 | 1296 |
| ÖLFLEX CLASSIC 130 H BK 0,6/1 kV 4 G 25 | Lapp 1123444 | 4 G 25 | 26,2 | 960.0 | 1631 |