Description: **ÖLFLEX CLASSIC 135 CH BK 0,6-1 kV 5 G 1,0_**
Lapp code: Lapp 1123463

The **Test voltage** of the cable Lapp 1123463 is Core/core: 4000 V Core/screen: 2000 V.

Application range

- Public buildings
- Plant engineering
  Industrial machinery
  Heating and air-conditioning systems
- Particularly where human and animal life as well as valuable property are exposed to high risk of fire hazards
- For outdoor applications
- Note: for the use of AWM (Appliance Wiring Material) cables in industrial machinery (USA) according to NFPA 79 Ed. 2012: please see the catalogue appendix table T29

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: Halogen-free
- Halogen-free plastic foil wrapping
- Tinned-copper braiding
- Outer sheath made of special halogen-free coumpound, black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 1123463 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 135 CH 0.6/1 kV - coloured cores					
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 2 X 1,0	Lapp 1123460	2 X 1,0	9,4	39.5	120
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 3 G 1,0	Lapp 1123461	3 G 1,0	9,8	51.0	140
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 4 G 1,0	Lapp 1123462	4 G 1,0	10,4	62.8	165
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 5 G 1,0	Lapp 1123463	5 G 1,0	11,2	76.0	191
ÖLFLEX® CLASSIC 135 CH 0.6/1 kV - numbered cores					
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 7 G 1,0	Lapp 1123464	7 G 1,0	11,9	97.2	231
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 12 G 1,0	Lapp 1123465	12 G 1,0	15.0	169.1	360
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 18 G 1,0	Lapp 1123466	18 G 1,0	17,3	238.2	494
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 25 G 1,0	Lapp 1123467	25 G 1,0	19,8	315.5	643
ÖLFLEX® CLASSIC 135 CH 0.6/1 kV - coloured cores					
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 2 X 1,5	Lapp 1123468	2 X 1,5	10,4	53.2	149
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 3 G 1,5	Lapp 1123469	3 G 1,5	10,9	69.5	177
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 4 G 1,5	Lapp 1123470	4 G 1,5	11,6	86.5	209
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 5 G 1,5	Lapp 1123471	5 G 1,5	12,5	104.3	243
ÖLFLEX® CLASSIC 135 CH 0.6/1 kV - numbered cores					
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 7 G 1,5	Lapp 1123472	7 G 1,5	13,4	136.5	300
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 12 G 1,5	Lapp 1123473	12 G 1,5	17,3	238.3	486
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 18 G 1,5	Lapp 1123474	18 G 1,5	20,2	355.4	691
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 25 G 1,5	Lapp 1123475	25 G 1,5	23,1	475.1	914
ÖLFLEX® CLASSIC 135 CH 0.6/1 kV - coloured cores					
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 2 X 2,5	Lapp 1123476	2 X 2,5	11,6	79.4	197
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 3 G 2,5	Lapp 1123477	3 G 2,5	12,1	106.1	243
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 4 G 2,5	Lapp 1123478	4 G 2,5	13.0	134.3	293

ÖLFLEX CLASSIC 135 CH BK 0,6-1 kV 5 G 1,0_

Lapp 1123463

Product Name	Lapp Nr.	Number of cores and mm² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 5 G 2,5	Lapp 1123479	5 G 2,5	14,1	158.3	342
ÖLFLEX® CLASSIC 135 CH 0.6/1 kV - numbered cores					
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 7 G 2,5	Lapp 1123480	7 G 2,5	15,4	225.0	462
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 12 G 2,5	Lapp 1123481	12 G 2,5	20,1	383.6	718
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 18 G 2,5	Lapp 1123482	18 G 2,5	23,4	548.9	1011
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 25 G 2,5	Lapp 1123483	25 G 2,5	27,4	761.7	1370
ÖLFLEX® CLASSIC 135 CH 0.6/1 kV - coloured cores					
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 3 G 4	Lapp 1123484	3 G 4	13,4	167.7	327
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 4 G 4	Lapp 1123485	4 G 4	14,7	211.9	399
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 5 G 4	Lapp 1123486	5 G 4	15,9	250.3	471
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 3 G 6	Lapp 1123487	3 G 6	14,9	232.1	414
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 4 G 6	Lapp 1123488	4 G 6	16,1	298.5	519
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 5 G 6	Lapp 1123489	5 G 6	17,8	356.1	607
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 4 G 10	Lapp 1123490	4 G 10	20,1	490.6	837
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 5 G 10	Lapp 1123491	5 G 10	21,9	586.6	995
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 4 G 16	Lapp 1123492	4 G 16	22,5	735.1	1157
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 5 G 16	Lapp 1123493	5 G 16	25.0	888.7	1407
ÖLFLEX CLASSIC 135 CH BK 0,6/1 kV 4 G 25	Lapp 1123494	4 G 25	27,8	1126.6	1683