



Description: ÖLFLEX CLASSIC 400 CP 18 G 1,5_

Lapp code: Lapp 1313318

The **Test voltage** of the cable Lapp 1313318 is 4000 V.

Application range

- Machine tools
- Industrial machinery and machine tools
- Measurement, control and electrical applications
- Very suitable for oily wet areas within machinery and production lines that are subject to normal mechanical stress
- Outdoor use is possible within the indicated operating temperature range

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: special PVC
- Cores twisted in layers
- PVC inner sheath, grey
- Tinned-copper braiding
- Special polyurethane outer sheath (PUR)
- Sheath colour: silver grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 1313318 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|---------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® CLASSIC 400 CP | | | | | |
| ÖLFLEX CLASSIC 400 CP 2 X 0,75 | Lapp 1313852 | 2 X 0,75 | 7,4 | 45.0 | 85 |
| ÖLFLEX CLASSIC 400 CP 3 G 0,75 | Lapp 1313103 | 3 G 0,75 | 7,9 | 52.0 | 99 |
| ÖLFLEX CLASSIC 400 CP 3 X 0,75 | Lapp 1313853 | 3 X 0,75 | 7,9 | 52.0 | 99 |
| ÖLFLEX CLASSIC 400 CP 4 G 0,75 | Lapp 1313104 | 4 G 0,75 | 8,4 | 77.0 | 114 |
| ÖLFLEX CLASSIC 400 CP 4 X 0,75 | Lapp 1313854 | 4 X 0,75 | 8,4 | 77.0 | 114 |
| ÖLFLEX CLASSIC 400 CP 5 G 0,75 | Lapp 1313105 | 5 G 0,75 | 8,9 | 84.0 | 130 |
| ÖLFLEX CLASSIC 400 CP 5 X 0,75 | Lapp 1313855 | 5 X 0,75 | 8,9 | 84.0 | 130 |
| ÖLFLEX CLASSIC 400 CP 7 G 0,75 | Lapp 1313107 | 7 G 0,75 | 9,7 | 92.0 | 161 |
| ÖLFLEX CLASSIC 400 CP 7 X 0,75 | Lapp 1313857 | 7 X 0,75 | 9,7 | 92.0 | 161 |
| ÖLFLEX CLASSIC 400 CP 12 G 0,75 | Lapp 1313112 | 12 G 0,75 | 12,3 | 138.0 | 245 |
| ÖLFLEX CLASSIC 400 CP 18 G 0,75 | Lapp 1313118 | 18 G 0,75 | 14,5 | 219.0 | 354 |
| ÖLFLEX CLASSIC 400 CP 25 G 0,75 | Lapp 1313125 | 25 G 0,75 | 16,6 | 277.0 | 463 |
| ÖLFLEX CLASSIC 400 CP 34 G 0,75 | Lapp 1313134 | 34 G 0,75 | 18,9 | 420.0 | 598 |
| ÖLFLEX CLASSIC 400 CP 41 G 0,75 | Lapp 1313141 | 41 G 0,75 | 20,6 | 500.0 | 725 |
| ÖLFLEX CLASSIC 400 CP 2 X 1,0 | Lapp 1313902 | 2 X 1,0 | 7,9 | 50.0 | 97 |
| ÖLFLEX CLASSIC 400 CP 3 G 1,0 | Lapp 1313203 | 3 G 1,0 | 8,2 | 77.0 | 111 |
| ÖLFLEX CLASSIC 400 CP 3 X 1,0 | Lapp 1313903 | 3 X 1,0 | 8,2 | 77.0 | 111 |
| ÖLFLEX CLASSIC 400 CP 4 G 1,0 | Lapp 1313204 | 4 G 1,0 | 8,7 | 87.0 | 129 |
| ÖLFLEX CLASSIC 400 CP 4 X 1,0 | Lapp 1313904 | 4 X 1,0 | 8,7 | 87.0 | 129 |
| ÖLFLEX CLASSIC 400 CP 5 G 1,0 | Lapp 1313205 | 5 G 1,0 | 9,5 | 90.0 | 152 |
| ÖLFLEX CLASSIC 400 CP 7 G 1,0 | Lapp 1313207 | 7 G 1,0 | 10,2 | 110.0 | 184 |
| ÖLFLEX CLASSIC 400 CP 12 G 1,0 | Lapp 1313212 | 12 G 1,0 | 13,3 | 194.0 | 306 |
| ÖLFLEX CLASSIC 400 CP 18 G 1,0 | Lapp 1313218 | 18 G 1,0 | 15,5 | 267.0 | 417 |
| ÖLFLEX CLASSIC 400 CP 25 G 1,0 | Lapp 1313225 | 25 G 1,0 | 17,5 | 379.0 | 541 |

ÖLFLEX CLASSIC 400 CP 18 G 1,5_

Lapp 1313318



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX CLASSIC 400 CP 34 G 1,0 | Lapp 1313234 | 34 G 1,0 | 20,3 | 516.0 | 735 |
| ÖLFLEX CLASSIC 400 CP 41 G 1,0 | Lapp 1313241 | 41 G 1,0 | 22.0 | 610.0 | 860 |
| ÖLFLEX CLASSIC 400 CP 2 X 1,5 | Lapp 1313952 | 2 X 1,5 | 8,5 | 77.0 | 116 |
| ÖLFLEX CLASSIC 400 CP 3 G 1,5 | Lapp 1313303 | 3 G 1,5 | 8,9 | 85.0 | 135 |
| ÖLFLEX CLASSIC 400 CP 3 X 1,5 | Lapp 1313953 | 3 X 1,5 | 8,9 | 85.0 | 135 |
| ÖLFLEX CLASSIC 400 CP 4 G 1,5 | Lapp 1313304 | 4 G 1,5 | 9,6 | 100.0 | 162 |
| ÖLFLEX CLASSIC 400 CP 4 X 1,5 | Lapp 1313954 | 4 X 1,5 | 9,6 | 100.0 | 162 |
| ÖLFLEX CLASSIC 400 CP 5 G 1,5 | Lapp 1313305 | 5 G 1,5 | 10,3 | 120.0 | 187 |
| ÖLFLEX CLASSIC 400 CP 5 X 1,5 | Lapp 1313955 | 5 X 1,5 | 10,3 | 120.0 | 187 |
| ÖLFLEX CLASSIC 400 CP 7 G 1,5 | Lapp 1313307 | 7 G 1,5 | 11,3 | 152.0 | 236 |
| ÖLFLEX CLASSIC 400 CP 7 X 1,5 | Lapp 1313957 | 7 X 1,5 | 11,3 | 152.0 | 236 |
| ÖLFLEX CLASSIC 400 CP 12 G 1,5 | Lapp 1313312 | 12 G 1,5 | 14,8 | 267.0 | 392 |
| ÖLFLEX CLASSIC 400 CP 18 G 1,5 | Lapp 1313318 | 18 G 1,5 | 17,2 | 400.0 | 536 |
| ÖLFLEX CLASSIC 400 CP 25 G 1,5 | Lapp 1313325 | 25 G 1,5 | 20,1 | 572.0 | 742 |
| ÖLFLEX CLASSIC 400 CP 34 G 1,5 | Lapp 1313334 | 34 G 1,5 | 21,9 | 754.0 | 960 |
| ÖLFLEX CLASSIC 400 CP 41 G 1,5 | Lapp 1313341 | 41 G 1,5 | 24,7 | 874.0 | 1118 |
| ÖLFLEX CLASSIC 400 CP 3 G 2,5 | Lapp 1313403 | 3 G 2,5 | 10,3 | 121.0 | 191 |
| ÖLFLEX CLASSIC 400 CP 4 G 2,5 | Lapp 1313404 | 4 G 2,5 | 11,3 | 163.0 | 232 |
| ÖLFLEX CLASSIC 400 CP 5 G 2,5 | Lapp 1313405 | 5 G 2,5 | 12,6 | 199.0 | 282 |
| ÖLFLEX CLASSIC 400 CP 7 G 2,5 | Lapp 1313407 | 7 G 2,5 | 13,9 | 261.0 | 370 |
| ÖLFLEX CLASSIC 400 CP 12 G 2,5 | Lapp 1313412 | 12 G 2,5 | 17,2 | 470.0 | 580 |
| ÖLFLEX CLASSIC 400 CP 4 G 4 | Lapp 1313504 | 4 G 4 | 13,4 | 238.0 | 345 |
| ÖLFLEX CLASSIC 400 CP 5 G 4 | Lapp 1313505 | 5 G 4 | 14,7 | 279.0 | 412 |
| ÖLFLEX CLASSIC 400 CP 4 G 6 | Lapp 1313604 | 4 G 6 | 15,8 | 318.0 | 483 |
| ÖLFLEX CLASSIC 400 CP 5 G 6 | Lapp 1313605 | 5 G 6 | 17,3 | 370.0 | 576 |
| ÖLFLEX CLASSIC 400 CP 4 G 10 | Lapp 1313614 | 4 G 10 | 19.0 | 558.0 | 733 |

ÖLFLEX CLASSIC 400 CP 18 G 1,5_

Lapp 1313318



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX CLASSIC 400 CP 4 G 16 | Lapp 1313624 | 4 G 16 | 22,2 | 804.0 | 1340 |