



Description: ÖLFLEX CLASSIC 400 CP 5 X 1,5_

Lapp code: Lapp 1313955

The **Test voltage** of the cable Lapp 1313955 is 4000 V.

Application range

- Machine tools
- Industrial machinery and machine tools
- Measurement, control and electrical applications
- Very suitable for oily wet areas within machinery and production lines that are subject to normal mechanical stress
- Outdoor use is possible within the indicated operating temperature range

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: special PVC
- Cores twisted in layers
- PVC inner sheath, grey
- Tinned-copper braiding
- Special polyurethane outer sheath (PUR)
- Sheath colour: silver grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 1313955 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 400 CP					
ÖLFLEX CLASSIC 400 CP 2 X 0,75	Lapp 1313852	2 X 0,75	7,4	45.0	85
ÖLFLEX CLASSIC 400 CP 3 G 0,75	Lapp 1313103	3 G 0,75	7,9	52.0	99
ÖLFLEX CLASSIC 400 CP 3 X 0,75	Lapp 1313853	3 X 0,75	7,9	52.0	99
ÖLFLEX CLASSIC 400 CP 4 G 0,75	Lapp 1313104	4 G 0,75	8,4	77.0	114
ÖLFLEX CLASSIC 400 CP 4 X 0,75	Lapp 1313854	4 X 0,75	8,4	77.0	114
ÖLFLEX CLASSIC 400 CP 5 G 0,75	Lapp 1313105	5 G 0,75	8,9	84.0	130
ÖLFLEX CLASSIC 400 CP 5 X 0,75	Lapp 1313855	5 X 0,75	8,9	84.0	130
ÖLFLEX CLASSIC 400 CP 7 G 0,75	Lapp 1313107	7 G 0,75	9,7	92.0	161
ÖLFLEX CLASSIC 400 CP 7 X 0,75	Lapp 1313857	7 X 0,75	9,7	92.0	161
ÖLFLEX CLASSIC 400 CP 12 G 0,75	Lapp 1313112	12 G 0,75	12,3	138.0	245
ÖLFLEX CLASSIC 400 CP 18 G 0,75	Lapp 1313118	18 G 0,75	14,5	219.0	354
ÖLFLEX CLASSIC 400 CP 25 G 0,75	Lapp 1313125	25 G 0,75	16,6	277.0	463
ÖLFLEX CLASSIC 400 CP 34 G 0,75	Lapp 1313134	34 G 0,75	18,9	420.0	598
ÖLFLEX CLASSIC 400 CP 41 G 0,75	Lapp 1313141	41 G 0,75	20,6	500.0	725
ÖLFLEX CLASSIC 400 CP 2 X 1,0	Lapp 1313902	2 X 1,0	7,9	50.0	97
ÖLFLEX CLASSIC 400 CP 3 G 1,0	Lapp 1313203	3 G 1,0	8,2	77.0	111
ÖLFLEX CLASSIC 400 CP 3 X 1,0	Lapp 1313903	3 X 1,0	8,2	77.0	111
ÖLFLEX CLASSIC 400 CP 4 G 1,0	Lapp 1313204	4 G 1,0	8,7	87.0	129
ÖLFLEX CLASSIC 400 CP 4 X 1,0	Lapp 1313904	4 X 1,0	8,7	87.0	129
ÖLFLEX CLASSIC 400 CP 5 G 1,0	Lapp 1313205	5 G 1,0	9,5	90.0	152
ÖLFLEX CLASSIC 400 CP 7 G 1,0	Lapp 1313207	7 G 1,0	10,2	110.0	184
ÖLFLEX CLASSIC 400 CP 12 G 1,0	Lapp 1313212	12 G 1,0	13,3	194.0	306
ÖLFLEX CLASSIC 400 CP 18 G 1,0	Lapp 1313218	18 G 1,0	15,5	267.0	417
ÖLFLEX CLASSIC 400 CP 25 G 1,0	Lapp 1313225	25 G 1,0	17,5	379.0	541

ÖLFLEX CLASSIC 400 CP 5 X 1,5_

Lapp 1313955



Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX CLASSIC 400 CP 34 G 1,0	Lapp 1313234	34 G 1,0	20,3	516.0	735
ÖLFLEX CLASSIC 400 CP 41 G 1,0	Lapp 1313241	41 G 1,0	22.0	610.0	860
ÖLFLEX CLASSIC 400 CP 2 X 1,5	Lapp 1313952	2 X 1,5	8,5	77.0	116
ÖLFLEX CLASSIC 400 CP 3 G 1,5	Lapp 1313303	3 G 1,5	8,9	85.0	135
ÖLFLEX CLASSIC 400 CP 3 X 1,5	Lapp 1313953	3 X 1,5	8,9	85.0	135
ÖLFLEX CLASSIC 400 CP 4 G 1,5	Lapp 1313304	4 G 1,5	9,6	100.0	162
ÖLFLEX CLASSIC 400 CP 4 X 1,5	Lapp 1313954	4 X 1,5	9,6	100.0	162
ÖLFLEX CLASSIC 400 CP 5 G 1,5	Lapp 1313305	5 G 1,5	10,3	120.0	187
ÖLFLEX CLASSIC 400 CP 5 X 1,5	Lapp 1313955	5 X 1,5	10,3	120.0	187
ÖLFLEX CLASSIC 400 CP 7 G 1,5	Lapp 1313307	7 G 1,5	11,3	152.0	236
ÖLFLEX CLASSIC 400 CP 7 X 1,5	Lapp 1313957	7 X 1,5	11,3	152.0	236
ÖLFLEX CLASSIC 400 CP 12 G 1,5	Lapp 1313312	12 G 1,5	14,8	267.0	392
ÖLFLEX CLASSIC 400 CP 18 G 1,5	Lapp 1313318	18 G 1,5	17,2	400.0	536
ÖLFLEX CLASSIC 400 CP 25 G 1,5	Lapp 1313325	25 G 1,5	20,1	572.0	742
ÖLFLEX CLASSIC 400 CP 34 G 1,5	Lapp 1313334	34 G 1,5	21,9	754.0	960
ÖLFLEX CLASSIC 400 CP 41 G 1,5	Lapp 1313341	41 G 1,5	24,7	874.0	1118
ÖLFLEX CLASSIC 400 CP 3 G 2,5	Lapp 1313403	3 G 2,5	10,3	121.0	191
ÖLFLEX CLASSIC 400 CP 4 G 2,5	Lapp 1313404	4 G 2,5	11,3	163.0	232
ÖLFLEX CLASSIC 400 CP 5 G 2,5	Lapp 1313405	5 G 2,5	12,6	199.0	282
ÖLFLEX CLASSIC 400 CP 7 G 2,5	Lapp 1313407	7 G 2,5	13,9	261.0	370
ÖLFLEX CLASSIC 400 CP 12 G 2,5	Lapp 1313412	12 G 2,5	17,2	470.0	580
ÖLFLEX CLASSIC 400 CP 4 G 4	Lapp 1313504	4 G 4	13,4	238.0	345
ÖLFLEX CLASSIC 400 CP 5 G 4	Lapp 1313505	5 G 4	14,7	279.0	412
ÖLFLEX CLASSIC 400 CP 4 G 6	Lapp 1313604	4 G 6	15,8	318.0	483
ÖLFLEX CLASSIC 400 CP 5 G 6	Lapp 1313605	5 G 6	17,3	370.0	576
ÖLFLEX CLASSIC 400 CP 4 G 10	Lapp 1313614	4 G 10	19.0	558.0	733

ÖLFLEX CLASSIC 400 CP 5 X 1,5_

Lapp 1313955



Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX CLASSIC 400 CP 4 G 16	Lapp 1313624	4 G 16	22,2	804.0	1340