



Description: ÖLFLEX CLASSIC 415 CP 25 G 2,5_

Lapp code: Lapp 1314067

The **Test voltage** of the cable Lapp 1314067 is Core/core: 4000 V Core/screen: 2000 V.

Application range

- Machine tools
- Industrial machinery and machine tools
- Measurement, control and electrical applications
- Very suitable for oily wet areas within machinery and production lines that are subject to normal mechanical stress
- Outdoor use is possible within the indicated operating temperature range

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: special PVC
- Cores twisted in layers
- Plastic foil wrapping
- Tinned-copper braiding
- Special polyurethane outer sheath (PUR)
- Sheath colour: silver grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 1314067 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® CLASSIC 415 CP | | | | | |
| ÖLFLEX CLASSIC 415 CP 2 X 0,5 | Lapp 1314000 | 2 X 0,5 | 5,8 | 36.0 | 45 |
| ÖLFLEX CLASSIC 415 CP 3 G 0,5 | Lapp 1314001 | 3 G 0,5 | 6,1 | 43.0 | 59 |
| ÖLFLEX CLASSIC 415 CP 3 X 0,5 | Lapp 1314002 | 3 X 0,5 | 6,1 | 43.0 | 59 |
| ÖLFLEX CLASSIC 415 CP 4 G 0,5 | Lapp 1314003 | 4 G 0,5 | 6,5 | 49.0 | 83 |
| ÖLFLEX CLASSIC 415 CP 4 X 0,5 | Lapp 1314004 | 4 X 0,5 | 6,5 | 49.0 | 83 |
| ÖLFLEX CLASSIC 415 CP 5 G 0,5 | Lapp 1314005 | 5 G 0,5 | 7.0 | 57.0 | 96 |
| ÖLFLEX CLASSIC 415 CP 5 X 0,5 | Lapp 1314006 | 5 X 0,5 | 7.0 | 57.0 | 96 |
| ÖLFLEX CLASSIC 415 CP 7 G 0,5 | Lapp 1314007 | 7 G 0,5 | 7,5 | 69.0 | 136 |
| ÖLFLEX CLASSIC 415 CP 7 X 0,5 | Lapp 1314008 | 7 X 0,5 | 7,5 | 69.0 | 136 |
| ÖLFLEX CLASSIC 415 CP 12 G 0,5 | Lapp 1314010 | 12 G 0,5 | 9,9 | 104.0 | 200 |
| ÖLFLEX CLASSIC 415 CP 12 X 0,5 | Lapp 1314011 | 12 X 0,5 | 9,9 | 104.0 | 200 |
| ÖLFLEX CLASSIC 415 CP 18 G 0,5 | Lapp 1314012 | 18 G 0,5 | 11,5 | 141.0 | 275 |
| ÖLFLEX CLASSIC 415 CP 18 X 0,5 | Lapp 1314013 | 18 X 0,5 | 11,5 | 141.0 | 275 |
| ÖLFLEX CLASSIC 415 CP 25 G 0,5 | Lapp 1314014 | 25 G 0,5 | 13,4 | 211.0 | 350 |
| ÖLFLEX CLASSIC 415 CP 25 X 0,5 | Lapp 1314015 | 25 X 0,5 | 13,4 | 211.0 | 350 |
| ÖLFLEX CLASSIC 415 CP 2 X 0,75 | Lapp 1314017 | 2 X 0,75 | 6,2 | 43.0 | 56 |
| ÖLFLEX CLASSIC 415 CP 3 G 0,75 | Lapp 1314018 | 3 G 0,75 | 6,5 | 52.0 | 70 |
| ÖLFLEX CLASSIC 415 CP 3 X 0,75 | Lapp 1314019 | 3 X 0,75 | 6,5 | 52.0 | 70 |
| ÖLFLEX CLASSIC 415 CP 4 G 0,75 | Lapp 1314020 | 4 G 0,75 | 7.0 | 61.0 | 95 |
| ÖLFLEX CLASSIC 415 CP 4 X 0,75 | Lapp 1314021 | 4 X 0,75 | 7.0 | 61.0 | 95 |
| ÖLFLEX CLASSIC 415 CP 5 G 0,75 | Lapp 1314022 | 5 G 0,75 | 7,7 | 72.0 | 130 |
| ÖLFLEX CLASSIC 415 CP 5 X 0,75 | Lapp 1314023 | 5 X 0,75 | 7,7 | 72.0 | 130 |
| ÖLFLEX CLASSIC 415 CP 7 G 0,75 | Lapp 1314024 | 7 G 0,75 | 8,3 | 89.0 | 168 |
| ÖLFLEX CLASSIC 415 CP 7 X 0,75 | Lapp 1314025 | 7 X 0,75 | 8,3 | 89.0 | 168 |

ÖLFLEX CLASSIC 415 CP 25 G 2,5_

Lapp 1314067



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|---------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX CLASSIC 415 CP 12 G 0,75 | Lapp 1314026 | 12 G 0,75 | 10,9 | 138.0 | 232 |
| ÖLFLEX CLASSIC 415 CP 18 G 0,75 | Lapp 1314027 | 18 G 0,75 | 12,7 | 211.0 | 315 |
| ÖLFLEX CLASSIC 415 CP 25 G 0,75 | Lapp 1314028 | 25 G 0,75 | 14,8 | 280.0 | 435 |
| ÖLFLEX CLASSIC 415 CP 25 X 0,75 | Lapp 1314029 | 25 X 0,75 | 14,8 | 280.0 | 435 |
| ÖLFLEX CLASSIC 415 CP 2 X 1,0 | Lapp 1314032 | 2 X 1,0 | 6,5 | 51.0 | 84 |
| ÖLFLEX CLASSIC 415 CP 3 G 1,0 | Lapp 1314033 | 3 G 1,0 | 6,8 | 62.0 | 110 |
| ÖLFLEX CLASSIC 415 CP 3 X 1,0 | Lapp 1314034 | 3 X 1,0 | 6,8 | 62.0 | 110 |
| ÖLFLEX CLASSIC 415 CP 4 G 1,0 | Lapp 1314035 | 4 G 1,0 | 7,3 | 74.0 | 130 |
| ÖLFLEX CLASSIC 415 CP 4 X 1,0 | Lapp 1314036 | 4 X 1,0 | 7,3 | 74.0 | 130 |
| ÖLFLEX CLASSIC 415 CP 5 G 1,0 | Lapp 1314037 | 5 G 1,0 | 8,1 | 88.0 | 156 |
| ÖLFLEX CLASSIC 415 CP 5 X 1,0 | Lapp 1314038 | 5 X 1,0 | 8,1 | 88.0 | 156 |
| ÖLFLEX CLASSIC 415 CP 7 G 1,0 | Lapp 1314039 | 7 G 1,0 | 8,8 | 112.0 | 192 |
| ÖLFLEX CLASSIC 415 CP 7 X 1,0 | Lapp 1314040 | 7 X 1,0 | 8,8 | 112.0 | 192 |
| ÖLFLEX CLASSIC 415 CP 12 G 1,0 | Lapp 1314041 | 12 G 1,0 | 11,5 | 185.0 | 285 |
| ÖLFLEX CLASSIC 415 CP 18 G 1,0 | Lapp 1314042 | 18 G 1,0 | 13,9 | 268.0 | 395 |
| ÖLFLEX CLASSIC 415 CP 25 G 1,0 | Lapp 1314043 | 25 G 1,0 | 15,9 | 354.0 | 656 |
| ÖLFLEX CLASSIC 415 CP 2 X 1,5 | Lapp 1314046 | 2 X 1,5 | 7,1 | 65.0 | 97 |
| ÖLFLEX CLASSIC 415 CP 3 G 1,5 | Lapp 1314047 | 3 G 1,5 | 7,5 | 82.0 | 125 |
| ÖLFLEX CLASSIC 415 CP 3 X 1,5 | Lapp 1314048 | 3 X 1,5 | 7,5 | 82.0 | 125 |
| ÖLFLEX CLASSIC 415 CP 4 G 1,5 | Lapp 1314049 | 4 G 1,5 | 8,2 | 100.0 | 165 |
| ÖLFLEX CLASSIC 415 CP 4 X 1,5 | Lapp 1314050 | 4 X 1,5 | 8,2 | 100.0 | 165 |
| ÖLFLEX CLASSIC 415 CP 5 G 1,5 | Lapp 1314051 | 5 G 1,5 | 8,9 | 119.0 | 193 |
| ÖLFLEX CLASSIC 415 CP 5 X 1,5 | Lapp 1314052 | 5 X 1,5 | 8,9 | 119.0 | 193 |
| ÖLFLEX CLASSIC 415 CP 7 G 1,5 | Lapp 1314053 | 7 G 1,5 | 9,9 | 154.0 | 245 |
| ÖLFLEX CLASSIC 415 CP 7 X 1,5 | Lapp 1314054 | 7 X 1,5 | 9,9 | 154.0 | 245 |
| ÖLFLEX CLASSIC 415 CP 12 G 1,5 | Lapp 1314055 | 12 G 1,5 | 13.0 | 268.0 | 365 |

ÖLFLEX CLASSIC 415 CP 25 G 2,5_

Lapp 1314067



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX CLASSIC 415 CP 18 G 1,5 | Lapp 1314056 | 18 G 1,5 | 15,6 | 373.0 | 553 |
| ÖLFLEX CLASSIC 415 CP 25 G 1,5 | Lapp 1314057 | 25 G 1,5 | 17,9 | 530.0 | 734 |
| ÖLFLEX CLASSIC 415 CP 34 G 1,5 | Lapp 1314058 | 34 G 1,5 | 20,8 | 683.0 | 944 |
| ÖLFLEX CLASSIC 415 CP 3 G 2,5 | Lapp 1314061 | 3 G 2,5 | 8,9 | 118.0 | 188 |
| ÖLFLEX CLASSIC 415 CP 4 G 2,5 | Lapp 1314062 | 4 G 2,5 | 9,9 | 147.0 | 236 |
| ÖLFLEX CLASSIC 415 CP 5 G 2,5 | Lapp 1314063 | 5 G 2,5 | 11,0 | 176.0 | 270 |
| ÖLFLEX CLASSIC 415 CP 7 G 2,5 | Lapp 1314064 | 7 G 2,5 | 11,9 | 253.0 | 340 |
| ÖLFLEX CLASSIC 415 CP 12 G 2,5 | Lapp 1314065 | 12 G 2,5 | 16,0 | 355.0 | 589 |
| ÖLFLEX CLASSIC 415 CP 18 G 2,5 | Lapp 1314066 | 18 G 2,5 | 19,0 | 569.0 | 978 |
| ÖLFLEX CLASSIC 415 CP 25 G 2,5 | Lapp 1314067 | 25 G 2,5 | 22,2 | 827.0 | 1358 |
| ÖLFLEX CLASSIC 415 CP 4 G 4 | Lapp 1314068 | 4 G 4 | 11,6 | 248.0 | 305 |
| ÖLFLEX CLASSIC 415 CP 7 G 4 | Lapp 1314070 | 7 G 4 | 14,4 | 355.0 | 500 |
| ÖLFLEX CLASSIC 415 CP 4 G 6 | Lapp 1314071 | 4 G 6 | 14,2 | 343.0 | 440 |
| ÖLFLEX CLASSIC 415 CP 7 G 6 | Lapp 1314073 | 7 G 6 | 17,0 | 505.0 | 672 |
| ÖLFLEX CLASSIC 415 CP 4 G 10 | Lapp 1314074 | 4 G 10 | 17,2 | 535.0 | 710 |
| ÖLFLEX CLASSIC 415 CP 4 G 16 | Lapp 1314075 | 4 G 16 | 20,2 | 800.0 | 1050 |
| ÖLFLEX CLASSIC 415 CP 4 G 25 | Lapp 1314076 | 4 G 25 | 25,1 | 1075.0 | 1570 |
| ÖLFLEX CLASSIC 415 CP 4 G 35 | Lapp 1314077 | 4 G 35 | 28,0 | 1576.0 | 2070 |