



Description: ÖLFLEX CLASSIC FD 810 CP 5 G 6_

Lapp code: Lapp 0026484

The **Test voltage** of the cable Lapp 0026484 is 4000 V.

Application range

- In power chains or moving machine parts
- Particularly in wet areas of machine tools and transfer lines
- Mechanical engineering
- Suitable for use in measuring, control and regulating circuits
- Power circuits for electrical equipments used in automation engineering

Product Make-up

- Extra-fine wire strand made of bare copper wires (class 6)
- Core insulation: PVC
- Cores twisted in short lay lengths
- Non-woven wrapping
- PVC inner sheath
- Tinned-copper braiding
- PUR outer sheath, grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 0026484 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|------------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® CLASSIC FD 810 CP | | | | | |
| ÖLFLEX CLASSIC FD 810 CP 2 X 0,5 | Lapp 0026400 | 2 X 0,5 | 6.9 | 33.0 | 70 |
| ÖLFLEX CLASSIC FD 810 CP 3 G 0,5 | Lapp 0026401 | 3 G 0,5 | 7.3 | 39.0 | 80 |
| ÖLFLEX CLASSIC FD 810 CP 4 G 0,5 | Lapp 0026402 | 4 G 0,5 | 7.9 | 46.0 | 94 |
| ÖLFLEX CLASSIC FD 810 CP 5 G 0,5 | Lapp 0026403 | 5 G 0,5 | 8.4 | 54.0 | 106 |
| ÖLFLEX CLASSIC FD 810 CP 7 G 0,5 | Lapp 0026404 | 7 G 0,5 | 9.8 | 70.0 | 138 |
| ÖLFLEX CLASSIC FD 810 CP 12 G 0,5 | Lapp 0026405 | 12 G 0,5 | 11.3 | 100.0 | 194 |
| ÖLFLEX CLASSIC FD 810 CP 2 X 0,75 | Lapp 0026419 | 2 X 0,75 | 7.3 | 39.0 | 81 |
| ÖLFLEX CLASSIC FD 810 CP 3 G 0,75 | Lapp 0026420 | 3 G 0,75 | 7.8 | 48.0 | 95 |
| ÖLFLEX CLASSIC FD 810 CP 4 G 0,75 | Lapp 0026421 | 4 G 0,75 | 8.4 | 59.0 | 111 |
| ÖLFLEX CLASSIC FD 810 CP 5 G 0,75 | Lapp 0026422 | 5 G 0,75 | 9.0 | 69.0 | 128 |
| ÖLFLEX CLASSIC FD 810 CP 7 G 0,75 | Lapp 0026423 | 7 G 0,75 | 10.7 | 90.0 | 171 |
| ÖLFLEX CLASSIC FD 810 CP 12 G 0,75 | Lapp 0026424 | 12 G 0,75 | 12.4 | 129.0 | 244 |
| ÖLFLEX CLASSIC FD 810 CP 16 G 0,75 | Lapp 0026425 | 16 G 0,75 | 14.2 | 186.0 | 328 |
| ÖLFLEX CLASSIC FD 810 CP 18 G 0,75 | Lapp 0026426 | 18 G 0,75 | 14.9 | 205.0 | 356 |
| ÖLFLEX CLASSIC FD 810 CP 25 G 0,75 | Lapp 0026427 | 25 G 0,75 | 17.4 | 271.0 | 479 |
| ÖLFLEX CLASSIC FD 810 CP 2 X 1,0 | Lapp 0026430 | 2 X 1,0 | 7.7 | 46.0 | 93 |
| ÖLFLEX CLASSIC FD 810 CP 3 G 1,0 | Lapp 0026431 | 3 G 1,0 | 8.2 | 57.0 | 109 |
| ÖLFLEX CLASSIC FD 810 CP 4 G 1,0 | Lapp 0026432 | 4 G 1,0 | 8.9 | 70.0 | 129 |
| ÖLFLEX CLASSIC FD 810 CP 5 G 1,0 | Lapp 0026433 | 5 G 1,0 | 9.8 | 81.0 | 154 |
| ÖLFLEX CLASSIC FD 810 CP 7 G 1,0 | Lapp 0026434 | 7 G 1,0 | 11.4 | 110.0 | 200 |
| ÖLFLEX CLASSIC FD 810 CP 12 G 1,0 | Lapp 0026435 | 12 G 1,0 | 13.4 | 182.0 | 304 |
| ÖLFLEX CLASSIC FD 810 CP 18 G 1,0 | Lapp 0026438 | 18 G 1,0 | 16.1 | 254.0 | 429 |
| ÖLFLEX CLASSIC FD 810 CP 25 G 1,0 | Lapp 0026439 | 25 G 1,0 | 18.8 | 365.0 | 593 |
| ÖLFLEX CLASSIC FD 810 CP 2 X 1,5 | Lapp 0026449 | 2 X 1,5 | 8.4 | 58.0 | 112 |

ÖLFLEX CLASSIC FD 810 CP 5 G 6_

Lapp 0026484



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-----------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX CLASSIC FD 810 CP 3 G 1,5 | Lapp 0026450 | 3 G 1,5 | 9.0 | 75.0 | 133 |
| ÖLFLEX CLASSIC FD 810 CP 4 G 1,5 | Lapp 0026451 | 4 G 1,5 | 9.9 | 91.0 | 163 |
| ÖLFLEX CLASSIC FD 810 CP 5 G 1,5 | Lapp 0026452 | 5 G 1,5 | 10.9 | 112.0 | 193 |
| ÖLFLEX CLASSIC FD 810 CP 7 G 1,5 | Lapp 0026453 | 7 G 1,5 | 12.7 | 145.0 | 252 |
| ÖLFLEX CLASSIC FD 810 CP 12 G 1,5 | Lapp 0026454 | 12 G 1,5 | 15.1 | 247.0 | 391 |
| ÖLFLEX CLASSIC FD 810 CP 18 G 1,5 | Lapp 0026456 | 18 G 1,5 | 17.8 | 348.0 | 542 |
| ÖLFLEX CLASSIC FD 810 CP 25 G 1,5 | Lapp 0026457 | 25 G 1,5 | 21.2 | 498.0 | 767 |
| ÖLFLEX CLASSIC FD 810 CP 3 G 2,5 | Lapp 0026470 | 3 G 2,5 | 10.8 | 119.0 | 199 |
| ÖLFLEX CLASSIC FD 810 CP 4 G 2,5 | Lapp 0026471 | 4 G 2,5 | 11.8 | 161.0 | 238 |
| ÖLFLEX CLASSIC FD 810 CP 5 G 2,5 | Lapp 0026472 | 5 G 2,5 | 13.2 | 194.0 | 297 |
| ÖLFLEX CLASSIC FD 810 CP 7 G 2,5 | Lapp 0026473 | 7 G 2,5 | 15.8 | 262.0 | 403 |
| ÖLFLEX CLASSIC FD 810 CP 12 G 2,5 | Lapp 0026474 | 12 G 2,5 | 18.2 | 410.0 | 589 |
| ÖLFLEX CLASSIC FD 810 CP 14 G 2,5 | Lapp 0026475 | 14 G 2,5 | 19.8 | 490.0 | 702 |
| ÖLFLEX CLASSIC FD 810 CP 4 G 4 | Lapp 0026481 | 4 G 4 | 13.7 | 238.0 | 349 |
| ÖLFLEX CLASSIC FD 810 CP 4 G 6 | Lapp 0026483 | 4 G 6 | 16.1 | 318.0 | 499 |
| ÖLFLEX CLASSIC FD 810 CP 5 G 6 | Lapp 0026484 | 5 G 6 | 17.7 | 410.0 | 596 |
| ÖLFLEX CLASSIC FD 810 CP 4 G 10 | Lapp 0026485 | 4 G 10 | 20.2 | 521.0 | 842 |
| ÖLFLEX CLASSIC FD 810 CP 4 G 16 | Lapp 0026487 | 4 G 16 | 23.6 | 780.0 | 1173 |