



Description: ÖLFLEX CLASSIC FD 810 CY 4 G 6_

Lapp code: Lapp 0026283

The **Test voltage** of the cable Lapp 0026283 is 4000 V.

Application range

- In power chains or moving machine parts
- Suitable for use in measuring, control and regulating circuits
- Power circuits for electrical equipments used in automation engineering
- Assembly lines, production lines, in all kinds of machines
- Plant engineering

Product Make-up

- Extra-fine wire strand made of bare copper wires (class 6)
- Core insulation: PVC
- Cores twisted in layers in short lay lengths
- PVC inner sheath, grey
- Tinned-copper braiding
- Non-woven wrapping
- PVC outer sheath, grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 0026283 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|------------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® CLASSIC FD 810 CY | | | | | |
| ÖLFLEX CLASSIC FD 810 CY 2 X 0,5 | Lapp 0026200 | 2 X 0,5 | 6.9 | 33.0 | 74 |
| ÖLFLEX CLASSIC FD 810 CY 3 G 0,5 | Lapp 0026201 | 3 G 0,5 | 7.3 | 39.0 | 84 |
| ÖLFLEX CLASSIC FD 810 CY 4 G 0,5 | Lapp 0026202 | 4 G 0,5 | 7.9 | 46.0 | 98 |
| ÖLFLEX CLASSIC FD 810 CY 5 G 0,5 | Lapp 0026203 | 5 G 0,5 | 8.4 | 54.0 | 110 |
| ÖLFLEX CLASSIC FD 810 CY 7 G 0,5 | Lapp 0026204 | 7 G 0,5 | 9.8 | 70.0 | 143 |
| ÖLFLEX CLASSIC FD 810 CY 12 G 0,5 | Lapp 0026205 | 12 G 0,5 | 11.3 | 100.0 | 201 |
| ÖLFLEX CLASSIC FD 810 CY 18 G 0,5 | Lapp 0026206 | 18 G 0,5 | 13.4 | 153.0 | 287 |
| ÖLFLEX CLASSIC FD 810 CY 25 G 0,5 | Lapp 0026207 | 25 G 0,5 | 15.9 | 202.0 | 394 |
| ÖLFLEX CLASSIC FD 810 CY 30 G 0,5 | Lapp 0026208 | 30 G 0,5 | 16.5 | 228.0 | 432 |
| ÖLFLEX CLASSIC FD 810 CY 2 X 0,75 | Lapp 0026219 | 2 X 0,75 | 7.3 | 39.0 | 85 |
| ÖLFLEX CLASSIC FD 810 CY 3 G 0,75 | Lapp 0026220 | 3 G 0,75 | 7.8 | 48.0 | 99 |
| ÖLFLEX CLASSIC FD 810 CY 4 G 0,75 | Lapp 0026221 | 4 G 0,75 | 8.4 | 59.0 | 116 |
| ÖLFLEX CLASSIC FD 810 CY 5 G 0,75 | Lapp 0026222 | 5 G 0,75 | 9.0 | 69.0 | 133 |
| ÖLFLEX CLASSIC FD 810 CY 7 G 0,75 | Lapp 0026223 | 7 G 0,75 | 10.7 | 90.0 | 178 |
| ÖLFLEX CLASSIC FD 810 CY 12 G 0,75 | Lapp 0026224 | 12 G 0,75 | 12.4 | 129.0 | 253 |
| ÖLFLEX CLASSIC FD 810 CY 18 G 0,75 | Lapp 0026226 | 18 G 0,75 | 14.9 | 205.0 | 368 |
| ÖLFLEX CLASSIC FD 810 CY 25 G 0,75 | Lapp 0026227 | 25 G 0,75 | 17.4 | 271.0 | 496 |
| ÖLFLEX CLASSIC FD 810 CY 30 G 0,75 | Lapp 0026229 | 30 G 0,75 | 18.0 | 320.0 | 549 |
| ÖLFLEX CLASSIC FD 810 CY 2 X 1,0 | Lapp 0026230 | 2 X 1,0 | 7.7 | 46.0 | 97 |
| ÖLFLEX CLASSIC FD 810 CY 3 G 1,0 | Lapp 0026231 | 3 G 1,0 | 8.2 | 57.0 | 114 |
| ÖLFLEX CLASSIC FD 810 CY 4 G 1,0 | Lapp 0026232 | 4 G 1,0 | 8.9 | 70.0 | 134 |
| ÖLFLEX CLASSIC FD 810 CY 5 G 1,0 | Lapp 0026233 | 5 G 1,0 | 9.8 | 81.0 | 159 |
| ÖLFLEX CLASSIC FD 810 CY 7 G 1,0 | Lapp 0026234 | 7 G 1,0 | 11.4 | 110.0 | 207 |
| ÖLFLEX CLASSIC FD 810 CY 12 G 1,0 | Lapp 0026235 | 12 G 1,0 | 13.4 | 182.0 | 314 |

ÖLFLEX CLASSIC FD 810 CY 4 G 6_

Lapp 0026283



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-----------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX CLASSIC FD 810 CY 18 G 1,0 | Lapp 0026238 | 18 G 1,0 | 16.1 | 254.0 | 443 |
| ÖLFLEX CLASSIC FD 810 CY 25 G 1,0 | Lapp 0026239 | 25 G 1,0 | 18.8 | 365.0 | 612 |
| ÖLFLEX CLASSIC FD 810 CY 26 G 1,0 | Lapp 0026240 | 26 G 1,0 | 18.8 | 374.0 | 625 |
| ÖLFLEX CLASSIC FD 810 CY 34 G 1,0 | Lapp 0026241 | 34 G 1,0 | 21.5 | 463.0 | 787 |
| ÖLFLEX CLASSIC FD 810 CY 41 G 1,0 | Lapp 0026242 | 41 G 1,0 | 23.2 | 542.0 | 918 |
| ÖLFLEX CLASSIC FD 810 CY 50 G 1,0 | Lapp 0026243 | 50 G 1,0 | 25.3 | 640.0 | 1120 |
| ÖLFLEX CLASSIC FD 810 CY 2 X 1,5 | Lapp 0026249 | 2 X 1,5 | 8.4 | 58.0 | 117 |
| ÖLFLEX CLASSIC FD 810 CY 3 G 1,5 | Lapp 0026250 | 3 G 1,5 | 9.0 | 75.0 | 139 |
| ÖLFLEX CLASSIC FD 810 CY 4 G 1,5 | Lapp 0026251 | 4 G 1,5 | 9.9 | 91.0 | 169 |
| ÖLFLEX CLASSIC FD 810 CY 5 G 1,5 | Lapp 0026252 | 5 G 1,5 | 10.9 | 112.0 | 201 |
| ÖLFLEX CLASSIC FD 810 CY 7 G 1,5 | Lapp 0026253 | 7 G 1,5 | 12.7 | 145.0 | 262 |
| ÖLFLEX CLASSIC FD 810 CY 12 G 1,5 | Lapp 0026254 | 12 G 1,5 | 15.1 | 247.0 | 404 |
| ÖLFLEX CLASSIC FD 810 CY 16 G 1,5 | Lapp 0026255 | 16 G 1,5 | 16.8 | 314.0 | 503 |
| ÖLFLEX CLASSIC FD 810 CY 18 G 1,5 | Lapp 0026256 | 18 G 1,5 | 17.8 | 348.0 | 560 |
| ÖLFLEX CLASSIC FD 810 CY 25 G 1,5 | Lapp 0026257 | 25 G 1,5 | 21.2 | 498.0 | 793 |
| ÖLFLEX CLASSIC FD 810 CY 34 G 1,5 | Lapp 0026259 | 34 G 1,5 | 23.9 | 700.0 | 1005 |
| ÖLFLEX CLASSIC FD 810 CY 3 G 2,5 | Lapp 0026270 | 3 G 2,5 | 10.8 | 119.0 | 207 |
| ÖLFLEX CLASSIC FD 810 CY 4 G 2,5 | Lapp 0026271 | 4 G 2,5 | 11.8 | 161.0 | 247 |
| ÖLFLEX CLASSIC FD 810 CY 5 G 2,5 | Lapp 0026272 | 5 G 2,5 | 13.2 | 194.0 | 307 |
| ÖLFLEX CLASSIC FD 810 CY 7 G 2,5 | Lapp 0026273 | 7 G 2,5 | 15.8 | 262.0 | 418 |
| ÖLFLEX CLASSIC FD 810 CY 4 G 4 | Lapp 0026281 | 4 G 4 | 13.7 | 238.0 | 360 |
| ÖLFLEX CLASSIC FD 810 CY 5 G 4 | Lapp 0026282 | 5 G 4 | 15.3 | 280.0 | 436 |
| ÖLFLEX CLASSIC FD 810 CY 4 G 6 | Lapp 0026283 | 4 G 6 | 16.1 | 318.0 | 514 |
| ÖLFLEX CLASSIC FD 810 CY 4 G 10 | Lapp 0026285 | 4 G 10 | 20.2 | 521.0 | 824 |
| ÖLFLEX CLASSIC FD 810 CY 4 G 16 | Lapp 0026287 | 4 G 16 | 23.6 | 780.0 | 1207 |