



Description: ÖLFLEX CLASSIC FD 810 CY 5 G 1,0_

Lapp code: Lapp 0026233

The **Test voltage** of the cable Lapp 0026233 is 4000 V.

Application range

- In power chains or moving machine parts
- Suitable for use in measuring, control and regulating circuits
- Power circuits for electrical equipments used in automation engineering
- Assembly lines, production lines, in all kinds of machines
- Plant engineering

Product Make-up

- Extra-fine wire strand made of bare copper wires (class 6)
- Core insulation: PVC
- Cores twisted in layers in short lay lengths
- PVC inner sheath, grey
- Tinned-copper braiding
- Non-woven wrapping
- PVC outer sheath, grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 0026233 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC FD 810 CY					
ÖLFLEX CLASSIC FD 810 CY 2 X 0,5	Lapp 0026200	2 X 0,5	6.9	33.0	74
ÖLFLEX CLASSIC FD 810 CY 3 G 0,5	Lapp 0026201	3 G 0,5	7.3	39.0	84
ÖLFLEX CLASSIC FD 810 CY 4 G 0,5	Lapp 0026202	4 G 0,5	7.9	46.0	98
ÖLFLEX CLASSIC FD 810 CY 5 G 0,5	Lapp 0026203	5 G 0,5	8.4	54.0	110
ÖLFLEX CLASSIC FD 810 CY 7 G 0,5	Lapp 0026204	7 G 0,5	9.8	70.0	143
ÖLFLEX CLASSIC FD 810 CY 12 G 0,5	Lapp 0026205	12 G 0,5	11.3	100.0	201
ÖLFLEX CLASSIC FD 810 CY 18 G 0,5	Lapp 0026206	18 G 0,5	13.4	153.0	287
ÖLFLEX CLASSIC FD 810 CY 25 G 0,5	Lapp 0026207	25 G 0,5	15.9	202.0	394
ÖLFLEX CLASSIC FD 810 CY 30 G 0,5	Lapp 0026208	30 G 0,5	16.5	228.0	432
ÖLFLEX CLASSIC FD 810 CY 2 X 0,75	Lapp 0026219	2 X 0,75	7.3	39.0	85
ÖLFLEX CLASSIC FD 810 CY 3 G 0,75	Lapp 0026220	3 G 0,75	7.8	48.0	99
ÖLFLEX CLASSIC FD 810 CY 4 G 0,75	Lapp 0026221	4 G 0,75	8.4	59.0	116
ÖLFLEX CLASSIC FD 810 CY 5 G 0,75	Lapp 0026222	5 G 0,75	9.0	69.0	133
ÖLFLEX CLASSIC FD 810 CY 7 G 0,75	Lapp 0026223	7 G 0,75	10.7	90.0	178
ÖLFLEX CLASSIC FD 810 CY 12 G 0,75	Lapp 0026224	12 G 0,75	12.4	129.0	253
ÖLFLEX CLASSIC FD 810 CY 18 G 0,75	Lapp 0026226	18 G 0,75	14.9	205.0	368
ÖLFLEX CLASSIC FD 810 CY 25 G 0,75	Lapp 0026227	25 G 0,75	17.4	271.0	496
ÖLFLEX CLASSIC FD 810 CY 30 G 0,75	Lapp 0026229	30 G 0,75	18.0	320.0	549
ÖLFLEX CLASSIC FD 810 CY 2 X 1,0	Lapp 0026230	2 X 1,0	7.7	46.0	97
ÖLFLEX CLASSIC FD 810 CY 3 G 1,0	Lapp 0026231	3 G 1,0	8.2	57.0	114
ÖLFLEX CLASSIC FD 810 CY 4 G 1,0	Lapp 0026232	4 G 1,0	8.9	70.0	134
ÖLFLEX CLASSIC FD 810 CY 5 G 1,0	Lapp 0026233	5 G 1,0	9.8	81.0	159
ÖLFLEX CLASSIC FD 810 CY 7 G 1,0	Lapp 0026234	7 G 1,0	11.4	110.0	207
ÖLFLEX CLASSIC FD 810 CY 12 G 1,0	Lapp 0026235	12 G 1,0	13.4	182.0	314

ÖLFLEX CLASSIC FD 810 CY 5 G 1,0_

Lapp 0026233



Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX CLASSIC FD 810 CY 18 G 1,0	Lapp 0026238	18 G 1,0	16.1	254.0	443
ÖLFLEX CLASSIC FD 810 CY 25 G 1,0	Lapp 0026239	25 G 1,0	18.8	365.0	612
ÖLFLEX CLASSIC FD 810 CY 26 G 1,0	Lapp 0026240	26 G 1,0	18.8	374.0	625
ÖLFLEX CLASSIC FD 810 CY 34 G 1,0	Lapp 0026241	34 G 1,0	21.5	463.0	787
ÖLFLEX CLASSIC FD 810 CY 41 G 1,0	Lapp 0026242	41 G 1,0	23.2	542.0	918
ÖLFLEX CLASSIC FD 810 CY 50 G 1,0	Lapp 0026243	50 G 1,0	25.3	640.0	1120
ÖLFLEX CLASSIC FD 810 CY 2 X 1,5	Lapp 0026249	2 X 1,5	8.4	58.0	117
ÖLFLEX CLASSIC FD 810 CY 3 G 1,5	Lapp 0026250	3 G 1,5	9.0	75.0	139
ÖLFLEX CLASSIC FD 810 CY 4 G 1,5	Lapp 0026251	4 G 1,5	9.9	91.0	169
ÖLFLEX CLASSIC FD 810 CY 5 G 1,5	Lapp 0026252	5 G 1,5	10.9	112.0	201
ÖLFLEX CLASSIC FD 810 CY 7 G 1,5	Lapp 0026253	7 G 1,5	12.7	145.0	262
ÖLFLEX CLASSIC FD 810 CY 12 G 1,5	Lapp 0026254	12 G 1,5	15.1	247.0	404
ÖLFLEX CLASSIC FD 810 CY 16 G 1,5	Lapp 0026255	16 G 1,5	16.8	314.0	503
ÖLFLEX CLASSIC FD 810 CY 18 G 1,5	Lapp 0026256	18 G 1,5	17.8	348.0	560
ÖLFLEX CLASSIC FD 810 CY 25 G 1,5	Lapp 0026257	25 G 1,5	21.2	498.0	793
ÖLFLEX CLASSIC FD 810 CY 34 G 1,5	Lapp 0026259	34 G 1,5	23.9	700.0	1005
ÖLFLEX CLASSIC FD 810 CY 3 G 2,5	Lapp 0026270	3 G 2,5	10.8	119.0	207
ÖLFLEX CLASSIC FD 810 CY 4 G 2,5	Lapp 0026271	4 G 2,5	11.8	161.0	247
ÖLFLEX CLASSIC FD 810 CY 5 G 2,5	Lapp 0026272	5 G 2,5	13.2	194.0	307
ÖLFLEX CLASSIC FD 810 CY 7 G 2,5	Lapp 0026273	7 G 2,5	15.8	262.0	418
ÖLFLEX CLASSIC FD 810 CY 4 G 4	Lapp 0026281	4 G 4	13.7	238.0	360
ÖLFLEX CLASSIC FD 810 CY 5 G 4	Lapp 0026282	5 G 4	15.3	280.0	436
ÖLFLEX CLASSIC FD 810 CY 4 G 6	Lapp 0026283	4 G 6	16.1	318.0	514
ÖLFLEX CLASSIC FD 810 CY 4 G 10	Lapp 0026285	4 G 10	20.2	521.0	824
ÖLFLEX CLASSIC FD 810 CY 4 G 16	Lapp 0026287	4 G 16	23.6	780.0	1207