



Description: ÖLFLEX CLASSIC FD 810 P 25 G 0,75_

Lapp code: Lapp 0026327

The **Test voltage** of the cable Lapp 0026327 is 4000 V.

Application range

- In power chains or moving machine parts
- Particularly in wet areas of machine tools and transfer lines
- Mechanical engineering
- Suitable for use in measuring, control and regulating circuits
- Power circuits for electrical equipments used in automation engineering

Product Make-up

- Extra-fine wire strand made of bare copper wires (class 6)
- Core insulation: PVC
- Cores twisted in short lay lengths
- Non-woven wrapping
- PUR outer sheath, grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 0026327 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-----------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® CLASSIC FD 810 P | | | | | |
| ÖLFLEX CLASSIC FD 810 P 2 X 0,5 | Lapp 0026300 | 2 X 0,5 | 5.3 | 10.0 | 36 |
| ÖLFLEX CLASSIC FD 810 P 3 G 0,5 | Lapp 0026301 | 3 G 0,5 | 5.7 | 15.0 | 44 |
| ÖLFLEX CLASSIC FD 810 P 4 G 0,5 | Lapp 0026302 | 4 G 0,5 | 6.3 | 19.0 | 53 |
| ÖLFLEX CLASSIC FD 810 P 5 G 0,5 | Lapp 0026303 | 5 G 0,5 | 6.8 | 24.0 | 62 |
| ÖLFLEX CLASSIC FD 810 P 7 G 0,5 | Lapp 0026304 | 7 G 0,5 | 8.0 | 34.0 | 82 |
| ÖLFLEX CLASSIC FD 810 P 12 G 0,5 | Lapp 0026305 | 12 G 0,5 | 9.5 | 58.0 | 129 |
| ÖLFLEX CLASSIC FD 810 P 18 G 0,5 | Lapp 0026306 | 18 G 0,5 | 11.4 | 86.4 | 185 |
| ÖLFLEX CLASSIC FD 810 P 2 X 0,75 | Lapp 0026319 | 2 X 0,75 | 5.7 | 15.0 | 44 |
| ÖLFLEX CLASSIC FD 810 P 3 G 0,75 | Lapp 0026320 | 3 G 0,75 | 6.2 | 22.0 | 55 |
| ÖLFLEX CLASSIC FD 810 P 4 G 0,75 | Lapp 0026321 | 4 G 0,75 | 6.8 | 29.0 | 67 |
| ÖLFLEX CLASSIC FD 810 P 5 G 0,75 | Lapp 0026322 | 5 G 0,75 | 7.4 | 37.0 | 80 |
| ÖLFLEX CLASSIC FD 810 P 7 G 0,75 | Lapp 0026323 | 7 G 0,75 | 8.9 | 51.0 | 109 |
| ÖLFLEX CLASSIC FD 810 P 12 G 0,75 | Lapp 0026324 | 12 G 0,75 | 10.6 | 87.0 | 172 |
| ÖLFLEX CLASSIC FD 810 P 18 G 0,75 | Lapp 0026326 | 18 G 0,75 | 12.7 | 130.0 | 247 |
| ÖLFLEX CLASSIC FD 810 P 25 G 0,75 | Lapp 0026327 | 25 G 0,75 | 15.2 | 181.0 | 346 |
| ÖLFLEX CLASSIC FD 810 P 2 X 1,0 | Lapp 0026330 | 2 X 1,0 | 6.1 | 20.0 | 52 |
| ÖLFLEX CLASSIC FD 810 P 3 G 1,0 | Lapp 0026331 | 3 G 1,0 | 6.6 | 29.0 | 66 |
| ÖLFLEX CLASSIC FD 810 P 4 G 1,0 | Lapp 0026332 | 4 G 1,0 | 7.3 | 39.0 | 82 |
| ÖLFLEX CLASSIC FD 810 P 5 G 1,0 | Lapp 0026333 | 5 G 1,0 | 8.0 | 48.0 | 97 |
| ÖLFLEX CLASSIC FD 810 P 7 G 1,0 | Lapp 0026334 | 7 G 1,0 | 9.6 | 67.0 | 117 |
| ÖLFLEX CLASSIC FD 810 P 12 G 1,0 | Lapp 0026335 | 12 G 1,0 | 11.4 | 115.0 | 211 |
| ÖLFLEX CLASSIC FD 810 P 18 G 1,0 | Lapp 0026338 | 18 G 1,0 | 13.9 | 173.0 | 310 |
| ÖLFLEX CLASSIC FD 810 P 25 G 1,0 | Lapp 0026339 | 25 G 1,0 | 16.4 | 240.0 | 426 |
| ÖLFLEX CLASSIC FD 810 P 34 G 1,0 | Lapp 0026341 | 34 G 1,0 | 18.9 | 326.4 | 571 |

ÖLFLEX CLASSIC FD 810 P 25 G 0,75_

Lapp 0026327



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|----------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX CLASSIC FD 810 P 41 G 1,0 | Lapp 0026342 | 41 G 1,0 | 20.6 | 394.0 | 684 |
| ÖLFLEX CLASSIC FD 810 P 50 G 1,0 | Lapp 0026343 | 50 G 1,0 | 22.3 | 480.0 | 822 |
| ÖLFLEX CLASSIC FD 810 P 65 G 1,0 | Lapp 0026344 | 65 G 1,0 | 25.4 | 624.0 | 1058 |
| ÖLFLEX CLASSIC FD 810 P 2 X 1,5 | Lapp 0026349 | 2 X 1,5 | 6.8 | 29.0 | 68 |
| ÖLFLEX CLASSIC FD 810 P 3 G 1,5 | Lapp 0026350 | 3 G 1,5 | 7.4 | 43.2 | 86 |
| ÖLFLEX CLASSIC FD 810 P 4 G 1,5 | Lapp 0026351 | 4 G 1,5 | 8.1 | 58.0 | 106 |
| ÖLFLEX CLASSIC FD 810 P 5 G 1,5 | Lapp 0026352 | 5 G 1,5 | 9.1 | 72.0 | 131 |
| ÖLFLEX CLASSIC FD 810 P 7 G 1,5 | Lapp 0026353 | 7 G 1,5 | 10.9 | 101.0 | 178 |
| ÖLFLEX CLASSIC FD 810 P 12 G 1,5 | Lapp 0026354 | 12 G 1,5 | 12.9 | 173.0 | 281 |
| ÖLFLEX CLASSIC FD 810 P 16 G 1,5 | Lapp 0026355 | 16 G 1,5 | 14.6 | 230.0 | 365 |
| ÖLFLEX CLASSIC FD 810 P 18 G 1,5 | Lapp 0026356 | 18 G 1,5 | 15.6 | 259.0 | 411 |
| ÖLFLEX CLASSIC FD 810 P 25 G 1,5 | Lapp 0026357 | 25 G 1,5 | 18.6 | 360.0 | 571 |
| ÖLFLEX CLASSIC FD 810 P 34 G 1,5 | Lapp 0026359 | 34 G 1,5 | 21.1 | 489.6 | 753 |
| ÖLFLEX CLASSIC FD 810 P 42 G 1,5 | Lapp 0026361 | 42 G 1,5 | 23.0 | 629.0 | 919 |
| ÖLFLEX CLASSIC FD 810 P 50 G 1,5 | Lapp 0026362 | 50 G 1,5 | 25.0 | 720.0 | 1093 |
| ÖLFLEX CLASSIC FD 810 P 3 G 2,5 | Lapp 0026370 | 3 G 2,5 | 9.0 | 72.0 | 135 |
| ÖLFLEX CLASSIC FD 810 P 4 G 2,5 | Lapp 0026371 | 4 G 2,5 | 10.0 | 96.0 | 168 |
| ÖLFLEX CLASSIC FD 810 P 5 G 2,5 | Lapp 0026372 | 5 G 2,5 | 11.2 | 120.0 | 206 |
| ÖLFLEX CLASSIC FD 810 P 7 G 2,5 | Lapp 0026373 | 7 G 2,5 | 13.6 | 168.0 | 286 |
| ÖLFLEX CLASSIC FD 810 P 12 G 2,5 | Lapp 0026374 | 12 G 2,5 | 16.0 | 288.0 | 453 |
| ÖLFLEX CLASSIC FD 810 P 14 G 2,5 | Lapp 0026375 | 14 G 2,5 | 17.2 | 336.0 | 525 |
| ÖLFLEX CLASSIC FD 810 P 4 G 4 | Lapp 0026381 | 4 G 4 | 11.7 | 160.0 | 252 |
| ÖLFLEX CLASSIC FD 810 P 5 G 4 | Lapp 0026382 | 5 G 4 | 13.1 | 200.0 | 309 |
| ÖLFLEX CLASSIC FD 810 P 1 G 6 | Lapp 0029200 | 1 G 6 | 6.4 | 60.0 | 84 |
| ÖLFLEX CLASSIC FD 810 P 4 G 6 | Lapp 0026383 | 4 G 6 | 13.9 | 230.0 | 377 |
| ÖLFLEX CLASSIC FD 810 P 1 G 10 | Lapp 0029210 | 1 G 10 | 7.7 | 100.0 | 141 |

ÖLFLEX CLASSIC FD 810 P 25 G 0,75_

Lapp 0026327



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--------------------------------|--------------|---|---------------------|----------------------|----------------|
| ÖLFLEX CLASSIC FD 810 P 4 G 10 | Lapp 0026385 | 4 G 10 | 17.6 | 384.0 | 614 |
| ÖLFLEX CLASSIC FD 810 P 5 G 10 | Lapp 0026386 | 5 G 10 | 19.6 | 480.0 | 751 |
| ÖLFLEX CLASSIC FD 810 P 1 G 16 | Lapp 0029220 | 1 G 16 | 9.2 | 160.0 | 198 |
| ÖLFLEX CLASSIC FD 810 P 4 G 16 | Lapp 0026387 | 4 G 16 | 21.0 | 615.0 | 851 |