



Description: ÖLFLEX CLASSIC FD 810 P 41 G 1,0_

Lapp code: Lapp 0026342

The **Test voltage** of the cable Lapp 0026342 is 4000 V.

Application range

- In power chains or moving machine parts
- Particularly in wet areas of machine tools and transfer lines
- Mechanical engineering
- Suitable for use in measuring, control and regulating circuits
- Power circuits for electrical equipments used in automation engineering

Product Make-up

- Extra-fine wire strand made of bare copper wires (class 6)
- Core insulation: PVC
- Cores twisted in short lay lengths
- Non-woven wrapping
- PUR outer sheath, grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 0026342 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC FD 810 P					
ÖLFLEX CLASSIC FD 810 P 2 X 0,5	Lapp 0026300	2 X 0,5	5.3	10.0	36
ÖLFLEX CLASSIC FD 810 P 3 G 0,5	Lapp 0026301	3 G 0,5	5.7	15.0	44
ÖLFLEX CLASSIC FD 810 P 4 G 0,5	Lapp 0026302	4 G 0,5	6.3	19.0	53
ÖLFLEX CLASSIC FD 810 P 5 G 0,5	Lapp 0026303	5 G 0,5	6.8	24.0	62
ÖLFLEX CLASSIC FD 810 P 7 G 0,5	Lapp 0026304	7 G 0,5	8.0	34.0	82
ÖLFLEX CLASSIC FD 810 P 12 G 0,5	Lapp 0026305	12 G 0,5	9.5	58.0	129
ÖLFLEX CLASSIC FD 810 P 18 G 0,5	Lapp 0026306	18 G 0,5	11.4	86.4	185
ÖLFLEX CLASSIC FD 810 P 2 X 0,75	Lapp 0026319	2 X 0,75	5.7	15.0	44
ÖLFLEX CLASSIC FD 810 P 3 G 0,75	Lapp 0026320	3 G 0,75	6.2	22.0	55
ÖLFLEX CLASSIC FD 810 P 4 G 0,75	Lapp 0026321	4 G 0,75	6.8	29.0	67
ÖLFLEX CLASSIC FD 810 P 5 G 0,75	Lapp 0026322	5 G 0,75	7.4	37.0	80
ÖLFLEX CLASSIC FD 810 P 7 G 0,75	Lapp 0026323	7 G 0,75	8.9	51.0	109
ÖLFLEX CLASSIC FD 810 P 12 G 0,75	Lapp 0026324	12 G 0,75	10.6	87.0	172
ÖLFLEX CLASSIC FD 810 P 18 G 0,75	Lapp 0026326	18 G 0,75	12.7	130.0	247
ÖLFLEX CLASSIC FD 810 P 25 G 0,75	Lapp 0026327	25 G 0,75	15.2	181.0	346
ÖLFLEX CLASSIC FD 810 P 2 X 1,0	Lapp 0026330	2 X 1,0	6.1	20.0	52
ÖLFLEX CLASSIC FD 810 P 3 G 1,0	Lapp 0026331	3 G 1,0	6.6	29.0	66
ÖLFLEX CLASSIC FD 810 P 4 G 1,0	Lapp 0026332	4 G 1,0	7.3	39.0	82
ÖLFLEX CLASSIC FD 810 P 5 G 1,0	Lapp 0026333	5 G 1,0	8.0	48.0	97
ÖLFLEX CLASSIC FD 810 P 7 G 1,0	Lapp 0026334	7 G 1,0	9.6	67.0	117
ÖLFLEX CLASSIC FD 810 P 12 G 1,0	Lapp 0026335	12 G 1,0	11.4	115.0	211
ÖLFLEX CLASSIC FD 810 P 18 G 1,0	Lapp 0026338	18 G 1,0	13.9	173.0	310
ÖLFLEX CLASSIC FD 810 P 25 G 1,0	Lapp 0026339	25 G 1,0	16.4	240.0	426
ÖLFLEX CLASSIC FD 810 P 34 G 1,0	Lapp 0026341	34 G 1,0	18.9	326.4	571

ÖLFLEX CLASSIC FD 810 P 41 G 1,0_

Lapp 0026342



Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX CLASSIC FD 810 P 41 G 1,0	Lapp 0026342	41 G 1,0	20.6	394.0	684
ÖLFLEX CLASSIC FD 810 P 50 G 1,0	Lapp 0026343	50 G 1,0	22.3	480.0	822
ÖLFLEX CLASSIC FD 810 P 65 G 1,0	Lapp 0026344	65 G 1,0	25.4	624.0	1058
ÖLFLEX CLASSIC FD 810 P 2 X 1,5	Lapp 0026349	2 X 1,5	6.8	29.0	68
ÖLFLEX CLASSIC FD 810 P 3 G 1,5	Lapp 0026350	3 G 1,5	7.4	43.2	86
ÖLFLEX CLASSIC FD 810 P 4 G 1,5	Lapp 0026351	4 G 1,5	8.1	58.0	106
ÖLFLEX CLASSIC FD 810 P 5 G 1,5	Lapp 0026352	5 G 1,5	9.1	72.0	131
ÖLFLEX CLASSIC FD 810 P 7 G 1,5	Lapp 0026353	7 G 1,5	10.9	101.0	178
ÖLFLEX CLASSIC FD 810 P 12 G 1,5	Lapp 0026354	12 G 1,5	12.9	173.0	281
ÖLFLEX CLASSIC FD 810 P 16 G 1,5	Lapp 0026355	16 G 1,5	14.6	230.0	365
ÖLFLEX CLASSIC FD 810 P 18 G 1,5	Lapp 0026356	18 G 1,5	15.6	259.0	411
ÖLFLEX CLASSIC FD 810 P 25 G 1,5	Lapp 0026357	25 G 1,5	18.6	360.0	571
ÖLFLEX CLASSIC FD 810 P 34 G 1,5	Lapp 0026359	34 G 1,5	21.1	489.6	753
ÖLFLEX CLASSIC FD 810 P 42 G 1,5	Lapp 0026361	42 G 1,5	23.0	629.0	919
ÖLFLEX CLASSIC FD 810 P 50 G 1,5	Lapp 0026362	50 G 1,5	25.0	720.0	1093
ÖLFLEX CLASSIC FD 810 P 3 G 2,5	Lapp 0026370	3 G 2,5	9.0	72.0	135
ÖLFLEX CLASSIC FD 810 P 4 G 2,5	Lapp 0026371	4 G 2,5	10.0	96.0	168
ÖLFLEX CLASSIC FD 810 P 5 G 2,5	Lapp 0026372	5 G 2,5	11.2	120.0	206
ÖLFLEX CLASSIC FD 810 P 7 G 2,5	Lapp 0026373	7 G 2,5	13.6	168.0	286
ÖLFLEX CLASSIC FD 810 P 12 G 2,5	Lapp 0026374	12 G 2,5	16.0	288.0	453
ÖLFLEX CLASSIC FD 810 P 14 G 2,5	Lapp 0026375	14 G 2,5	17.2	336.0	525
ÖLFLEX CLASSIC FD 810 P 4 G 4	Lapp 0026381	4 G 4	11.7	160.0	252
ÖLFLEX CLASSIC FD 810 P 5 G 4	Lapp 0026382	5 G 4	13.1	200.0	309
ÖLFLEX CLASSIC FD 810 P 1 G 6	Lapp 0029200	1 G 6	6.4	60.0	84
ÖLFLEX CLASSIC FD 810 P 4 G 6	Lapp 0026383	4 G 6	13.9	230.0	377
ÖLFLEX CLASSIC FD 810 P 1 G 10	Lapp 0029210	1 G 10	7.7	100.0	141

ÖLFLEX CLASSIC FD 810 P 41 G 1,0_

Lapp 0026342



Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX CLASSIC FD 810 P 4 G 10	Lapp 0026385	4 G 10	17.6	384.0	614
ÖLFLEX CLASSIC FD 810 P 5 G 10	Lapp 0026386	5 G 10	19.6	480.0	751
ÖLFLEX CLASSIC FD 810 P 1 G 16	Lapp 0029220	1 G 16	9.2	160.0	198
ÖLFLEX CLASSIC FD 810 P 4 G 16	Lapp 0026387	4 G 16	21.0	615.0	851