



**Description:** ÖLFLEX CRANE 2S 12 G 1,5\_

**Lapp code:** Lapp 0027504

The **Test voltage** of the cable Lapp 0027504 is 3000 V.

## Application range

- For connecting movable control panels and consoles
- As a self-supporting shaft cable; in high rack systems
- Suitable for outdoor applications
- Do not use for lift applications!
- The application profiles for ÖLFLEX® CRANE and ÖLFLEX(R) LIFT cables can be found in the appendix, selection table A3

## Product Make-up

- Strands of bare copper wires
- Special PVC-based core insulation
- Special textile wrapping to improve sliding movement between the sheath and cores
- Special PVC-based outer sheath
- Opposing, integrated steel supporting elements

In our Cable list on next page you can find all interesting information acc. article Lapp 0027504 and much more.

CABLE LIST - all informations you need you can find here

| Product Name             | Lapp Nr.     | Number of cores and mm <sup>2</sup> per conductor | Cable Ø (mm) | Distance between strain wires (mm) | Copper index (kg/km) | Weight (kg/km) |
|--------------------------|--------------|---|--------------|------------------------------------|----------------------|----------------|
| ÖLFLEX® CRANE 2S         |              |   |              |                                    |                      |                |
| ÖLFLEX CRANE 2S 8 G 1,5  | Lapp 0027503 | 8 G 1,5   | 14.7         | 20                                 | 115.0                | 372.5          |
| ÖLFLEX CRANE 2S 12 G 1,5 | Lapp 0027504 | 12 G 1,5  | 16.2         | 21                                 | 172.8                | 439            |
| ÖLFLEX CRANE 2S 20 G 1,5 | Lapp 0027505 | 20 G 1,5  | 20.1         | 25                                 | 288.0                | 674            |