



Description: ÖLFLEX CRANE CF 8 G 1,5_

Lapp code: Lapp 0041076

The **Test voltage** of the cable Lapp 0041076 is 2000 V.

Application range

- In crane systems on building sites and shipyards for fixed installation, or for flexible use in cable trolley systems
- Sewage treatment plants, steelworks and high rack facilities
- The application profiles for ÖLFLEX® CRANE and ÖLFLEX(R) LIFT cables can be found in the appendix, selection table A3

Product Make-up

- Strands of bare or tinned-copper wires
- Core insulation: rubber compound
- Individual core screening consist of
 - plastic foil wrapping
 - tin-plated copper braiding
 - plastic foil wrapping
- Outer sheath: special rubber compound

In our Cable list on next page you can find all interesting information acc. article Lapp 0041076 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer dimensions/ width x height (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CRANE CF					
ÖLFLEX CRANE CF 4 G 1,5	Lapp 0041075	4 G 1,5	18,5 x 6,5	79.0	220
ÖLFLEX CRANE CF 8 G 1,5	Lapp 0041076	8 G 1,5	36 x 7,5	155.0	470
ÖLFLEX CRANE CF 12 G 1,5	Lapp 0041077	12 G 1,5	54,5 x 8,5	238.0	745
ÖLFLEX CRANE CF 4 G 2,5	Lapp 0041078	4 G 2,5	22,5 x 7,5	141.0	320
ÖLFLEX CRANE CF 12 G 2,5	Lapp 0041079	12 G 2,5	69,5 x 9,5	499.0	1180
ÖLFLEX CRANE CF 4 G 4	Lapp 0041080	4 G 4	29 x 10,5	219.0	505
ÖLFLEX CRANE CF 4 G 6	Lapp 0041081	4 G 6	31 x 10,5	302.0	605
ÖLFLEX CRANE CF 4 G 10	Lapp 0041082	4 G 10	36 x 11,5	472.0	840
ÖLFLEX CRANE CF 4 G 16	Lapp 0041083	4 G 16	41,5 x 13,5	687.0	1180
ÖLFLEX CRANE CF 4 G 25	Lapp 0041084	4 G 25	47 x 15	1114.0	1605
ÖLFLEX CRANE CF 4 G 35	Lapp 0041085	4 G 35	55 x 17	1482.0	2520
ÖLFLEX CRANE CF 4 G 50	Lapp 0041086	4 G 50	66 x 20,5	2238.0	3000