



Description: ÖLFLEX CRANE F 7 G 6_

Lapp code: Lapp 0041056

The **Test voltage** of the cable Lapp 0041056 is 3000 V.

Application range

- In crane systems on building sites and shipyards for fixed installation, or for flexible use in cable trolley systems
- Sewage treatment plants, steelworks and high rack facilities
- The application profiles for ÖLFLEX® CRANE and ÖLFLEX(R) LIFT cables can be found in the appendix, selection table A3

Product Make-up

- Strands of bare or tinned-copper wires
- Core insulation: rubber compound
- Outer sheath: special rubber compound

In our Cable list on next page you can find all interesting information acc. article Lapp 0041056 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer dimensions/ width x height (mm) | Copper index (kg/km) | Weight (kg/km) |
|-------------------------|--------------|---|---------------------------------------|----------------------|----------------|
| ÖLFLEX® CRANE F | | | | | |
| ÖLFLEX CRANE F 4 G 1,5 | Lapp 0041041 | 4 G 1,5 | 17,5 x 6,2 | 57.6 | 200 |
| ÖLFLEX CRANE F 5 G 1,5 | Lapp 0041042 | 5 G 1,5 | 21,5 x 6,2 | 72.0 | 240 |
| ÖLFLEX CRANE F 7 G 1,5 | Lapp 0041043 | 7 G 1,5 | 29 x 6,2 | 100.8 | 360 |
| ÖLFLEX CRANE F 8 G 1,5 | Lapp 0041044 | 8 G 1,5 | 31,5 x 6,2 | 115.0 | 370 |
| ÖLFLEX CRANE F 10 G 1,5 | Lapp 0041045 | 10 G 1,5 | 40 x 6,5 | 144.0 | 520 |
| ÖLFLEX CRANE F 12 G 1,5 | Lapp 0041046 | 12 G 1,5 | 47 x 6,5 | 172.8 | 620 |
| ÖLFLEX CRANE F 4 G 2,5 | Lapp 0041047 | 4 G 2,5 | 21 x 7,5 | 96.0 | 280 |
| ÖLFLEX CRANE F 5 G 2,5 | Lapp 0041048 | 5 G 2,5 | 27 x 7,5 | 120.0 | 400 |
| ÖLFLEX CRANE F 7 G 2,5 | Lapp 0041049 | 7 G 2,5 | 35 x 7,5 | 168.0 | 520 |
| ÖLFLEX CRANE F 8 G 2,5 | Lapp 0041050 | 8 G 2,5 | 39 x 7,5 | 192.0 | 550 |
| ÖLFLEX CRANE F 12 G 2,5 | Lapp 0041051 | 12 G 2,5 | 56 x 8 | 288.0 | 800 |
| ÖLFLEX CRANE F 4 G 4 | Lapp 0041052 | 4 G 4 | 26 x 9 | 153.6 | 410 |
| ÖLFLEX CRANE F 7 G 4 | Lapp 0041053 | 7 G 4 | 42 x 9 | 268.8 | 700 |
| ÖLFLEX CRANE F 4 G 6 | Lapp 0041054 | 4 G 6 | 29 x 9,5 | 230.0 | 600 |
| ÖLFLEX CRANE F 5 G 6 | Lapp 0041055 | 5 G 6 | 35 x 9,5 | 288.0 | 650 |
| ÖLFLEX CRANE F 7 G 6 | Lapp 0041056 | 7 G 6 | 42 x 9,5 | 403.0 | 850 |
| ÖLFLEX CRANE F 4 G 10 | Lapp 0041057 | 4 G 10 | 33 x 11 | 384.0 | 800 |
| ÖLFLEX CRANE F 5 G 10 | Lapp 0041058 | 5 G 10 | 44 x 11 | 480.0 | 1000 |
| ÖLFLEX CRANE F 4 G 16 | Lapp 0041059 | 4 G 16 | 38 x 13 | 614.0 | 1150 |
| ÖLFLEX CRANE F 4 G 25 | Lapp 0041060 | 4 G 25 | 49,5 x 15 | 960.0 | 1700 |
| ÖLFLEX CRANE F 4 G 35 | Lapp 0041061 | 4 G 35 | 55 x 17 | 1344.0 | 2360 |
| ÖLFLEX CRANE F 4 G 50 | Lapp 0041062 | 4 G 50 | 63 x 19 | 1920.0 | 3000 |
| ÖLFLEX CRANE F 4 G 70 | Lapp 0041063 | 4 G 70 | 71 x 22 | 2688.0 | 4000 |