



Description: ÖLFLEX CRANE F 8 G 2,5_

Lapp code: Lapp 0041050

The **Test voltage** of the cable Lapp 0041050 is 3000 V.

Application range

- In crane systems on building sites and shipyards for fixed installation, or for flexible use in cable trolley systems
- Sewage treatment plants, steelworks and high rack facilities
- The application profiles for ÖLFLEX® CRANE and ÖLFLEX(R) LIFT cables can be found in the appendix, selection table A3

Product Make-up

- Strands of bare or tinned-copper wires
- Core insulation: rubber compound
- Outer sheath: special rubber compound

In our Cable list on next page you can find all interesting information acc. article Lapp 0041050 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer dimensions/ width x height (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CRANE F					
ÖLFLEX CRANE F 4 G 1,5	Lapp 0041041	4 G 1,5	17,5 x 6,2	57.6	200
ÖLFLEX CRANE F 5 G 1,5	Lapp 0041042	5 G 1,5	21,5 x 6,2	72.0	240
ÖLFLEX CRANE F 7 G 1,5	Lapp 0041043	7 G 1,5	29 x 6,2	100.8	360
ÖLFLEX CRANE F 8 G 1,5	Lapp 0041044	8 G 1,5	31,5 x 6,2	115.0	370
ÖLFLEX CRANE F 10 G 1,5	Lapp 0041045	10 G 1,5	40 x 6,5	144.0	520
ÖLFLEX CRANE F 12 G 1,5	Lapp 0041046	12 G 1,5	47 x 6,5	172.8	620
ÖLFLEX CRANE F 4 G 2,5	Lapp 0041047	4 G 2,5	21 x 7,5	96.0	280
ÖLFLEX CRANE F 5 G 2,5	Lapp 0041048	5 G 2,5	27 x 7,5	120.0	400
ÖLFLEX CRANE F 7 G 2,5	Lapp 0041049	7 G 2,5	35 x 7,5	168.0	520
ÖLFLEX CRANE F 8 G 2,5	Lapp 0041050	8 G 2,5	39 x 7,5	192.0	550
ÖLFLEX CRANE F 12 G 2,5	Lapp 0041051	12 G 2,5	56 x 8	288.0	800
ÖLFLEX CRANE F 4 G 4	Lapp 0041052	4 G 4	26 x 9	153.6	410
ÖLFLEX CRANE F 7 G 4	Lapp 0041053	7 G 4	42 x 9	268.8	700
ÖLFLEX CRANE F 4 G 6	Lapp 0041054	4 G 6	29 x 9,5	230.0	600
ÖLFLEX CRANE F 5 G 6	Lapp 0041055	5 G 6	35 x 9,5	288.0	650
ÖLFLEX CRANE F 7 G 6	Lapp 0041056	7 G 6	42 x 9,5	403.0	850
ÖLFLEX CRANE F 4 G 10	Lapp 0041057	4 G 10	33 x 11	384.0	800
ÖLFLEX CRANE F 5 G 10	Lapp 0041058	5 G 10	44 x 11	480.0	1000
ÖLFLEX CRANE F 4 G 16	Lapp 0041059	4 G 16	38 x 13	614.0	1150
ÖLFLEX CRANE F 4 G 25	Lapp 0041060	4 G 25	49,5 x 15	960.0	1700
ÖLFLEX CRANE F 4 G 35	Lapp 0041061	4 G 35	55 x 17	1344.0	2360
ÖLFLEX CRANE F 4 G 50	Lapp 0041062	4 G 50	63 x 19	1920.0	3000
ÖLFLEX CRANE F 4 G 70	Lapp 0041063	4 G 70	71 x 22	2688.0	4000