



Description: ÖLFLEX CRANE NSHTÖU 18 G 1,5_

Lapp code: Lapp 0043010

The **Test voltage** of the cable Lapp 0043010 is 3000 V.

Application range

- For use in hoists, transport and conveyor systems
- Reeling/unreeling during operation without fixing
- In dry or damp interiors, outdoors, or not more than 2 weeks without interruption in industrial water
- The application profiles for ÖLFLEX® CRANE and ÖLFLEX(R) LIFT cables can be found in the appendix, selection table A3
- The assembly and handling guidelines for ÖLFLEX® CRANE cables can be found in the catalogue appendix, technical table T4; for ÖLFLEX(R) LIFT cables please see the catalogue appendix, technical table T5

Product Make-up

- Strands of tinned-copper wires
- Core insulation: rubber compound type 3GI3
- Support braid integrated in the outer sheath
- Outer sheath: rubber compound, type 5GM3

In our Cable list on next page you can find all interesting information acc. article Lapp 0043010 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|------------------------------|---------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® CRANE NSHTÖU | | | | | |
| ÖLFLEX CRANE NSHTÖU 3 G 1,5 | Lapp 0043006 | 3 G 1,5 | 12.2 | 43.2 | 190 |
| ÖLFLEX CRANE NSHTÖU 4 G 1,5 | Lapp 00430053 | 4 G 1,5 | 14.8 | 57.6 | 220 |
| ÖLFLEX CRANE NSHTÖU 5 G 1,5 | Lapp 00430073 | 5 G 1,5 | 15.7 | 72.0 | 260 |
| ÖLFLEX CRANE NSHTÖU 7 G 1,5 | Lapp 0043008 | 7 G 1,5 | 18.2 | 100.8 | 380 |
| ÖLFLEX CRANE NSHTÖU 12 G 1,5 | Lapp 0043009 | 12 G 1,5 | 23.9 | 172.8 | 720 |
| ÖLFLEX CRANE NSHTÖU 18 G 1,5 | Lapp 0043010 | 18 G 1,5 | 23.9 | 259.2 | 770 |
| ÖLFLEX CRANE NSHTÖU 24 G 1,5 | Lapp 0043011 | 24 G 1,5 | 27.1 | 345.6 | 1000 |
| ÖLFLEX CRANE NSHTÖU 30 G 1,5 | Lapp 0043012 | 30 G 1,5 | 30.2 | 432.0 | 1320 |
| ÖLFLEX CRANE NSHTÖU 3 G 2,5 | Lapp 0043013 | 3 G 2,5 | 13.5 | 72.0 | 250 |
| ÖLFLEX CRANE NSHTÖU 4 G 2,5 | Lapp 00430303 | 4 G 2,5 | 16.9 | 96.0 | 330 |
| ÖLFLEX CRANE NSHTÖU 5 G 2,5 | Lapp 00430143 | 5 G 2,5 | 18.0 | 120.0 | 390 |
| ÖLFLEX CRANE NSHTÖU 7 G 2,5 | Lapp 0043015 | 7 G 2,5 | 20.6 | 168.0 | 510 |
| ÖLFLEX CRANE NSHTÖU 12 G 2,5 | Lapp 0043016 | 12 G 2,5 | 27.4 | 288.0 | 970 |
| ÖLFLEX CRANE NSHTÖU 18 G 2,5 | Lapp 0043017 | 18 G 2,5 | 27.4 | 432.0 | 1100 |
| ÖLFLEX CRANE NSHTÖU 24 G 2,5 | Lapp 0043018 | 24 G 2,5 | 31.6 | 576.0 | 1450 |
| ÖLFLEX CRANE NSHTÖU 30 G 2,5 | Lapp 0043019 | 30 G 2,5 | 36.3 | 720.0 | 1950 |
| ÖLFLEX CRANE NSHTÖU 4 G 4 | Lapp 00430203 | 4 G 4 | 18.4 | 153.6 | 440 |
| ÖLFLEX CRANE NSHTÖU 5 G 4 | Lapp 00430333 | 5 G 4 | 19.6 | 192.0 | 520 |
| ÖLFLEX CRANE NSHTÖU 4 G 6 | Lapp 00430213 | 4 G 6 | 19.8 | 230.4 | 530 |
| ÖLFLEX CRANE NSHTÖU 5 G 6 | Lapp 00430343 | 5 G 6 | 21.7 | 288.0 | 690 |
| ÖLFLEX CRANE NSHTÖU 4 G 10 | Lapp 00430223 | 4 G 10 | 23.4 | 384.0 | 830 |
| ÖLFLEX CRANE NSHTÖU 5 G 10 | Lapp 00430003 | 5 G 10 | 25.2 | 480.0 | 1000 |
| ÖLFLEX CRANE NSHTÖU 4 G 16 | Lapp 00430233 | 4 G 16 | 25.5 | 614.4 | 1170 |
| ÖLFLEX CRANE NSHTÖU 5 G 16 | Lapp 00430323 | 5 G 16 | 27.5 | 768.0 | 1400 |

ÖLFLEX CRANE NSHTÖU 18 G 1,5_

Lapp 0043010



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|----------------------------|---------------|---|---------------------|----------------------|----------------|
| ÖLFLEX CRANE NSHTÖU 4 G 25 | Lapp 00430243 | 4 G 25 | 32.6 | 960.0 | 1830 |
| ÖLFLEX CRANE NSHTÖU 4 G 35 | Lapp 00430253 | 4 G 35 | 34.8 | 1344.0 | 2280 |
| ÖLFLEX CRANE NSHTÖU 4 G 50 | Lapp 00430263 | 4 G 50 | 40.6 | 1920.0 | 3220 |
| ÖLFLEX CRANE NSHTÖU 4 G 70 | Lapp 00430283 | 4 G 70 | 44.8 | 2688.0 | 4200 |
| ÖLFLEX CRANE NSHTÖU 4 G 95 | Lapp 00430293 | 4 G 95 | 51.2 | 3648.0 | 5530 |