



Description: ÖLFLEX CRANE NSHTÖU 5 G 2,5_

Lapp code: Lapp 00430143

The **Test voltage** of the cable Lapp 00430143 is 3000 V.

Application range

- For use in hoists, transport and conveyor systems
- Reeling/unreeling during operation without fixing
- In dry or damp interiors, outdoors, or not more than 2 weeks without interruption in industrial water
- The application profiles for ÖLFLEX® CRANE and ÖLFLEX(R) LIFT cables can be found in the appendix, selection table A3
- The assembly and handling guidelines for ÖLFLEX® CRANE cables can be found in the catalogue appendix, technical table T4; for ÖLFLEX(R) LIFT cables please see the catalogue appendix, technical table T5

Product Make-up

- Strands of tinned-copper wires
- Core insulation: rubber compound type 3GI3
- Support braid integrated in the outer sheath
- Outer sheath: rubber compound, type 5GM3

In our Cable list on next page you can find all interesting information acc. article Lapp 00430143 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CRANE NSHTÖU					
ÖLFLEX CRANE NSHTÖU 3 G 1,5	Lapp 0043006	3 G 1,5	12.2	43.2	190
ÖLFLEX CRANE NSHTÖU 4 G 1,5	Lapp 00430053	4 G 1,5	14.8	57.6	220
ÖLFLEX CRANE NSHTÖU 5 G 1,5	Lapp 00430073	5 G 1,5	15.7	72.0	260
ÖLFLEX CRANE NSHTÖU 7 G 1,5	Lapp 0043008	7 G 1,5	18.2	100.8	380
ÖLFLEX CRANE NSHTÖU 12 G 1,5	Lapp 0043009	12 G 1,5	23.9	172.8	720
ÖLFLEX CRANE NSHTÖU 18 G 1,5	Lapp 0043010	18 G 1,5	23.9	259.2	770
ÖLFLEX CRANE NSHTÖU 24 G 1,5	Lapp 0043011	24 G 1,5	27.1	345.6	1000
ÖLFLEX CRANE NSHTÖU 30 G 1,5	Lapp 0043012	30 G 1,5	30.2	432.0	1320
ÖLFLEX CRANE NSHTÖU 3 G 2,5	Lapp 0043013	3 G 2,5	13.5	72.0	250
ÖLFLEX CRANE NSHTÖU 4 G 2,5	Lapp 00430303	4 G 2,5	16.9	96.0	330
ÖLFLEX CRANE NSHTÖU 5 G 2,5	Lapp 00430143	5 G 2,5	18.0	120.0	390
ÖLFLEX CRANE NSHTÖU 7 G 2,5	Lapp 0043015	7 G 2,5	20.6	168.0	510
ÖLFLEX CRANE NSHTÖU 12 G 2,5	Lapp 0043016	12 G 2,5	27.4	288.0	970
ÖLFLEX CRANE NSHTÖU 18 G 2,5	Lapp 0043017	18 G 2,5	27.4	432.0	1100
ÖLFLEX CRANE NSHTÖU 24 G 2,5	Lapp 0043018	24 G 2,5	31.6	576.0	1450
ÖLFLEX CRANE NSHTÖU 30 G 2,5	Lapp 0043019	30 G 2,5	36.3	720.0	1950
ÖLFLEX CRANE NSHTÖU 4 G 4	Lapp 00430203	4 G 4	18.4	153.6	440
ÖLFLEX CRANE NSHTÖU 5 G 4	Lapp 00430333	5 G 4	19.6	192.0	520
ÖLFLEX CRANE NSHTÖU 4 G 6	Lapp 00430213	4 G 6	19.8	230.4	530
ÖLFLEX CRANE NSHTÖU 5 G 6	Lapp 00430343	5 G 6	21.7	288.0	690
ÖLFLEX CRANE NSHTÖU 4 G 10	Lapp 00430223	4 G 10	23.4	384.0	830
ÖLFLEX CRANE NSHTÖU 5 G 10	Lapp 00430003	5 G 10	25.2	480.0	1000
ÖLFLEX CRANE NSHTÖU 4 G 16	Lapp 00430233	4 G 16	25.5	614.4	1170
ÖLFLEX CRANE NSHTÖU 5 G 16	Lapp 00430323	5 G 16	27.5	768.0	1400

ÖLFLEX CRANE NSHTÖU 5 G 2,5_

Lapp 00430143



Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX CRANE NSHTÖU 4 G 25	Lapp 00430243	4 G 25	32.6	960.0	1830
ÖLFLEX CRANE NSHTÖU 4 G 35	Lapp 00430253	4 G 35	34.8	1344.0	2280
ÖLFLEX CRANE NSHTÖU 4 G 50	Lapp 00430263	4 G 50	40.6	1920.0	3220
ÖLFLEX CRANE NSHTÖU 4 G 70	Lapp 00430283	4 G 70	44.8	2688.0	4200
ÖLFLEX CRANE NSHTÖU 4 G 95	Lapp 00430293	4 G 95	51.2	3648.0	5530