



Description: ÖLFLEX FD 891 5 G 1,0_

Lapp code: Lapp 1026130

The **Test voltage** of the cable Lapp 1026130 is 4000 V.

Application range

- In power chains or moving machine parts
- Suitable for use in measuring, control and regulating circuits
- Assembly lines, production lines, in all kinds of machines
- Machine tools
- Plant engineering

Product Make-up

- Extra-fine wire strand made of bare copper wires (class 6)
- Core insulation: PVC
- Cores twisted in layers in short lay lengths
- Non-woven wrapping
- PVC outer sheath, black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 1026130 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® FD 891					
ÖLFLEX FD 891 12 G 0,5	Lapp 1026012	12 G 0,5	10.8	57.6	162
ÖLFLEX FD 891 3 G 0,75	Lapp 1026103	3 G 0,75	6.6	21.6	63
ÖLFLEX FD 891 4 G 0,75	Lapp 1026104	4 G 0,75	7.3	28.8	75
ÖLFLEX FD 891 5 G 0,75	Lapp 1026105	5 G 0,75	8.0	36.0	90
ÖLFLEX FD 891 7 G 0,75	Lapp 1026107	7 G 0,75	9.6	50.4	132
ÖLFLEX FD 891 12 G 0,75	Lapp 1026112	12 G 0,75	11.6	86.5	201
ÖLFLEX FD 891 18 G 0,75	Lapp 1026118	18 G 0,75	13.9	129.6	300
ÖLFLEX FD 891 25 G 0,75	Lapp 1026125	25 G 0,75	16.6	180.0	415
ÖLFLEX FD 891 3 G 1,0	Lapp 1026127	3 G 1,0	7.1	28.8	65
ÖLFLEX FD 891 4 G 1,0	Lapp 1026129	4 G 1,0	7.8	39.0	82
ÖLFLEX FD 891 5 G 1,0	Lapp 1026130	5 G 1,0	8.8	48.0	105
ÖLFLEX FD 891 7 G 1,0	Lapp 1026128	7 G 1,0	10.5	67.2	149
ÖLFLEX FD 891 12 G 1,0	Lapp 1026131	12 G 1,0	12.5	116.0	225
ÖLFLEX FD 891 18 G 1,0	Lapp 1026132	18 G 1,0	15.0	173.0	331
ÖLFLEX FD 891 25 G 1,0	Lapp 1026133	25 G 1,0	17.9	240.0	484
ÖLFLEX FD 891 3 G 1,5	Lapp 1026303	3 G 1,5	7.7	43.2	93
ÖLFLEX FD 891 4 G 1,5	Lapp 1026304	4 G 1,5	8.8	57.6	122
ÖLFLEX FD 891 5 G 1,5	Lapp 1026305	5 G 1,5	9.6	72.0	147
ÖLFLEX FD 891 7 G 1,5	Lapp 1026307	7 G 1,5	11.6	100.8	219
ÖLFLEX FD 891 12 G 1,5	Lapp 1026312	12 G 1,5	13.9	172.8	322
ÖLFLEX FD 891 18 G 1,5	Lapp 1026318	18 G 1,5	16.9	259.2	478
ÖLFLEX FD 891 25 G 1,5	Lapp 1026325	25 G 1,5	20.1	360.0	670
ÖLFLEX FD 891 34 G 1,5	Lapp 1026334	34 G 1,5	23.6	489.6	897
ÖLFLEX FD 891 3 G 2,5	Lapp 1026403	3 G 2,5	8.8	72.0	129
ÖLFLEX FD 891 4 G 2,5	Lapp 1026404	4 G 2,5	9.8	96.0	167
ÖLFLEX FD 891 5 G 2,5	Lapp 1026405	5 G 2,5	11.0	120.0	212
ÖLFLEX FD 891 7 G 2,5	Lapp 1026407	7 G 2,5	13.4	168.0	304
ÖLFLEX FD 891 12 G 2,5	Lapp 1026412	12 G 2,5	15.8	288.0	452
ÖLFLEX FD 891 4 G 4	Lapp 1026504	4 G 4	11.8	153.6	263

ÖLFLEX FD 891 5 G 1,0_

Lapp 1026130



Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX FD 891 5 G 4	Lapp 1026505	5 G 4	13.2	192.0	325
ÖLFLEX FD 891 7 G 4	Lapp 1026507	7 G 4	16.1	268.8	469
ÖLFLEX FD 891 4 G 6	Lapp 1026604	4 G 6	13.7	230.4	368
ÖLFLEX FD 891 4 G 10	Lapp 1026614	4 G 10	17.9	384.0	588
ÖLFLEX FD 891 4 G 16	Lapp 1026624	4 G 16	24.1	614.4	1031
ÖLFLEX FD 891 4 G 25	Lapp 1026634	4 G 25	27.9	960.0	1530
ÖLFLEX FD 891 4 G 35	Lapp 1026644	4 G 35	31.1	1344.0	1959