



Description: ÖLFLEX FD 891 P 3 G 2,5_

Lapp code: Lapp 1028403

The **Test voltage** of the cable Lapp 1028403 is 4000 V.

Application range

- In power chains or moving machine parts
- Plant engineering
- Machine tools

Product Make-up

- Extra-fine wire strand made of bare copper wires (class 6)
- Core insulation: PVC
- Cores twisted in layers in short lay lengths
- Non-woven wrapping
- PUR outer sheath, black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 1028403 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® FD 891 P					
ÖLFLEX FD 891 P 2 X 0,5	Lapp 1028752	2 X 0,5	6.5	9.6	46
ÖLFLEX FD 891 P 7 G 0,5	Lapp 1028007	7 G 0,5	9.6	33.6	118
ÖLFLEX FD 891 P 3 G 0,75	Lapp 1028103	3 G 0,75	7.3	21.6	66
ÖLFLEX FD 891 P 4 G 0,75	Lapp 1028104	4 G 0,75	8.0	28.8	82
ÖLFLEX FD 891 P 5 G 0,75	Lapp 1028105	5 G 0,75	8.7	36.0	101
ÖLFLEX FD 891 P 7 G 0,75	Lapp 1028107	7 G 0,75	10.7	50.4	142
ÖLFLEX FD 891 P 12 G 0,75	Lapp 1028112	12 G 0,75	11.7	86.4	196
ÖLFLEX FD 891 P 18 G 0,75	Lapp 1028118	18 G 0,75	13.9	129.6	282
ÖLFLEX FD 891 P 25 G 0,75	Lapp 1028125	25 G 0,75	16.6	180.0	404
ÖLFLEX FD 891 P 34 G 0,75	Lapp 1028134	34 G 0,75	18.9	244.8	541
ÖLFLEX FD 891 P 50 G 0,75	Lapp 1028150	50 G 0,75	22.5	360.0	738
ÖLFLEX FD 891 P 3 G 1,5	Lapp 1028303	3 G 1,5	8.4	43.2	98
ÖLFLEX FD 891 P 4 G 1,5	Lapp 1028304	4 G 1,5	9.3	57.6	125
ÖLFLEX FD 891 P 5 G 1,5	Lapp 1028305	5 G 1,5	10.1	72.0	155
ÖLFLEX FD 891 P 7 G 1,5	Lapp 1028307	7 G 1,5	11.9	100.8	221
ÖLFLEX FD 891 P 12 G 1,5	Lapp 1028312	12 G 1,5	13.9	172.8	318
ÖLFLEX FD 891 P 18 G 1,5	Lapp 1028318	18 G 1,5	16.9	259.2	484
ÖLFLEX FD 891 P 25 G 1,5	Lapp 1028325	25 G 1,5	20.1	360.0	671
ÖLFLEX FD 891 P 34 G 1,5	Lapp 1028334	34 G 1,5	23.1	489.6	910
ÖLFLEX FD 891 P 2 X 2,5	Lapp 1028952	2 X 2,5	8.9	48.0	102
ÖLFLEX FD 891 P 3 G 2,5	Lapp 1028403	3 G 2,5	9.3	72.0	134
ÖLFLEX FD 891 P 4 G 2,5	Lapp 1028404	4 G 2,5	10.3	96.0	173
ÖLFLEX FD 891 P 5 G 2,5	Lapp 1028405	5 G 2,5	11.3	120.0	217
ÖLFLEX FD 891 P 7 G 2,5	Lapp 1028407	7 G 2,5	13.4	168.0	312

ÖLFLEX FD 891 P 3 G 2,5_

Lapp 1028403



Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX FD 891 P 12 G 2,5	Lapp 1028412	12 G 2,5	15.8	288.0	460
ÖLFLEX FD 891 P 3 G 4	Lapp 1028503	3 G 4	10.9	115.2	197
ÖLFLEX FD 891 P 4 G 4	Lapp 1028504	4 G 4	12.1	153.6	257
ÖLFLEX FD 891 P 7 G 4	Lapp 1028507	7 G 4	16.1	268.8	471
ÖLFLEX FD 891 P 4 G 6	Lapp 1028604	4 G 6	13.7	230.4	363
ÖLFLEX FD 891 P 4 G 10	Lapp 1028614	4 G 10	17.9	384.0	605
ÖLFLEX FD 891 P 4 G 16	Lapp 1028624	4 G 16	23.4	614.4	973
ÖLFLEX FD 891 P 4 G 25	Lapp 1028634	4 G 25	27.6	960.0	1437