



Description: ÖLFLEX FD 90 150_

Lapp code: Lapp 0026625

The **Test voltage** of the cable Lapp 0026625 is 4000 V.

Application range

- In power chains or moving machine parts
- For internal wiring of electric and electronic equipment in switch cabinets
- This cable can substitute multi-core shielded servo drive cables where space requirements or minimum bending radii cause problems
- Specially designed for power circuits of servomotors driven by frequency converters
- Test systems in the automotive industry, vehicles and stationary fuel cell systems

Product Make-up

- Extra-fine wire strand made of bare copper wires (class 6)
- Non-woven wrapping
- Core insulation: PVC
- PVC outer sheath, black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 0026625 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Conductor cross-section (mm²)	Outer diameter (mm)	Core colour	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® FD 90						
ÖLFLEX FD 90 10	Lapp 0026600	10	9.0	green-yellow	96.0	176
ÖLFLEX FD 90 10	Lapp 0026601	10	9.0	black	96.0	176
ÖLFLEX FD 90 16	Lapp 0026603	16	10.5	green-yellow	153.6	240
ÖLFLEX FD 90 16	Lapp 0026604	16	10.5	black	153.6	240
ÖLFLEX FD 90 25	Lapp 0026607	25	11.8	green-yellow	240.0	361
ÖLFLEX FD 90 25	Lapp 0026608	25	11.8	black	240.0	361
ÖLFLEX FD 90 35	Lapp 0026610	35	14.2	green-yellow	336.0	482
ÖLFLEX FD 90 35	Lapp 0026611	35	14.2	black	336.0	482
ÖLFLEX FD 90 50	Lapp 0026613	50	16.2	green-yellow	480.0	660
ÖLFLEX FD 90 50	Lapp 0026614	50	16.2	black	480.0	660
ÖLFLEX FD 90 70	Lapp 0026616	70	18.3	green-yellow	672.0	898
ÖLFLEX FD 90 70	Lapp 0026617	70	18.3	black	672.0	898
ÖLFLEX FD 90 95	Lapp 0026619	95	19.8	green-yellow	912.0	1179
ÖLFLEX FD 90 95	Lapp 0026620	95	19.8	black	912.0	1179
ÖLFLEX FD 90 120	Lapp 0026622	120	23.4	green-yellow	1152.0	1521
ÖLFLEX FD 90 120	Lapp 0026623	120	23.4	black	1152.0	1521
ÖLFLEX FD 90 150	Lapp 0026625	150	25.1	green-yellow	1440.0	1739
ÖLFLEX FD 90 150	Lapp 0026626	150	25.1	black	1440.0	1739
ÖLFLEX FD 90 185	Lapp 0026628	185	28.1	green-yellow	1776.0	2305
ÖLFLEX FD 90 185	Lapp 0026629	185	28.1	black	1776.0	2305
ÖLFLEX FD 90 240	Lapp 0026634	240	31.6	green-yellow	2304.0	2944
ÖLFLEX FD 90 240	Lapp 0026635	240	31.6	black	2304.0	2944
ÖLFLEX FD 90 300	Lapp 0026640	300	33.5	green-yellow	2880.0	3545
ÖLFLEX FD 90 300	Lapp 0026641	300	33.5	black	2880.0	3545