



Description: ÖLFLEX FD 90 95_
Lapp code: Lapp 0026619

The **Test voltage** of the cable Lapp 0026619 is 4000 V.

Application range

- In power chains or moving machine parts
- For internal wiring of electric and electronic equipment in switch cabinets
- This cable can substitute multi-core shielded servo drive cables where space requirements or minimum bending radii cause problems
- Specially designed for power circuits of servomotors driven by frequency converters
- Test systems in the automotive industry, vehicles and stationary fuel cell systems

Product Make-up

- Extra-fine wire strand made of bare copper wires (class 6)
- Non-woven wrapping
- Core insulation: PVC
- PVC outer sheath, black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 0026619 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Conductor cross-section (mm²) | Outer diameter (mm) | Core colour | Copper index (kg/km) | Weight (kg/km) |
|------------------|--------------|-------------------------------|---------------------|--------------|----------------------|----------------|
| ÖLFLEX® FD 90 | | | | | | |
| ÖLFLEX FD 90 10 | Lapp 0026600 | 10 | 9.0 | green-yellow | 96.0 | 176 |
| ÖLFLEX FD 90 10 | Lapp 0026601 | 10 | 9.0 | black | 96.0 | 176 |
| ÖLFLEX FD 90 16 | Lapp 0026603 | 16 | 10.5 | green-yellow | 153.6 | 240 |
| ÖLFLEX FD 90 16 | Lapp 0026604 | 16 | 10.5 | black | 153.6 | 240 |
| ÖLFLEX FD 90 25 | Lapp 0026607 | 25 | 11.8 | green-yellow | 240.0 | 361 |
| ÖLFLEX FD 90 25 | Lapp 0026608 | 25 | 11.8 | black | 240.0 | 361 |
| ÖLFLEX FD 90 35 | Lapp 0026610 | 35 | 14.2 | green-yellow | 336.0 | 482 |
| ÖLFLEX FD 90 35 | Lapp 0026611 | 35 | 14.2 | black | 336.0 | 482 |
| ÖLFLEX FD 90 50 | Lapp 0026613 | 50 | 16.2 | green-yellow | 480.0 | 660 |
| ÖLFLEX FD 90 50 | Lapp 0026614 | 50 | 16.2 | black | 480.0 | 660 |
| ÖLFLEX FD 90 70 | Lapp 0026616 | 70 | 18.3 | green-yellow | 672.0 | 898 |
| ÖLFLEX FD 90 70 | Lapp 0026617 | 70 | 18.3 | black | 672.0 | 898 |
| ÖLFLEX FD 90 95 | Lapp 0026619 | 95 | 19.8 | green-yellow | 912.0 | 1179 |
| ÖLFLEX FD 90 95 | Lapp 0026620 | 95 | 19.8 | black | 912.0 | 1179 |
| ÖLFLEX FD 90 120 | Lapp 0026622 | 120 | 23.4 | green-yellow | 1152.0 | 1521 |
| ÖLFLEX FD 90 120 | Lapp 0026623 | 120 | 23.4 | black | 1152.0 | 1521 |
| ÖLFLEX FD 90 150 | Lapp 0026625 | 150 | 25.1 | green-yellow | 1440.0 | 1739 |
| ÖLFLEX FD 90 150 | Lapp 0026626 | 150 | 25.1 | black | 1440.0 | 1739 |
| ÖLFLEX FD 90 185 | Lapp 0026628 | 185 | 28.1 | green-yellow | 1776.0 | 2305 |
| ÖLFLEX FD 90 185 | Lapp 0026629 | 185 | 28.1 | black | 1776.0 | 2305 |
| ÖLFLEX FD 90 240 | Lapp 0026634 | 240 | 31.6 | green-yellow | 2304.0 | 2944 |
| ÖLFLEX FD 90 240 | Lapp 0026635 | 240 | 31.6 | black | 2304.0 | 2944 |
| ÖLFLEX FD 90 300 | Lapp 0026640 | 300 | 33.5 | green-yellow | 2880.0 | 3545 |
| ÖLFLEX FD 90 300 | Lapp 0026641 | 300 | 33.5 | black | 2880.0 | 3545 |