



Description: ÖLFLEX HEAT 105 MC 2 X 1,5_

Lapp code: Lapp 0026011

The **Test voltage** of the cable Lapp 0026011 is 2500 V.

Application range

- For connection of motors, transformers, reels, plants, machines, appliances, switch cabinets and other installations with a higher operating or ambient temperature

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: PVC, high heat-resistance
- Cores twisted in layers
- Outer sheath: PVC, heat-resistant, black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 0026011 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® HEAT 105 MC					
ÖLFLEX HEAT 105 MC 2 X 0,75	Lapp 0026001	2 X 0,75	6,2	14.4	53
ÖLFLEX HEAT 105 MC 3 G 0,75	Lapp 0026002	3 G 0,75	6,5	21.6	62
ÖLFLEX HEAT 105 MC 4 G 0,75	Lapp 00260033	4 G 0,75	7,1	28.8	76
ÖLFLEX HEAT 105 MC 5 G 0,75	Lapp 00260043	5 G 0,75	8.0	36.0	95
ÖLFLEX HEAT 105 MC 7 G 0,75	Lapp 0026005	7 G 0,75	9,7	50.0	113
ÖLFLEX HEAT 105 MC 2 X 1	Lapp 0026006	2 X 1	6,5	19.2	61
ÖLFLEX HEAT 105 MC 3 G 1	Lapp 0026007	3 G 1	6,9	29.0	74
ÖLFLEX HEAT 105 MC 4 G 1	Lapp 00260083	4 G 1	7,7	38.4	89
ÖLFLEX HEAT 105 MC 5 G 1	Lapp 00260093	5 G 1	8,4	48.0	110
ÖLFLEX HEAT 105 MC 7 G 1	Lapp 0026010	7 G 1	10,2	67.0	130
ÖLFLEX HEAT 105 MC 2 X 1,5	Lapp 0026011	2 X 1,5	7,5	29.0	78
ÖLFLEX HEAT 105 MC 3 G 1,5	Lapp 0026012	3 G 1,5	8,1	43.2	98
ÖLFLEX HEAT 105 MC 4 G 1,5	Lapp 00260133	4 G 1,5	8,9	57.6	122
ÖLFLEX HEAT 105 MC 5 G 1,5	Lapp 00260143	5 G 1,5	10.0	72.0	144
ÖLFLEX HEAT 105 MC 7 G 1,5	Lapp 0026015	7 G 1,5	12,3	101.0	180