



Description: ÖLFLEX HEAT 1565 MC 4 x 1,5_

Lapp code: Lapp 30016600

The **Test voltage** of the cable Lapp 30016600 is 2200 V.

Application range

- Guarantees the circuit even in areas with extremely high ambient temperatures
- Blast furnaces and coking plants
- Refineries
- Glassworks
- Aluminium and steelworks

Product Make-up

- Fine-wire strand made of nickel-plated copper
- MICA tape wrapping and impregnated glass fibre braiding
- Cores twisted together
- Outer sheath: MICA tape-wrapping, impregnated glass fibre braiding, red

In our Cable list on next page you can find all interesting information acc. article Lapp 30016600 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® HEAT 1565 MC					
ÖLFLEX HEAT 1565 MC 2 x 0,5	Lapp 30020808	2 x 0,5	7,0	9,6	48
ÖLFLEX HEAT 1565 MC 2 x 0,75	Lapp 30020809	2 x 0,75	7,4	14,4	66
ÖLFLEX HEAT 1565 MC 2 x 1	Lapp 30016609	2 x 1	7,7	19,2	74
ÖLFLEX HEAT 1565 MC 2 x 1,5	Lapp 30016603	2 x 1,5	8,2	28,8	87
ÖLFLEX HEAT 1565 MC 2 x 2,5	Lapp 30020810	2 x 2,5	9,7	48,0	114
ÖLFLEX HEAT 1565 MC 2 x 4	Lapp 30020811	2 x 4	11,2	76,8	161
ÖLFLEX HEAT 1565 MC 4 x 1	Lapp 30016606	4 x 1	8,9	38,4	123
ÖLFLEX HEAT 1565 MC 4 x 1,5	Lapp 30016600	4 x 1,5	9,5	57,6	148