Description: **ÖLFLEX HEAT 1565 SC 1,5_**
Lapp code: Lapp 3013234

The **Test voltage** of the cable Lapp 3013234 is 2200 V.

Application range

- Guarantees the circuit even in areas with extremely high ambient temperatures
- Blast furnaces and coking plants
- Refineries
- Glassworks
- Aluminium and steelworks

Product Make-up

- Fine-wire strand made of nickel-plated copper
- Mica tape wrapping
- Impregnated glass fibre braiding,
  core colour: red

In our Cable list on next page you can find all interesting information acc. article Lapp 3013234 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Conductor cross-section (mm²)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® HEAT SC 1565					
ÖLFLEX HEAT 1565 SC 0,75	Lapp 3020780	0,75	2,9	7.2	15.9
ÖLFLEX HEAT 1565 SC 1	Lapp 3020781	1	3.0	9.6	18.8
ÖLFLEX HEAT 1565 SC 1,5	Lapp 3013234	1,5	3,3	14.4	24.3
ÖLFLEX HEAT 1565 SC 2,5	Lapp 3020782	2,5	3,8	24.0	35.0
ÖLFLEX HEAT 1565 SC 4	Lapp 3018942	4	4,8	38.4	56.0
ÖLFLEX HEAT 1565 SC 6	Lapp 3020783	6	5,6	57.6	86.4
ÖLFLEX HEAT 1565 SC 10	Lapp 3016697	10	6,2	96.0	123.0
ÖLFLEX HEAT 1565 SC 16	Lapp 3016698	16	7,9	153.6	202.5
ÖLFLEX HEAT 1565 SC 25	Lapp 3016699	25	9,2	240.0	295.1
ÖLFLEX HEAT 1565 SC 35	Lapp 3016771	35	10,6	336.0	403.9
ÖLFLEX HEAT 1565 SC 50	Lapp 3017861	50	12,2	480.0	545.0

PERTRONIC CABLES SASA PERIC ROSENSTR.6 74239 HARDTHAUSEN TEL: 07139-507-8687 FAX: 07139-507-8680
www.pertronic-cables.com | sales@pertronic.eu | Skype PERTRONIC-CABLES | see you GOOGLE + PERTRONIC KABEL