



Description: ÖLFLEX HEAT 205 PTFE-FEP 4 X 0,75_

Lapp code: Lapp 30016373

The **Test voltage** of the cable Lapp 30016373 is C/C: 2500 V C/S: 2000 V.

Application range

- Conventional cables are not designed for use in environments with very high operating temperatures, heavy usage of chemical agents, or tight spaces
- Typical fields of application
 - Industrial furnace construction
 - Foundries
 - Chemical industry
 - Power plant engineering
 - Paint shop line technology
 - Heating elements
 - Polymer processing
 - Wind turbine engineering

Product Make-up

- Fine-wire, tinned-copper conductor
- PTFE-based core insulation
- Cores twisted together
- Tinned-copper braiding
- Outer sheath: FEP-based, white

In our Cable list on next page you can find all interesting information acc. article Lapp 30016373 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® HEAT 205 PTFE/FEP					
ÖLFLEX HEAT 205 PTFE/FEP 4 X 0,75	Lapp 30016373	4 X 0,75	5,9	49.0	78