



Description: ÖLFLEX HEAT 260 C MC 4 G 1,5_

Lapp code: Lapp 0091335

The **Test voltage** of the cable Lapp 0091335 is C/C: 2500 V C/S: 2000 V.

Application range

- Conventional cables are not designed for use in environments with very high operating temperatures, heavy usage of chemical agents, or tight spaces
- ÖLFLEX® HEAT 260 has proven to be an effective solution in harsh environments such as paint shop lines
- Typical fields of application
 - Industrial furnace construction
 - Foundries
 - Chemical industry
 - Power plant engineering
 - Paint shop line technology
 - Heating elements
 - Polymer processing
 - Wind turbine engineering

Product Make-up

- Fine-wire strand made of nickel-plated copper
- PTFE-based core insulation
- Cores twisted together
- Special wrapping
- Nickel-plated copper braiding
- PTFE-based outer sheath, black

In our Cable list on next page you can find all interesting information acc. article Lapp 0091335 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® HEAT 260 C MC					
ÖLFLEX HEAT 260 C MC 3 G 0,75	Lapp 0091330	3 G 0,75	5,5	46.0	75
ÖLFLEX HEAT 260 C MC 4 G 0,75	Lapp 0091331	4 G 0,75	5,9	51.0	87
ÖLFLEX HEAT 260 C MC 3 G 1	Lapp 0091332	3 G 1	5,8	48.0	81
ÖLFLEX HEAT 260 C MC 4 G 1	Lapp 0091333	4 G 1	6,4	65.0	104
ÖLFLEX HEAT 260 C MC 3 G 1,5	Lapp 0091334	3 G 1,5	6,3	65.0	101
ÖLFLEX HEAT 260 C MC 4 G 1,5	Lapp 0091335	4 G 1,5	7,2	86.0	134
ÖLFLEX HEAT 260 C MC 5 G 1,5	Lapp 0091336	5 G 1,5	7,8	105.0	162
ÖLFLEX HEAT 260 C MC 3 G 2,5	Lapp 0091337	3 G 2,5	7,9	114.0	160
ÖLFLEX HEAT 260 C MC 4 G 2,5	Lapp 0091338	4 G 2,5	8,7	140.0	204
ÖLFLEX HEAT 260 C MC 5 G 2,5	Lapp 0091339	5 G 2,5	9,4	209.0	270